

## BATCH CONTROLLERS

### S21IP65 - BATCH CONTROLLER WITH ADVANCED FUNCTIONS IN IP65 PROTECTED CASE

Metering system for use in the field.

Based on the [S21](#) batch controller housed in an ABS case protected to IP65.

The case features a transparent front aperture providing a full view of the batch controller displays.

All the control and programming keys are located on the outside.



#### [APPLICATION EXAMPLES](#)

#### TECHNICAL DATA

- Power supply :  
S21IP65-1-ST 115 / 230 Vac +/- 10% 50 / 60 Hz  
S21IP65-23-ST 24 Vdc-ac +/- 10%
- Power consumption : 10 VA
- Inputs : contact, reed, 2/3 wires NPN sensor, PNP sensor, 12/24 Vdc pulse, NAMUR sensor, photoelectric sensor and HALL effect sensor
- Outputs: 2 relays with 1 SPDT changeover 5 A 250 Vac (resistive load)
- Operating temp. : 0 / + 50 °C
- Humidity : 90 % a 40 °C (non-condensing)
- Case protection : IP65
- Dimensions (b x h x d) : 340 x 190 x 230 mm
- Weight : approx. 3 kg.

#### ORDERING CODES

Code	Power supply
<b>S21IP65-1-ST</b>	115 - 230 Vac
<b>S21IP65-23-ST</b>	24 Vdc-ac

*For more info please refer to the operating manual*

Characteristics can be subject to change without notice