

A chi di competenza
To whom it may concern

DICHIARAZIONE A LUNGO TERMINE DI ORIGINE PREFERENZIALE MERCI LONG-TERM SUPPLIER'S DECLARATION FOR PRODUCTS HAVING PREFERENTIAL ORIGIN

Si dichiara che i seguenti prodotti, con validità dal 01/01/2024 al 31/12/2024, sono di origine come specificato nelle pagine seguenti. Si certifica inoltre che tali prodotti sono conformi ai principi generali di sicurezza, alle norme Europee che li regolano e alla normativa CE e rispettano le norme di origine che disciplinano gli scambi preferenziali con.

It is hereby declared that the following products with validity from 01/01/2024 to 31/12/2024 are of origin as specified in the following pages. It is also certified that these products comply with the general principles of safety, the European standards governing them and the EC regulations, and comply with the rules of origin governing preferential trade with.

AL	Albania	GB	Great Britain	NI	Nicaragua	XK	Kosovo
BA	Bosnia-Erzegovina	GE	Georgia	NO	Norway	XL	Melilla
CA	Canada	GH	Ghana	PA	Panama	XS	Serbia
CAM	Cambodia	GT	Guatemala	PE	Peru	VN	VietNam
CH	Switzerland	HN	Honduras	PG	Papua Nuova Guinea	ZA	South Africa
CI	Ivory Coast	IL	Israel	PS	Occupied Territories	KR	Korea
CL	Chile	JO	Jordan	SC	Seychelles	UA	Ukraine
CO	Colombia	JP	Japan	SG	Singapore		CARIFORUM
CM	Cameroon	LB	Lebanon	SV	El Salvador		ESA COUNTRIES
CR	Costa Rica	LI	Liechtenstein	TN	Tunisia		SADC
DZ	Algeria	MA	Morocco	XC	Ceuta		WPS
EC	Ecuador	MD	Moldova				
EG	Egypt	ME	Montenegro				
FO	Faroer (Isole)	MK	North Macedonia				
IS	Island	MX	Mexico				

Si dichiara / We declare that

- Cumulo non applicato / *cumulation not applied*
 Cumulo applicato con / *cumulation applied with*

Sarà nostro impegno informarvi qualora la presente dichiarazione non sia più valida e mettere a disposizione delle autorità doganali eventuali ulteriori documenti giustificativi.

It will be our commitment to inform you if this declaration is no longer valid and to make any additional supporting documents available to the customs authorities.

Padova, 8/1/2024

Pierluigi Egidi

Managing Director

SENECA S.R.L.

Via Austria, 26 - 35127 PADOVA
Tel. 049.8705359 Fax 049.8706287
C.F.-P.IVA 02536650282

SENECA s.r.l.

Sede legale e operativa / Headquarters:
Via Austria, 26 - 35127 Padova (PD) - ITALY
T. +39 049 8705.359 - F. +39 049 8706.287
info@seneca.it - senecasrl@pec.it
www.seneca.it

Informazioni legali / Legal Notice

• C.F. / P.I. / VAT nr 02536650282
• Iscrizione camera commercio / Chamber of Commerce registration: C.C.I.A.A. PD N° 236346
• Iscrizione registro imprese / Company Register: Trib. PD 39486 Reg. Soc.
Capitale sociale i.v. / Paid-up capital € 2.500.000,00

Marchi e certificazioni / Marks and certificates

• S SENECA (SENECA s.r.l.) marchio europeo registrato European Community Mark with international registration [Nr. 1055079 - OHIM]
• Sistema di Qualità Certificato / Certified Quality System [ISO 9001 Nr. 9115.SENE]

Elenco dei prodotti allegato alla dichiarazione a lungo termine
Product list attached to the long term declaration

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
A					
A-169DV12	85291069	5A001	IT	Antenna 169MHz, dip. verticale lambda/2, BNC M, cavo 5 mt	169MHz vert.Dip. lambda/2 ant, BNC M, 5mt,low loss cable
A-169DV12-10	85291069	5A001	IT	Antenna 169MHz, dip. verticale lambda/2, BNC M, cavo 10 mt	169MHz vert.Dip. lambda/2 ant, BNC M, 10 mt,low loss cable
A-169DV14	85291069	5A001	IT	Ant. 169MHz, stilo vert.lambda/4, BNC M, L=450 mm	169MHz vert.Dip. lambda/4 ant, BNC M, L=450 mm
A-169DV16	85291069	5A001	IT	Antenna 169MHz, ¼ lambda, lunghezza 45 cm, + BNC M	169MHz vert.Dip. lambda/4 ant, BNC M
A-169YAGI	85291069	5A001	IT	Antenna 169MHz, Yagi a 3 elementi, BNC M, cavo 10 mt	169MHz 3 elem. Yagi Ant., BNC M, 10 mt, low loss cable
A-DIN-T201	85389099	5A001	IT	Aggancio in plastica da guida DIN per Serie T201	DIN rail plastic clip for T201 Series
A-GPS	85291069	5A001	IT	Antenna GPS esterna con base magnetica MMCX, cavo 3 mt	External GPS antenna - magnetic mount
A-GPS-SMA	85291069	5A001	IT	Antenna GPS con attacco SMA	GPS antenna with SMA connector
A-GSM	85291069	5A001	IT	Antenna esterna GSM dual band swing cavo 3,2 m	Dual band swing GSM external antenna, cable 3,2 m, SMA
A-GSM-DIR-5M	85291069	5A001	IT	Antenna direz. triband GSM-DECT-UMTS SMA-M,cavo 5 mt	GSM-DECT-UMTS directive compact antenna
A-GSM-MG	85291069	5A001	IT	Antenna esterna magnetica dual band SMA cavo 2,5 mt	External magnetic dual band antenna SMA 4 dbi, cable 2,5 mt
A-GSM-OMNIDIR	85291069	5A001	IT	Antenna Omnidir. GSM-UMTS-WIFI, 5.1 dB, SMA-M cavo 5 mt	GSM-UMTS-WIFI Omnidirectional Antenna
A-GSM-OMNIDIR-10	85291069	5A001	IT	Antenna Omnidir. GSM-UMTS-WIFI, 5.1 dB, SMA-M cavo 10 mt	GSM-UMTS-WIFI Omnidirectional Antenna, L=10 m
A-GSM-QUAD-N	85291069	5A001	IT	Antenna esterna omnidirezionale 4G/Wi-Fi, FME, cavo 5 mt	4G/WiFi omnidirectional antenna, FME, L=5mt
ALIM-MY2	85044090	EAR99	IT	Alimentatore 230 V / 12 V per MYALARM2 e R-KEY-LT	Power Supply Unit for MYALARM2 and R-KEY-LT
ALIM-MY2-12-24	85044090	EAR99	IT	Alimentatore MyBoat 24V	MyBoat 24V power supply unit
ALIM-USB-1A	85044090	EAR99	IT	Alimentatore stabilizzato 5V 1A con porta USB-A	Stabilised power supply 5V 1A with USB-A port
A-SCR-90	85291069	5A001	IT	Antenna/spare part con montaggio a vite a 90° su connettore SMA	Antenna/spare part with 90° screw mounting on SMA connector
A-STIL	85291069	5A001	IT	Antenna stilo GSM 90° SMA-M	GSM stilo antenna for M-RTU
A-STIL-D	85291069	5A001	IT	Antenna stilo GSM stilo diritta SMA-M	Straight GSM Antenna for MY2
A-STIL-4G	85291069	5A001	IT	Antenna stilo 4G LTE diritta SMA-M, ricambio serie MYALARM	MyALARM 4G LTE straight SMA-M stylus antenna
B					
B-ALARM	85176200	5A991	IT	Unità di teleallarme 1DI / 1DO, funzioni di base	Remote alarm Unit, 1DI / 1DO, basic functions
BATT-2S	85076000	3A226	IT	Pacco doppio batterie litio3 celle 11,1 V - 14,5 Ah	Double battery pack 3 cell 11,1 V - 14,5 Ah
BATT-GP80	85076000	3A226	IT	Batteria di ricambio per B-ALARM	B-ALARM spare part battery
BATT-MY2	85076000	3A226	IT	Batteria lito 3,7V - 1.200mAh per MYALARM2	Lithium Polymer (LiPo) Battery Pack 3.7V - 1200mAh for MY2
BATT-S	85076000	3A226	IT	Pacco singolo batterie litio3 celle 11,1 V - 14,5 Ah	Single battery pack 3 cell 11,1 V - 14,5 Ah
BOX-RTU-IP65	85389091	5A991	IT	Cassetta IP65 con supporto installazione batterie	IP65 junction box with fixing support
C					
CE-RJ45-RJ45-C	85444290	0A606	IT	Cavo Ethernet incrociato (RJ45 / RJ45) 1,5 MT	Crossover Ethernet cable (RJ45-RJ45)
CE-RJ45-RJ45-R	85444290	0A606	IT	Cavo Ethernet diritto (RJ45 / RJ45) 1,5 MT	Straight-thru Ethernet cable (RJ45-RJ45)
COMPOSITOR	-	2D002	IT	Tool di configurazione e test per convertitori f.o.	Test and programming toolkit for fiber optic converters
CS-DB9F-CFV10	85444290	0A606	IT	Cavo di collegamento RS232 (DB9F-CFV10) per M-RTU	RS232 connection cable (DB9F-CFV10)
CS-DB9F-CLAMP	85444290	0A606	IT	Cavo ser. RS485 (DB9F / morsetti) 1,5 MT - VISUAL/Z-FLOW	RS485 conn. cable (DB9F-Clamps) for VISUAL
CS-DB9F-DB25M	85444290	0A606	IT	Cavo seriale colleg. S21N - Stampante a impatto FH190-24	Serial connection cable S21N - FH190-24
CS-DB9F-DB9F	85444290	0A606	IT	Cavo seriale RS232 (DB9F / DB9F)	RS232 serial connection cable (DB9F / DB9F)
CS-DB9F-TIP	85444290	0A606	IT	Cavo di comunicazione K107B RS232 (DB9F - puntali)	RS232 communication cable (DB9F - tips)
CS-DB9F-TIP-V	85444290	0A606	IT	Cavo seriale RS485 (DB9F / puntali) 1,5 MT - VISUAL1/2/3	RS485 serial conn. cable (DB9F - tips) for VISUAL1/2/3

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
CS-DB9M-DB9F	85444290	0A606	IT	Cavo seriale RS232 diritto per prog. (DB9M / DB9F)	RS232 straight thru programming cable (DB9M - DB9F)
CS-DB9M-DB9F-CR	85444290	0A606	IT	Cavo seriale firmware 2mt [DB9M / DB9F) per RTU-LP	Update firmware serial cable (DB9M / DB9F) for RTU-LP
CS-DB9M-DB9M	85444290	0A606	IT	Cavo seriale RS232 (DB9M / DB9M)	RS232 serial connection cable (DB9M - DB9M)
CS-DB9M-MEF-1012	85444290	0A606	IT	Cavo com.seriale Z-KEY (DB9M / MEF 10-12) 1,5 MT	Serial commun. cable (DB9M / MEF 10-12) for Z-KEY
CS-DB9M-MEF-PH	85444290	0A606	IT	Cavo com. seriale (DB9M / MEF PH) 3 fili 1,5 MT	Serial comm. cable (DB9M / MEF 10-12) 3 wires, 1,5 mt
CS-DB9M-TIP	85444290	0A606	IT	Cavo seriale RS485 per radiomodem (DB9M / Puntali)	RS485 serial connection cable (DB9M - tips)
CS-DB9M-TIP-V	85444290	0A606	IT	Cavo seriale RS485 (DB9M / puntali) per HMI VISUAL4	RS485 serial conn. cable (DB9M - tips) for VISUAL4
CS-JACK-DB9F	85444290	0A606	IT	Cavo seriale di programmazione (Jack / DB9F)	Serial programming cable (Jack / DB9F)
CS-JACK-JACK	85444290	0A606	IT	Cavo di programmazione Z109REG2 / Test-3 (Jack / Jack)	Programming cable Z109REG2 (Jack / Jack)
CS-RJ10-AMP	85444290	0A606	IT	Cavo prog. T120/T121/ K120RTD/K121/K111/MY2 (RJ10 / AMP MODU II 4 F)	Programm. cable T120/T121/ K120RTD/K121/K111/MY2
CS-RJ10-DB25M-1	85444290	0A606	IT	Cavo comunicazione modem (RJ10 / DB25M)	Communication cable for modem (RJ10 / DB25M)
CS-RJ10-DB25M-2	85444290	0A606	IT	Cavo comunicazione modem e HMI (RJ10 / DB25M)	Comm. cable for modem and oper. panels (RJ10 / DB25M)
CS-RJ10-DB9F	85444290	0A606	IT	Cavo seriale RS232 (RJ10 / DB9F)	RS232 serial connection cable (RJ10 / DB9F)
CS-RJ10-DB9M	85444290	0A606	IT	Cavo seriale modem (RJ10 / DB9M)	Modem serial connection cable (RJ10 / DB9M)
CS-RJ10-TIP	85444290	0A606	IT	Cavo comunicazione seriale (RJ10/ 4 Puntali) mt 1,5	Serial communication cable (RJ10 / 4 tips) 1,5 mt
CS-TIP-MEF-PH	85444290	0A606	IT	Cavo com. seriale (Puntali /Connettore 4 vie)	Serial communication cable (tips/4-ways connector)
CS-TPW-TIP	85444290	0A606	IT	Cavo seriale RS485 Tp-wire (Tp-wire / Puntali)	RS485 Tp-Wire serial cable (Tp-Wire / tips)
CS-TPW-TPW	85444290	0A606	IT	Cavo Tp-Wire (Tp-wire / Tp-wire)	Tp-Wire cable (Tp-Wire / Tp-Wire)
CU-A-MICROB	85444290	0A606	IT	Cavo plug USB-A Micro USB-B 5P (KIT-USB, MY2, Z109REGBP)	USB-A Micro USB-B 5 P plug cable
CU-A-MICRO-OTG	85444290	0A606	IT	Cavo adattatore Micro USB OTG – USB Tipo A femmina	Micro USB OTG to USB Type A (female) Adapter Cable
CU-A-MINIB-1	85444290	0A606	IT	Cavo plug USB-A Mini USB-B 5 P, 1 mt	USB-A Mini USB-B 5 P plug cable, 1 mt
CU-A-MINIB-2	85444290	0A606	IT	Cavo plug USB-A Mini USB-B 5 P, 2 mt	USB-A Mini USB-B 5 P plug cable, 2 mt
D					
DR-02	85235110	EAR99	IT	Software DAQ "Data Recorder" 2 canali	2-CH DAQ Software
DR-04	85235110	EAR99	IT	Software DAQ "Data Recorder" 4 canali	4-CH DAQ Software
DR-04-PLUS	85235110	EAR99	IT	Software DAQ "Data Recorder" 4 canali + pacchetto plus (multi-client)	4-CH Data Recorder+ multi-client
DR-08	85235110	EAR99	IT	Software DAQ "Data Recorder" 8 canali	8-CH DAQ Software
DR-08-PLUS	85235110	EAR99	IT	Software DAQ "Data Recorder" 8 canali + pacchetto plus (multi-client)	8-CH Data Recorder+ multi-client
DR-16	85235110	EAR99	IT	Software DAQ "Data Recorder" 16 canali	16-CH DAQ Software
DR-16-PLUS	85235110	EAR99	IT	Software DAQ "Data Recorder" 16 canali + pacchetto plus (multi-client)	16-CH Data Recorder+multi-client
DR-32	85235110	EAR99	IT	Software DAQ "Data Recorder" 32 canali	32-CH DAQ Software
DR-32-PLUS	85235110	EAR99	IT	Software DAQ "Data Recorder" 32 canali + pacchetto plus (multi-client)	32-CH Data Recorder+multi-client
DR-64	85235110	EAR99	IT	Software DAQ "Data Recorder" 64 canali	64-CH DAQ Software
DR-64-PLUS	85235110	EAR99	IT	Software DAQ "Data Recorder" 64 canali + pacchetto plus (multi-client)	64-CH Data Recorder+multi-client
DR-UN	85235110	EAR99	IT	Software DAQ "Data Recorder" canali illimitati	Unlimited-CH DAQ Software
DR-UN-PLUS	85235110	EAR99	IT	Data Recorder canali illimitati + pacchetto plus (multi-client)	Unlimited-CH Data Recorder+multi-client
DR-UPGRADE	-	2D002	IT	Data Recorder pacchetto upgrade	Data Recorder license upgrade service
D-USB	85235110	EAR99	IT	Driver USB (S107USB, K107USB, EASY USB, S117P1)	USB drivers (S107USB, K107USB, EASY-USB, S117P1)
E					
EASY CEI	-	2D002	IT	Software di gestione MYALARM2 CEI	MYALARM2 CEI Management Software.
EASY LOG VIEWER	-	2D002	IT	Software DAQ e visualizz. dati per datalogger GSM/GPRS	DAQ and data visualization software for smart datalogger

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
EASY LP	-	2D002	IT	Raccolta configuratore plug&play strumenti loop powered	Plug&play suite instrument configurator loop powered
EASY MYALARM2	-	2D002	IT	Configuratore MYALARM2	MYALARM2 configurator
EASY RTU LP	-	2D002	IT	RTU-LP devices software configurator	RTU-LP devices software configurator
EASY SETUP	-	2D002	IT	Suite configuratori strumenti programmabili SENECA	SENECA Programmable Instrument Configurator Suite
EASY SETUP APP	-	2D002	IT	App iOS / Android Suite Completa EASY SETUP	EASY SETUP full App iOS / Android Suite
EASY SETUP2	-	2D002	IT	Suite configuratori strumenti programmabili SENECA	SENECA Programmable Instrument Configurator Suite
EASY Z-KEY	-	2D002	IT	Tool di configurazione indirizzo IP Z-KEY	Z-KEY IP address configuration tool
EASYFLOWCOMPUTER	-	2D002	IT	Software di gestione Z-FLOWCOMPUTER	Z-FLOWCOMPUTER Management Software
EASY-USB	85437090	EAR99	IT	Convertitore USB - UART TTL con software di programmazione	USB to UART TTL converter with programming software
EB PRO	-	2D002	TW	Software di configurazione pannelli operatore VISUAL	VISUAL Series operator panel configuration software
EDS	-	2D002	IT	Raccolta file EDS per moduli I/O CANopen	EDS file collection for CANopen I/O modules
E-M-BUS PACK	-	2D002	IT	Software di gestione contatori energia Serie S500 - M-BUS	M-BUS S500 Series Energy Meter Management Software
E-MODBUS PACK	-	2D002	IT	Software di gestione contatori energia Serie S500 - Modbus / Ethernet	Modbus/Ethernet S500 Series Energy Meter Management Software
E-POWER PACK	-	2D002	IT	Software di gestione analizzatori di rete Serie S604	S604 Series Power Meter Management Software
F					
FD01	85389091	EAR99	IT	Fotorilevatore "pulsecap" per conteggio impulsi, max freq 10 Hz	Pulsecap" photodetector for pulse counting, max freq 10 Hz
FH190-24	84433900	EAR99	IT	Stampante a impatto 24 colonne per batch controller S20N1/S21N1, alim. 9-40 Vdc	24-column impact printer for batch controller S20N1/S21N1, power supply 9-40 Vdc
FO TEST	-	2D002	IT	Software test automatico per convertitori fibra ottica	Automatic test software for fiber optic converters
I					
iMC784SHENN	90303900	EAR99	SI	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT
iMC784SHEPISANN	90303900	EAR99	SI	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DI, 2AI, 2DO, 2AO	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DI, 2AI, 2DO, 2AO
iMC784SHESNN	90303900	EAR99	SI	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DO	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DO
iMC784SHSEPISANN	90303900	EAR99	SI	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT, EN61850; 2DI, 2AI, 2DO, 2AO	PQA TFT 5.7"; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT, EN61850; 2DI, 2AI, 2DO, 2AO
K					
K107A	85437090	EAR99	IT	Amplificatore seriale RS485/RS485 isolato - alim. 24 Vdc	RS485 <-> RS485 serial amplifier/Isolator
K107B	85437090	EAR99	IT	Convertitore seriale RS232/RS485 isolato - alim. 24 Vdc	RS232 <-> RS485 serial converter/Isolator
K107USB	85437090	EAR99	IT	Convertitore USB - RS485	USB <-> RS485 converter / Isolator
K109LV	85437090	EAR99	IT	Isolatore convertitore shunt, 24 Vdc, 6,2 mm	mV to DC Current/Voltage Isolator/Converter
K109PT	85437090	EAR99	IT	Convertitore optoisolato PT100 / V-mA, 24 Vdc, 6,2 mm	PT100 to DC Current/Voltage Isolator/Converter
K109PT1000	85437090	EAR99	IT	Convertitore optoisolato PT1000 / V-mA, 24 Vdc, 6,2 mm	PT1000 to DC Current/Voltage Isolator/Converter
K109PT-HPC	85437090	EAR99	IT	Convertitore optoisolato PT100 / V-mA ad alta precisione, 24 Vdc, 6,2 mm	PT100 to DC Current/Volt. Isol/Conv. High prec.
K109S	85437090	EAR99	IT	Isolatore galvanico - alim. 24 Vdc, 6,2 mm	DC Current/Voltage to DC Current/Voltage Converter
K109TC	85437090	EAR99	IT	Convertitore TC / V-mA - alim. 24 Vdc, 6,2 mm	TC to DC Current/Volt. Isolator/Converter-with alarm
K109UI	85437090	EAR99	IT	Convertitore V-mA / V-mA - alim. 24 Vdc, 6,2 mm	DC Current/Volt. to DC Current/Volt. Isolator/Converter
K111	85437090	EAR99	IT	Soglia di frequenza con 2 uscite isolate	Isolated dual output frequency trip amplifier
K111-C	85437090	EAR99	IT	Soglia di frequenza con 2 uscite isolate - configurata	Isolated dual output frequency trip amplifier - config.
K111D	85437090	EAR99	IT	Divisore ripetitore di frequenza con due uscite isolate	2-CH frequency divider-repeater with 2 isolated outputs
K111D-C	85437090	EAR99	IT	Divisore ripetitore di frequenza con due uscite isolate configurato	2-CH frequency divider-repeater with 2 isolated outputs, config.
K112	85437090	EAR99	IT	Accoppiatore digitale isolato a doppio canale di uscita	Universal digital Coupler/Isolator
K120RTD	85437090	EAR99	IT	Convertitore di RTD loop powered non isolato 4..20mA	Pt100, Ni100 loop powered converter
K120RTD-C	85437090	EAR99	IT	Convertitore di RTD loop powered non isolato configurato	Pt100, Ni100 loop powered converter, config.

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
K121	85437090	EAR99	IT	Convertitore universale optoisolato loop powered, Atex Zona 2	Universal isolator converter loop powered
K121-C	85437090	EAR99	IT	Convertitore universale optoisolato loop powered, Atex Zona 2, preconfigurato	Universal isolator converter loop powered - config.
K400CL	85363030	EAR99	DE	Protezione sovratensioni 25VAC/36VDC, C1/2/3/D1 per segnali analogici e digitali	Analog and Digital Signals Surge Protection, 6,2 slim
K400CL-10	85363030	EAR99	DE	Kit 10 p.zi prot. sovrat. K400CL-1	K400CL-1 10 pieces kit
K-BUS	85371098	EAR99	IT	Connettore 2 slot guida DIN 35 mm per alim. rapida	Expandable power supply connector
KIT-USB	85235110	2D002	IT	Kit programmazione per strumenti con interfaccia USB (Cavo USB + CD)	Programming toolkit for USB interface instruments
K-SUPPLY	85044090	EAR99	IT	Modulo alim. con protezioni elettroniche della linea	Redundant power supply module for K-Line modules
L					
LOG FACTORY	-	2D002	IT	Tool di visualizzazione e archiviazione dati	Visualization and log data tool
LS-C	-	2D002	IT	Librerie SENECA - CoDeSys	SENECA - CoDeSys libraries
LS-S	-	2D002	IT	Librerie SENECA - Straton	SENECA - Straton libraries
LS-VI	-	2D002	IT	Librerie SENECA - LabVIEW Driver VI	SENECA - LabVIEW Driver VI libraries
M					
MC784SHENN	90303900	EAR99	SI	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT
MC784SHEPISANN	90303900	EAR99	SI	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DI, 2AI, 2DO, 2AO	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DI, 2AI, 2DO, 2AO
MC784SHESNN	90303900	EAR99	SI	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DO	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT; 2DO
MC784SHSEPISANN	90303900	EAR99	SI	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT, EN61850; 2DI, 2AI, 2DO, 2AO	PQA 128x64 graphic display; 80..300 Vdc; 80..276 Vac; Ethernet/USB; ModBus, DNP3, FFtp, MQTT, EN61850; 2DI, 2AI, 2DO, 2AO
MSC	90303100	EAR99	IT	Calibratore bluetooth multifunzione	Multifunction bluetooth calibrator
MSC BY SENECA	-	-	IT	App di gestione MSC	MSC management mobile App
MSC DESKTOP	-	2D002	IT	Software di esportazione dati e aggiornamento firmware MSC	MSC data export and firmware update
MSC-POWER	85044090	EAR99	IT	Alimentatore MSC	MSC Power Supply
MSC-T	-	2D002	IT	Rapporto di taratura MSC	MSC Calibration Report
MSD	85235110	EAR99	IT	Micro SD memory card con adattatore	Micro SD memory card with adapter
MY2B-0-0-M-B	85176200	5A991	IT	Unità di teleallarme, base / datalogger, morsetti, blu	Remote Alarm Unit - basic version, no relay, clamps, blue color
MY2B-0-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, base / datalogger, morsetti, blu, Custodia IP66	Remote Alarm Unit - basic, no relay, clamps, blue, IP66 case
MY2B-0-0-M-G	85176200	5A991	IT	Unità di teleallarme, base / datalogger, morsetti, grigio	Remote Alarm Unit - basic version, no relay, clamps, grey color
MY2B-0-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, base / datalogger, morsetti, grigio, Custodia IP66	Remote Alarm Unit - basic, no relay, clamps, grey, IP66 case
MY2B-R-0-M-B	85176200	5A991	IT	Unità di teleallarme, base / datalogger, relè, morsetti, blu	Remote Alarm Unit - basic version, relay, clamps, blue color
MY2B-R-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, base / datalogger, relè, morsetti, blu, Cust. IP66	Remote Alarm Unit - basic, relay, clamps, blue, IP66 case
MY2B-R-0-M-G	85176200	5A991	IT	Unità di teleallarme, base / datalogger, relè, morsetti, grigio	Remote Alarm Unit - basic version, relay, clamps, grey color
MY2B-R-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme base / datalogger, relè, morsetti, grigio, Cust. IP66	Remote Alarm Unit - basic, relay, clamps, grey, IP66 case
MY2CEI-016-0-220	85176200	EAR99	IT	Unità di teledistacco CEI 0-16, ant. integrata, alim. 220Vac - 12Vdc	Remote Discharge Unit, built-in antenna, 220 Vac - 12 Vdc
MY2CEI-016-0-24	85176200	EAR99	IT	Unità di teledistacco CEI 0-16, ant.a integrata, alim. 24Vdc - 12Vdc	Remote Discharge Unit, built-in antenna, 24 Vac - 12 Vdc
MY2CEI-016-A-220	85176200	EAR99	IT	Unità di teledistacco CEI 0-16, ant. est. A-GSM, alim. 220Vac - 12Vdc	Remote Discharge Unit, A-GSM, 220 Vac - 12 Vdc
MY2CEI-016-A-24	85176200	EAR99	IT	Unità di teledistacco CEI 0-16, ant. est. A-GSM, alim. 24Vdc - 12Vdc	Remote Discharge Unit, A-GSM, 24 Vac - 12 Vdc
MY2-CONV24-12	85044090	EAR99	TW	Convertitore DC DC 24 -> 12 V per MY2, MY3, MYCEI, MYSEAL	DC DC converter 24 -> 12 V for MY2, MY3, MYCEI, MYSEAL
MY2G-0-0-M-B	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, morsetti, blu	MyALARM2 - gps version, no relay, clamps, blue color
MY2G-0-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, morsetti, blu, IP66	MyALARM2 - gps, no relay, clamps, blue, IP66 case
MY2G-0-0-M-G	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, morsetti, grigio	MyALARM2 - gps version, no relay, clamps, grey color

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
MY2G-0-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, morsetti, grigio, IP66	MyALARM2 - gps, no relay, clamps, grey, IP66 case
MY2G-R-0-M-B	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, relè, morsetti, blu	MyALARM2 - gps version, relay, clamps, blue color
MY2G-R-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, relè, morsetti, blu, IP66	MyALARM2 -gps, relay, clamps, blue, IP66 case
MY2G-R-0-M-G	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, relè, morsetti, grigio	MyALARM2 - gps version, relay, clamps, grey color
MY2G-R-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, relè, morsetti, grigio, IP66	MyALARM2 - gps, relay, clamps, grey, IP66 case
MY2GL-0-0-M-B	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, morsetti, custodia blu	Remote alarm unit, GPS, 4G/LTE, clamps, blue case
MY2GL-0-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, morsetti, custodia blu IP66	Remote alarm unit, GPS, 4G/LTE, clamps, IP66 blue case
MY2GL-0-0-M-G	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, morsetti, custodia grigia	Remote alarm unit, GPS, 4G/LTE, clamps, gray case
MY2GL-0-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, morsetti, custodia grigia IP66	Remote alarm unit, GPS, 4G/LTE, clamps, IP66 gray case
MY2GL-R-0-M-B	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, relè, morsetti, custodia blu	Remote alarm unit, GPS, 4G/LTE, relays, clamps, blue case
MY2GL-R-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, relè, morsetti, custodia blu IP66	Remote alarm unit, GPS, 4G/LTE, relays, clamps, IP66 blue case
MY2GL-R-0-M-G	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, relè, morsetti, custodia grigia	Remote alarm unit, GPS, 4G/LTE, relays, clamps, gray case
MY2GL-R-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, GPS, 4G/LTE, relè, morsetti, custodia grigia IP66	Remote alarm unit, GPS, 4G/LTE, relays, clamps, IP66 gray case
MY2-KITIP66	85369095	5A991	IT	KIT ABS per montaggio rapido, protezione IP66	IP66 ABS kit enclosure for field application
MY2S-0-0-M-B	85176200	5A991	IT	Unità di teleallarme, security audio, SD card, morsetti, blu	Remote alarm unit- security, no relay, clamps, blue color
MY2S-0-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, security audio, SD card, morsetti, blu, Cust. IP66	Remote alarm unit - security, no relay, clamps, blue, IP66 case
MY2S-0-0-M-G	85176200	5A991	IT	Unità di teleallarme, versione GPS, SD card, morsetti, grigio	Remote alarm unit - security, no relay, clamps, grey color
MY2S-0-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, security audio, SD card, morsetti, grigio, Cust. IP66	Remote alarm unit - security, no relay, clamps, grey, IP66 case
MY2S-R-0-M-B	85176200	5A991	IT	Unità di teleallarme, security audio, SD card, relè, morsetti, blu	Remote alarm unit - security, relay, clamps, blue color
MY2S-R-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, security audio, SD card, relè, morsetti, blu, IP66	Remote alarm unit -security, relay, clamps, blue, IP66 case
MY2S-R-0-M-G	85176200	5A991	IT	Unità di teleallarme, security audio, SD card, relè, morsetti, grigio	Remote alarm unit - security, relay, clamps, grey color
MY2S-R-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, security audio, SD card, relè, morsetti, grigio, IP66	Remote alarm unit - security, relay, clamps, grey, IP66 case
MY2SL-0-0-M-B	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, morsetti, custodia blu	Remote alarm unit, security audio, 4G/LTE, clamps, blue case
MY2SL-0-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, morsetti, custodia blu IP66	Remote alarm unit, security audio, 4G/LTE, clamps, IP66 blue case
MY2SL-0-0-M-G	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, morsetti, custodia grigia	Remote alarm unit, security audio, 4G/LTE, clamps, gray case
MY2SL-0-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, morsetti, custodia grigia IP66	Remote alarm unit, security audio, 4G/LTE, clamps, IP66 gray case
MY2SL-R-0-M-B	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, relè, morsetti, custodia blu	Remote alarm unit, security audio, 4G/LTE, relays, clamps, blue case
MY2SL-R-0-M-B-4X	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, relè, morsetti, custodia blu IP66	Remote alarm unit, security audio, 4G/LTE, relays, clamps, IP66 blue case
MY2SL-R-0-M-G	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, relè, morsetti, custodia grigia	Remote alarm unit, security audio, 4G/LTE, relays, clamps, gray case
MY2SL-R-0-M-G-4X	85176200	5A991	IT	Unità di teleallarme, security audio, 4G/LTE, relè, morsetti, custodia grigia IP66	Remote alarm unit, security audio, 4G/LTE, relays, terminals, IP66 gray case
MY3C-1Y	-	2D002	IT	Rinnovo Servizio Cloud 12 mesi MyAlarm3 Cloud	12-month MyAlarm3 Cloud Service Renewal
MY3CLOUD-APP	-	2D002	IT	App di gestione iOS / Android MyAlarm3 Cloud	iOS / Android MyAlarm3 Cloud management app
MY3CLOUD-R-0-0-G	85176200	5A991	IT	Unità di teleallarme supporto Cloud, relè, colore grigio	Remote Alarm Unit, Cloud support, relay, grey color
MY3CLOUD-R-0-G-G	85176200	5A991	IT	Unità di teleallarme supporto Cloud, relè, GPS, colore grigio	Remote Alarm Unit, Cloud support, relay, GPS, grey color
MY3CL-R-0-0-G	85176200	5A991	IT	Unità di teleallarme supporto Cloud, 4G/LTE, relè, colore grigio	Remote Alarm Unit, Cloud support, 4G/LTE, relay, grey color
MY3CL-R-0-G-G	85176200	5A991	IT	Unità di teleallarme supporto Cloud, relè, 4G/LTE, GPS, colore grigio	Remote Alarm Unit, Cloud support, 4G/LTE, relay, GPS, grey color
MY-PT-150-3	90251900	EAR99	IT	Trasmettitore portatile per PT100 con PT-150-3-M12	PT100 handheld transmitter with PT-150-3-M12 probe
MY-PT-150-3R	90251900	EAR99	IT	Trasmettitore portatile per PT100 con PT-150-3R-M12	PT100 handheld transmitter with PT-150-3R-M12 probe
MY-PT-250-2	90251900	EAR99	IT	Trasmettitore portatile per PT100 con PT-250-2-M12	PT100 handheld transmitter with PT-250-2-M12 probe
MY-PT-KIT	90251900	EAR99	IT	Trasmettitore portatile per PT100 con 3 sonde PT	PT100 hand. trans. kit with PT-150-3, PT-250-2, PT-150-3R

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
MY-SEAL-0-0-0-B	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, colore blu	Remote datalogger with SEAL control logic, blue color
MY-SEAL-0-0-0-G	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, colore grigio	Remote datalogger with SEAL control logic, grey color
MY-SEAL-0-0-0-G-B	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, modulo GPS, colore blu	Remote datalogger with SEAL control logic, GPS receiver, blue color
MY-SEAL-0-0-0-G-G	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, modulo GPS, colore grigio	Remote datalogger with SEAL control logic, GPS receiver, grey color
MY-SEAL-R-0-0-B	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, scheda relè, colore blu	Remote datalogger with SEAL control logic, relay board, blue color
MY-SEAL-R-0-0-G	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, scheda relè, colore grigio	Remote datalogger with SEAL control logic, relay board, grey color
MY-SEAL-R-0-0-G-B	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, scheda relè, modulo GPS, colore blu	Remote datalogger with SEAL control logic, relay board, GPS receiver, blue color
MY-SEAL-R-0-0-G-G	85176200	5A991	IT	Datalogger remoto con logica programmabile SEAL, scheda relè, modulo GPS, colore grigio	Remote datalogger with SEAL control logic, relay board, GPS receiver, grey color
MY-TC-250-1.5	90251900	EAR99	IT	Trasmettitore portatile per termocoppia con 2 sonde TCK	TC hand. Trans. with TCK-250-1,5-M12 and TCK-W-1000-M12
MY-TC-250-3	90251900	EAR99	IT	Trasmettitore portatile per termocoppia con sonda TCK	TC hand. trans. with TCK-250-3-M12 and TCK-W-1000-M12
MY-TC-AC	90251900	EAR99	IT	Trasmettitore portatile per termocoppia con 2 sonde TCK	TC hand. Trans. with TCK-AC-M12 and TCK-W-1000-M12
MY-TC-KIT	90251900	EAR99	IT	Trasmettitore portatile per termocoppia con 4 sonde TCK	TC hand. Trans. Kit with Seneca handled termocouples
MY-UT	90251900	EAR99	IT	Trasmettitore portatile temp./umidità con sonda UT-M12	Temp./Relat. Humidity hand. Trans. with UT-M12 probe
N					
NTC-150	90251900	EAR99	IT	Sonda NTC esterna 1,5 m per MyALARM2	External NTC probe, 1,5 m, for MyALARM2
P					
PCCV150	85044090	0A606	IT	Cavo di alimentazione con connettore per stampante ad aghi FH190-24	Power cord with connector for FH190-24 dot matrix printer
PIV APP	-	2D002	IT	App Android per conf. sonde portali MY-PT, MY-TC, MY-UT	App Android for handheld probes (MY-PT, MY-TC, MY-UT)
POZZ-100	90259000	EAR99	IT	Pozzetto Inox att. 1/2" GM per PT100 L=100mm	Weld-in thermowell, length 100 mm
POZZ-150	90259000	EAR99	IT	Pozzetto Inox att. 1/2" GM per PT100 L=150mm	Weld-in thermowell, length 150 mm
POZZ-200	90259000	EAR99	IT	Pozzetto Inox att. 1/2" GM per PT100 L=200mm	Weld-in thermowell, length 200 mm
POZZ-250	90259000	EAR99	IT	Pozzetto Inox att. 1/2" GM per PT100 L=250mm	Weld-in thermowell, length 250 mm
POZZ-300	90259000	EAR99	IT	Pozzetto Inox att. 1/2" GM per PT100 L=300mm	Weld-in thermowell, length 300 mm
POZZ-50	90259000	EAR99	IT	Pozzetto Inox att. 1/2" GM per PT100 L=50mm	Weld-in thermowell, length 50 mm
PT100-100	90251900	EAR99	IT	Pt100 L=100 mm 3 fili testa stagna att. 1/2" G.M.	Pt100 std length 100 mm
PT100-100-MA	90251900	EAR99	IT	Pt100 L=100 mm 3 fili testa stagna att. 1/2" G.M. 4-20 mA	Pt100 std length 100 mm, 4-20 mA output
PT100-150	90251900	EAR99	IT	Pt100 L=150 mm 3 fili testa stagna att. 1/2" G.M.	Pt100 std length 150 mm
PT100-150-MA	90251900	EAR99	IT	Pt100 L=150 mm 3 fili testa stagna att. 1/2" G.M. 4-20 mA	Pt100 std length 150 mm, 4-20 mA output
PT100-200	90251900	EAR99	IT	Pt100 L=200 mm 3 fili testa stagna att. 1/2" G.M.	Pt100 std length 200 mm
PT100-200-MA	90251900	EAR99	IT	Pt100 L=200 mm 3 fili testa stagna att. 1/2" G.M. 4-20 mA	Pt100 std length 200 mm, 4-20 mA output
PT100-250	90251900	EAR99	IT	Pt100 L=250 mm 3 fili testa stagna att. 1/2" G.M.	Pt100 std length 250 mm
PT100-250-MA	90251900	EAR99	IT	Pt100 L=250 mm 3 fili testa stagna att. 1/2" G.M. 4-20 mA	Pt100 std length 250 mm, 4-20 mA output
PT100-300	90251900	EAR99	IT	Pt100 L=300 mm 3 fili testa stagna att. 1/2" G.M.	Pt100 std length 300 mm
PT100-300-MA	90251900	EAR99	IT	Pt100 L=300 mm 3 fili testa stagna att. 1/2" G.M. 4-20 mA	Pt100 std length 300 mm, 4-20 mA output
PT100-50	90251900	EAR99	IT	Pt100 L=50 mm 3 fili testa stagna att. 1/2" G.M.	Pt100 std length 50 mm
PT100-50-MA	90251900	EAR99	IT	Pt100 L=50 mm 3 fili testa stagna att. 1/2" G.M. 4-20 mA	Pt100 std length 50 mm, 4-20 mA output
PT100-A	90251900	EAR99	IT	Termoresistenza aria-ambiente IP66 standard	Atmosphere PT100
PT100-A-MA	90251900	EAR99	IT	Termoresistenza aria-ambiente IP66 uscita 4-20 mA	Atmosphere PT100, 4-20 mA output
PT100-SOLAR	90251900	EAR99	IT	PT100 solare con piastrina 25x25x3 mm, cavo 3 m	Single element 3 wires Pt100 for photovoltaic modules
PT100-SOLAR-MA	90251900	EAR99	IT	Sonda di temperatura moduli fotovoltaici, uscita 4-20mA	Single element Pt100 for PV modules, out 4-20 mA
PT-150-3-M12	90251900	EAR99	IT	PT100 classe B, d=3 mm, L= 150 mm, attacco M12	PT100 class B, d=3 mm, L= 150 mm, M12 connector

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
PT-150-3R-M12	90251900	EAR99	IT	PT100 classe B, d=3 mm, L= 150 mm, term. rastr. att. M12	PT100 class B, d=3 mm, L= 150 mm, tapered terminal, M12
PT-250-2-M12	90251900	EAR99	IT	PT100 classe B, d=2 mm, L= 250 mm, attacco M12	PT100 class B, d=2 mm, L= 250 mm, M12 connector
R					
R-16DI-8DO	85389091	EAR99	IT	Modulo 16 DI / 8 DO a relè Modbus TCP-IP / Modbus RTU (2 ETH)	16-CH digital inputs / 8-CH digital relay outputs Modbus TCP-IP / Modbus RTU module (2 ETH)
R-16DI-8DO-P	85389091	EAR99	IT	Modulo 16 DI / 8 DO a relè Profinet IO (2 ETH)	16-CH digital inputs / 8 digital relay outputs Profinet IO module (2 ETH)
R203-1-L	90303900	3A002	IT	Analizz. rete trifase, 1xETH, 24 Vdc, ModBUS RTU/TCP-IP	3-phase Power Meter, 1xETH, 24 Vdc, ModBUS RTU/TCP-IP
R203-1-H	90303900	3A002	IT	Analizz. rete trifase, 1xETH, 90-264 Vac, ModBUS RTU/TCP-IP	3-phase Power Meter, 1xETH, 90-264 Vac, ModBUS RTU/TCP-IP
R203-1-L-P	90303900	3A002	IT	Analizz. rete trifase, 1xETH, 24 Vdc, Profinet IO	3-phase Power Meter, 1xETH, 24 Vdc, Profinet IO
R203-1-H-P	90303900	3A002	IT	Analizz. rete trifase, 1xETH, 90-264 Vac, Profinet IO	3-phase Power Meter, 1xETH, 90-264 Vac, Profinet IO
R203-2-L	90303900	3A002	IT	Analizz. rete trifase, 2xETH, 24 Vd, ModBUS RTU/TCP-IP	3-phase Power Meter, 2xETH, 24 Vd, ModBUS RTU/TCP-IP
R203-2-H	90303900	3A002	IT	Analizz. rete trifase, 2xETH, 90-264 Vac, ModBUS RTU/TCP-IP	3-phase Power Meter, 2xETH, 90-264 Vac, ModBUS RTU/TCP-IP
R203-2-L-P	90303900	3A002	IT	Analizz. rete trifase, 2xETH, 24 Vdc, Profinet IO	3-phase Power Meter, 2xETH, 24 Vdc, Profinet IO
R203-2-H-P	90303900	3A002	IT	Analizz. rete trifase, 2xETH, 90-264 Vac, Profinet IO	3-phase Power Meter, 2xETH, 90-264 Vac, Profinet IO
R-32DIDO	85389091	EAR99	IT	Modulo 32 ingressi/uscite digitali Modbus TCP-IP / Modbus RTU (2 ETH)	32-CH digital inputs / outputs Modbus TCP-IP / Modbus RTU (2 ETH)
R-32DIDO-P	85389091	EAR99	IT	Modulo 32 ingressi/uscite digitali Profinet IO (2 ETH)	32-CH digital inputs / outputs Profinet IO (2 ETH)
R-32DIDO-1	85389091	EAR99	IT	Modulo 32 ingressi/uscite digitali Modbus TCP-IP / Modbus RTU (1 ETH)	32-CH digital inputs / outputs Modbus TCP-IP / Modbus RTU (1 ETH)
R-32DIDO-1-P	85389091	EAR99	IT	Modulo 32 ingressi/uscite digitali Profinet IO (1 ETH)	32-CH digital inputs / outputs Profinet IO (1 ETH)
R-32DIDO-2	85389091	EAR99	IT	Modulo 32 ingressi/uscite digitali Modbus TCP-IP / Modbus RTU (2 ETH)	32-CH digital inputs / outputs Modbus TCP-IP / Modbus RTU (2 ETH)
R-32DIDO-2-P	85389091	EAR99	IT	Modulo 32 ingressi/uscite digitali Profinet IO (2 ETH)	32-CH digital inputs / outputs Profinet IO (2 ETH)
R-8AI-8DIDO	85389091	EAR99	IT	Modulo 8 ingressi analogici, 8 ingressi/uscite digitali Modbus TCP-IP / Modbus RTU (2 ETH)	8-CH analog inputs / 8-CH digital inputs / outputs Modbus TCP-IP / Modbus RTU module (2 ETH)
R-8AI-8DIDO-P	85389091	EAR99	IT	Modulo 8 ingressi analogici / 8 ingressi / uscite digitali Profinet IO (2 ETH)	8-CH analog inputs / 8-CH digital inputs / outputs Profinet IO module (2 ETH)
R-8AI-8DIDO-2	85389091	EAR99	IT	Modulo 8 ingressi analogici, 8 ingressi/uscite digitali Modbus TCP-IP / Modbus RTU (2 ETH)	8-CH analog inputs / 8-CH digital inputs / outputs Modbus TCP-IP / Modbus RTU module (2 ETH)
R-8AI-8DIDO-2-P	85389091	EAR99	IT	Modulo 8 ingressi analogici / 8 ingressi / uscite digitali Profinet IO (2 ETH)	8-CH analog inputs / 8-CH digital inputs / outputs Profinet IO module (2 ETH)
RADIO SETUP	-	2D002	IT	Software di configurazione Z-AIR-1, RM169-1, RTURADIO 169	Configuration software Z-AIR-1, RM169-1, RTURADIO 169
R-BT1	85076000	3A226	IT	Pacco batteria singolo	Single battery pack
R-BT2	85076000	3A226	IT	Pacco batteria doppio 3,6V	Double battery pack 3.6V
RC150-025-100-10	85437090	EAR99	IT	Sens. Rogowski L=25cm D.int.8cm 100mV/1KA-50Hz cavo 10mt	Rogowski Coil L=25cm Øint.8cm,100mV/1KA-50Hz,cable L=10mt.
RC150-025-100-3M	85437090	EAR99	IT	Sens. Rogowski L=25cm D.int.8cm 100mV/1KA-50Hz cavo 3mt	Rogowski Coil L=25cm Øint.8cm,100mV/1KA-50Hz,cable L=3mt.
RC150-025-100-5M	85437090	EAR99	IT	Sens. Rogowski L=25cm D.int.8cm 100mV/1KA-50Hz cavo 5mt	Rogowski Coil L=25cm Øint.8cm,100mV/1KA-50Hz,cable L=5mt.
RC150-035-100-3M	85437090	EAR99	IT	Sens. Rogowski L=35cm D.int.11cm 100mV/1KA-50Hz cavo 3mt	Rogowski Coil L=35cm Øint.11cm,100mV/1KA-50Hz,cable L=3mt.
RC150-035-100-5M	85437090	EAR99	IT	Sens. Rogowski L=35cm D.int.11cm 100mV/1KA-50Hz cavo 5mt	Rogowski Coil L=35cm Øint.11cm,100mV/1KA-50Hz,cable L=5mt.
RC150-035-100-10	85437090	EAR99	IT	Sens. Rogowski L=35cm D.int.11cm 100mV/1KA-50Hz cavo 10mt	Rogowski Coil L=35cm Øint.11cm,100mV/1KA-50Hz,cable L=10mt.
RC150-040-100-10	85437090	EAR99	IT	Sens. Rogowski L=40cm D.int.8cm 100mV/1KA-50Hz cavo 10mt	Rogowski Coil L=40cm Øint.11cm,100mV/1KA-50Hz,cable L=10mt.
RC150-040-100-3M	85437090	EAR99	IT	Sens. Rogowski L=40cm D.int.12cm 100mV/1KA-50Hz cavo 3mt	Rogowski Coil L=40cm Øint.12cm,100mV/1KA-50Hz,cable L=3mt.
RC150-040-100-5M	85437090	EAR99	IT	Sens. Rogowski L=40cm D.int.8cm 100mV/1KA-50Hz cavo 5mt	Rogowski Coil L=40cm Øint.11cm,100mV/1KA-50Hz,cable L=5mt.
RC150-060-100-10	85437090	EAR99	IT	Sens. Rogowski L=60cm D.int.19cm 100mV/1KA-50Hz cavo 10m	Rogowski Coil L=60cm Øint.19cm,100mV/1KA-50Hz,cable L=10mt.
RC150-060-100-3M	85437090	EAR99	IT	Sens. Rogowski L=60cm D.int.19cm 100mV/1KA-50Hz cavo 3m	Rogowski Coil L=60cm Øint.19cm,100mV/1KA-50Hz,cable L=3mt.
RC150-060-100-5M	85437090	EAR99	IT	Sens. Rogowski L=60cm D.int.19cm 100mV/1KA-50Hz cavo 5m	Rogowski Coil L=60cm Øint.19cm,100mV/1KA-50Hz,cable L=5mt.
RC150-090-100-10	85437090	EAR99	IT	Sens. Rogowski L=90cm D.int.28cm 100mV/1KA-50Hz cavo 10m	Rogowski Coil L=90cm Øint.28cm,100mV/1KA-50Hz,cable L=10mt.
RC150-090-100-3M	85437090	EAR99	IT	Sens. Rogowski L=90cm D.int.28cm 100mV/1KA-50Hz cavo 3m	Rogowski Coil L=90cm Øint.28cm,100mV/1KA-50Hz,cable L=3mt.

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
RC150-090-100-5M	85437090	EAR99	IT	Sens. Rogowski L=90cm D.int.28cm 100mV/1KA-50Hz cavo 5m	Rogowski Coil L=90cm Øint.28cm,100mV/1KA-50Hz,cable L=5mt.
RC150-120-100-3M	85437090	EAR99	IT	Sens. Rogowski L=12cm D.int.38cm 100mV/1KA-50Hz cavo 3m	Rogowski Coil L=120cm Øint.38cm,100mV/1KA-50Hz,cable L=3mt.
RC150-120-100-5M	85437090	EAR99	IT	Sens. Rogowski L=12cm D.int.38cm 100mV/1KA-50Hz cavo 5m	Rogowski Coil L=120cm Øint.38cm,100mV/1KA-50Hz,cable L=5mt.
RC150-130-100-5M	85437090	EAR99	IT	Sens. Rogowski L=13cm D.int.38cm 100mV/1KA-50Hz cavo 5m	Rogowski Coil L=130cm Øint.38cm,100mV/1KA-50Hz,cable L=5mt.
RC150-180-100-3M	85437090	EAR99	IT	Sens. Rogowski L=180cm D.int.57cm 100mV/1KA-50Hz cavo 3m	Rogowski Coil L=180cm Øint.57cm,100mV/1KA-50Hz,cable L=3mt.
RC150-280-100-5M	85437090	EAR99	IT	Sens. Rogowski L=280cm D.int.57cm 100mV/1KA-50Hz cavo 5m	Rogowski Coil L=280cm Øint.57cm,100mV/1KA-50Hz,cable L=5mt.
RC150-300-100-5M	85437090	EAR99	IT	Sens. Rogowski L=300cm D.int.57cm 100mV/1KA-50Hz cavo 5m	Rogowski Coil L=300cm Øint.57cm,100mV/1KA-50Hz,cable L=5mt.
RC190-030-333-3M	85437090	EAR99	IT	Sensore Rogowski L-bobina=30cm, Øint. 9cm, 333mV/1KA-50Hz, L-cavo=3mt	Rogowski sensor L-coil=30cm, Øint. 9cm, 333mV/1KA-50Hz, L-cable=3mt
RC190-030-333-5M	85437090	EAR99	IT	Sensore Rogowski L-bobina=30cm, Øint. 9cm, 333mV/1KA-50Hz, L-cavo=5mt	Rogowski sensor L-coil=30cm, Øint. 9cm, 333mV/1KA-50Hz, L-cable=5mt
RC190-035-333-3M	85437090	EAR99	IT	Sensore Rogowski L-bobina=35cm, Øint. 9cm, 333mV/1KA-50Hz, L-cavo=3mt	Rogowski sensor L-coil=35cm, Øint. 9cm, 333mV/1KA-50Hz, L-cable=3mt
RC190-060-333-3M	85437090	EAR99	IT	Sensore Rogowski L-bobina=60cm, Øint. 9cm, 333mV/1KA-50Hz, L-cavo=3mt	Rogowski sensor L-coil=60cm, Øint. 9cm, 333mV/1KA-50Hz, L-cable=3mt
RC190-090-333-3M	85437090	EAR99	IT	Sensore Rogowski L-bobina=90cm, Øint. 9cm, 333mV/1KA-50Hz, L-cavo=3mt	Rogowski sensor L-coil=90cm, Øint. 9cm, 333mV/1KA-50Hz, L-cable=3mt
RC190-160-333-3M	85437090	EAR99	IT	Sensore Rogowski L-bobina=160cm, Øint. 9cm, 333mV/1KA-50Hz, L-cavo=3mt	Rogowski sensor L-coil=160cm, Øint. 9cm, 333mV/1KA-50Hz, L-cable=3mt
R-COMM-0-4GWW	85176200	5A991	IT	Modulo di comunicazione con modem 4GWW	Communication module with 4GWW modem
R-COMM-B-4GWW	85176200	5A991	IT	Modulo di comunicazione con mini UPS e modem 4GWW	Communication module with mini UPS and 4GWW modem
RC-V250-100	85437090	EAR99	IT	Sensore Rogowski 100mV/kA - 50/60Hz Ø 65 mm	Rogowski coil, 100 mv/kA output, 50-60 Hz, Ø 65 mm
RC-V400-050	85437090	EAR99	IT	Sensore Rogowski 50mV/kA - 50/60Hz cavo 2mt	Rogowski coil, 50 mv/kA output, 50-60 Hz, Ø 115 mm
RC-V400-100	85437090	EAR99	IT	Sensore Rogowski 100mV/kA - 50/60Hz cavo 2mt	Rogowski coil, 100 mv/kA output, 50-60 Hz, Ø 115 mm
RC-V500-100	85437090	EAR99	IT	Sensore Rogowski 100mV/kA - 50/60Hz cavo 2mt	Rogowski coil, 100 mv/kA output, 50-60 Hz, Ø 147 mm
R-GWR	85171800	EAR99	IT	Gateway ModBUS per sensori wireless	ModBUS gateway for wireless sensors
R-GWR-AF	85171800	EAR99	IT	Cavo sensore anti-allagamento	Anti-Flooding sensor cable
R-GWR-IP-1	85171800	EAR99	IT	Sensore industriale LoRa con ingresso analogico/digitale	LoRa industrial sensor with analog/digital input
R-GWR-IP-2	85171800	EAR99	IT	Sensore industriale LoRa con ingresso analogico/digitale, batteria doppia	Sensore industriale LoRa con ingresso analogico/digitale, batteria doppia
R-GWR-S-1	85171800	EAR99	IT	Sensore domotico LoRa con ingresso analogico/digitale e anti-allagamento	LoRa home automation sensor with analog/digital input and anti flooding
R-KEY-LT	85176200	5A991	IT	Gateway ModBUS / universale (ModBUS; Profinent, Ethernet/IP), 1 porta seriale, 1 porta Ethernet	ModBUS RTU/ASCII↔TCP-IP/universal (ModBUS; Profinent, Ethernet/IP) gateway, 1 serial port, 1 Ethernet port
R-KEY-LT-E	85176200	5A991	IT	Gateway ModBUS → Ethernet/IP (1 porta seriale, 1 porta Ethernet)	ModBUS → Ethernet/IP gateway (1 serial port, 1 Ethernet port)
R-KEY-LT-P	85176200	5A991	IT	Gateway ModBUS ↔ Profinet IO (1 porta seriale, 1 porta Ethernet)	ModBUS ↔ Profinet IO gateway (1 serial port, 1 Ethernet port)
R-KEY-MBUS	85176200	5A991	IT	Gateway ModBUS ↔ M-BUS (1 porta M-BUS, 1 porta seriale, 1 porta Ethernet)	ModBUS ↔ M-BUS gateway (1 M-BUS port, 1 serial port, 1 Ethernet port)
RM169-1	85171800	5A991	IT	Radiomodem 169MHZ, 1DI,1DO, RS485 connett. BNC F, RED	169MHZ Radiomodem, 1DI,1DO,1RS485, BNC-F connector, RED directive
RM169-1-169DV12	85171800	5A991	IT	Radiomodem 169MHZ, 1DI,1DO, RS485, ant. dip. lambda/2, RED	169MHZ Radiomodem, 1DI,1DO,1RS485, vertical dipole antenna, RED directive
RM169-1-DV12-10	85171800	5A991	IT	Radiomodem 169MHZ, 1DI,1DO, RS485, ant. dip. 10 mt, lambda/2, RED	169MHZ Radiomodem, 1DI,1DO,1RS485, vertical dipole antenna, 10 mt. RED directive
RM169-1-169DV14	85171800	5A991	IT	Radiomodem 169MHZ, 1DI,1DO, RS485, ant. stilo lambda/4, RED	169MHZ Radiomodem, 1DI,1DO,1RS485, vertical stilo antenna, RED directive
RM169-1-169YAGI	85171800	5A991	IT	Radiomodem 169MHZ, 1DI,1DO, RS485 + ant. Yagi 3 el., dir. RED	169MHZ Radiomodem, 1DI,1DO,1RS485, 3 elements Yagi antenna, RED directive
R-PASS-0-4-0	85176200	5A991	IT	Edge Gateway IIoT con 4 porte Ethernet	IIoT Edge Gateway with 4 Ethernet ports
R-PASS-0-4-E	85176200	5A991	IT	Edge Controller IIoT Straton con protocolli Energia e 4 porte Ethernet	IIoT Edge Controller Straton with Energy protocols and 4 Ethernet ports
R-PASS-0-4-S	84714100	5A991	IT	Edge Controller IIoT Straton con 4 porte Ethernet	IIoT Edge Controller Straton with 4 Ethernet Ports
R-PASS-W-4-0	85176200	5A991	IT	Edge Gateway IIoT con Wi-Fi e 4 porte Ethernet	IIoT Edge Gateway with Wi-Fi and 4 Ethernet ports
R-PASS-W-4-E	85176200	5A991	IT	Edge Controller IIoT Straton con protocolli Energia, Wi-Fi e 4 porte Ethernet	IIoT Edge Controller Straton with Energy protocols, Wi-Fi and 4 Ethernet ports
R-PASS-W-4-S	84714100	5A991	IT	Edge Controller IIoT Straton con Wi-Fi e 4 porte Ethernet	IIoT Edge Controller Straton with Wi-Fi and 4 Ethernet ports
R-SG3	85389091	EAR99	IT	Modulo convertitore strain gauge Modbus TCP-IP / Modbus RTU	Strain gauge Modbus TCP-IP / Modbus RTU converter module

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
R-SG3-P	85389091	EAR99	IT	Modulo convertitore strain gauge Profinet IO	Strain gauge Profinet IO converter module
RTU-LP-ST	85171800	5A991	IT	RTU low power, versione FTP, 4DI, 2AI, 2DO	Low power RTU, FTP version, 4DI, 2AI, 2DO
RTU-LP-ST1	85171800	5A991	IT	RTU low power, versione FTP, 4DI, 2AI, 2DO, batterie std	Low power RTU, FTP version, 4DI, 2AI, 2DO, single battery pack
RTU-LP-ST2	85171800	5A991	IT	RTU low power, versione FTP, 4DI, 2AI, 2DO, batteria doppia	Low power RTU, FTP version, 4DI, 2AI, 2DO, double battery pack
RTURADIO-169	85171800	5A991	IT	RTU Radio 169MHZ, 4DI, 2 DO, 1 contatore,2 AO,2 AI,RS485	Radiomodem 169MHZ, 4DI, 2DO, 2AO, 2AI, RS485
RTURADIO-169DV12	85171800	5A991	IT	RTU Radio 169MHZ, 4DI, 2 DO, 1 contatore,2 AO,2 AI,RS485	Radiomodem 169MHZ, 4DI, 2DO, 2AO, 2AI, RS485, dipole
RTURADIO-DV12-10	85171800	5A991	IT	RTU Radio 169MHZ, 4DI, 2 DO, 1 contatore, 2AO, 2AI,RS485, ant.dip. 10mt	Radiomodem 169MHZ, 4DI, 2DO, 2AO, 2AI, RS485, dipole 10 mt
RTURADIO-169DV14	85171800	5A991	IT	RTU Radio 169MHZ, 4DI, 2 DO, 1 contatore,2 AO,2 AI,RS485	Radiomodem 169MHZ, 4DI, 2DO, 2AO, 2AI, RS485, vertical
RTURADIO-169YAGI	85171800	5A991	IT	RTU Radio 169MHZ, 4DI, 2 DO, 1 contatore,2 AO,2 AI,RS485	Radiomodem169MHZ, 4DI, 2DO, 2AO, 2AI, RS485, yagi
RZACEA020	85235110	EAR99	IT	Card teleassistenza HMI Serie VISUAL	Remote Access Card for HMI Visual
S					
S100S-1-ST	85044090	EAR99	IT	Alim. doppio per loop di corrente, alim. 115 / 230 Vac	Current loop dual power supply, 115 / 230 Vac
S107P	85437090	EAR99	IT	Convertitore seriale RS232-RS485/422 (portatile)	RS232 - RS485/422 serial converter, portable version
S107USB	85437090	EAR99	IT	Convertitore seriale USB/RS485 portatile	RS485/USB serial converter, portable version
S109REG-1-ST	85437090	EAR99	IT	Convertitore isolatore Pt100 / V-I alim. 115 / 230 Vac	DC current - voltage converter/isolator, 115/230 Vac
S109REG-1-X7	85437090	EAR99	IT	Convertitore isolatore V-I / V-I ingresso fino a 200 Vdc	DC curr.-volt. conv./isol., 115/230 Vac, max in 200 Vdc
S109S-1-ST	85437090	EAR99	IT	Isolatore per loop 4..20 mA, alim. 115 / 230 Vac	Galvanic isolator for 4-20 mA current loop, 115/230 Vac
S112A-1-ST	85437090	EAR99	IT	Alim. - amplif. on-off, 1 uscita relè, 115/230 Vac	On/Off digital amplifier, 1 relay output, 115 / 230 Vac
S112M-1-ST	85437090	EAR99	IT	Alim. - amplif. on-off, 5 uscite relè, 115/230 Vac	On/Off digital amplifier, 5 relay output, 115 / 230 Vac
S112M-23-ST	85437090	EAR99	IT	Amplificatore per contatti digitali multiplo, 24 Vac/dc	On/Off digital amplifier, 5 relay output, 24 Vac/dc
S117P1	85437090	EAR99	IT	Convertitore Seriale RS232-TTL-RS485/USB	RS232/USB, TTL/USB, RS485/USB serial converter
S170-1-ST	85437090	EAR99	IT	Duplicatore convertitore di segnale, alim.115/230 Vac	DC duplicator - isolator, 115 / 230 Vac
S201RC-LP	85437090	3B992	IT	Convertitore di corrente loop powered per sens. Rogowski	Loop powered current converter for Rogowski Coils
S203RC-D	90303370	3A002	IT	Analizzatore di rete trifase, 600 Vac / 1000 Arms, Rogowski, uscite analogica e impulsiva, display LCD, app Micro USB	Three-phase Network Analyzer for Rogowski's sensor
S203TA-D	90303370	3A002	IT	Analizzatore di rete trifase, 600 Vac / 5 Arms, uscite analogica e impulsiva, TA standard, display LCD, app Micro USB	AC three phase network analyzer with energy meter
S20ADP	85389091	EAR99	IT	Scheda adattatrice ingressi - standard	Input adapter board self-powered for S20N1, S21N1, S30
S20ADP-CM	85389091	EAR99	IT	Scheda adattatrice ingressi, contenitore modulare	Self-powered input adapter board for S20N1, S21N1, S30
S20ADP-CM-S	85389091	EAR99	IT	Scheda adattatrice impulsi sinusoidali NPN onda quadra	Adapter module for sinusoidal sensor input
S20ADP-IP65	85389091	EAR99	IT	Scheda adattatrice ingressi, contenitore stagno	IP65 self-powered input adapter board
S20N1-1-ST	90268020	4A001	IT	Batch controller base, alim. 115 / 230 Vac	Batch controller, 115 / 230 Vac
S20N1-23-ST	90268020	4A001	IT	Batch controller base, alim. 24 Vac / dc	Batch controller, 24 Vac / dc
S20N1EX-1-ST	90268020	4A001	IT	Batch controller base in custodia Eexd, alim. 115 / 230 Vac	Batch controller in EExd case, 115 / 230 Vac
S20N1EX-23-ST	90268020	4A001	IT	Batch controller base in custodia Eexd, alim. 24 Vac / dc	Batch controller in EExd case, 24 Vac/dc
S20N1IP65-1-ST	90268020	4A001	IT	Batch controller base in custodia IP65, alim. 115 / 230 Vac	Batch controller in IP65 case, 115 / 230 Vac
S20N1IP65-23-ST	90268020	4A001	IT	Batch controller base in custodia IP65, alim. 24 Vac/dc	Batch controller in IP65 case, 24 Vac/dc
S20N1-KIT-1-ST	90268020	EAR99	IT	Kit comandi esterni per S20N / S21 - ALIM. 115/230 Vac	S20N1 / S21N1 remote board, 115 / 230 Vac
S20N1-KIT-23-ST	90268020	EAR99	IT	Kit comandi esterni per S20N / S21 - ALIM. 24 Vac/dc	S20N1 / S21N1 remote board, 24 Vac/dc
S21N1-1-ST	90268020	4A001	IT	Batch controller con funzioni avanzate, 115 / 230 Vac	Batch controller with advanced functions, 115 / 230 Vac
S21N1-23-ST	90268020	4A001	IT	Batch controller con funzioni avanzate, 24 Vac/dc	Batch controller with advanced functions, 24 Vac / dc
S21N1EX-1-ST	90268020	4A001	IT	Batch controller con funzioni avanzate Eexd, 115 / 230 Vac	Batch controller EExd, advanced functions, 115/230 Vac
S21N1EX-23-ST	90268020	4A001	IT	Batch controller con funzioni avanzate Eexd, 24 Vac/dc	Batch controller Eexd, advanced functions, 24 Vac/dc

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
S21N1IP65-1-ST	90268020	4A001	IT	Batch controller con funzioni avanzate IP65, 115/230 Vac	Batch controller IP65, advanced functions, 115/230 Vac
S21N1IP65-23-ST	90268020	4A001	IT	Batch controller con funzioni avanzate IP65, 24 Vac/dc	Batch controller IP65, advanced functions, 24 Vac/dc
S232-FO-MONO-DL	85437090	5A991	IT	Convertitore RS232 in fibra monomodale double loop	RS232 - single mode fiber, double loop converter
S232-FO-MONO-SL	85437090	5A991	IT	Convertitore RS232 in fibra monomodale single loop	RS232 - single mode fiber, single loop converter
S232-FO-MULTI-DL	85437090	5A991	IT	Convertitore multi-drop fibra ottica - RS232 double loop	RS232 - multi mode fiber, double loop converter
S232-FO-MULTI-SL	85437090	5A991	IT	Convertitore multi-drop fibra ottica - RS232 single loop	RS232 - multi mode fiber, single loop converter
S301-1-R	85312040	EAR99	IT	Ind. 4 cifre a μ P ingr.univ e uscita ritr. 115 / 230 Vac	4 digit indicator, univ. input, retr.out, 115/230 Vac
S301-1-R-AOC-S	85312040	EAR99	IT	Ind. 4 cfr uscita rit. 115/230 Vac, 4 all., RS232/RS485	4-digit indicator, 115/230 Vac, 4 o.c., RS232/RS485
S301-1-R-AR-S	85312040	EAR99	IT	Ind. 4 cfr uscita rit. 115/230 Vac 3 all. RS232/RS485	4-digit indicator, 115/230 Vac, 3 SPDT, RS232/RS485
S301-23-R	85312040	EAR99	IT	Ind. 4 cifre uscita rit. 24 Vac/dc	4 digit indicator, univ. input, retr.output, 24 Vac/dc
S301-23-R-AOC-S	85312040	EAR99	IT	Ind. 4 cfr uscita rit. 24 Vac/dc 4 all. RS232/RS485	4-digit indicator, 24 Vac/dc, 4 o.c., RS232/RS485
S301-23-R-AR-S	85312040	EAR99	IT	Ind. 4 cfr uscita rit. 24 Vac/dc 3 all. SPDT RS232/RS485	4-digit indicator, 24 Vac/dc, 3 SPDT, RS232/RS485
S301B-1-R	85312040	EAR99	IT	Ind. 4 cifre, bargraph, uscita rit, alim. 115 / 230 Vac	4 digit indicator+barg. univ. in, retr. out, 115/230Vac
S301B-1-R-AOC-S	85312040	EAR99	IT	Ind.4 cifre 4 all.open coll. Bargraph out ritr.+seriale	4-digit indicator+barg. 115/230 Vac, 4 o.c. RS232/RS485
S301B-1-R-AR-S	85312040	EAR99	IT	Ind. 4 cfr barg. out rit. 115/230 Vac 3 all. RS232/RS485	4-digit indicator, 115 / 230 Vac, 3 SPDT, RS232/RS485
S301B-23-R	85312040	EAR99	IT	Ind. 4 cifre bargraph uscita rit. alim. 24 Vac/dc	4 digit indicator + bargraph, power supply 24 Vac/dc
S301B-23-R-AOC-S	85312040	EAR99	IT	Ind. 4 cfr barg. out rit. 24 Vac/dc, 4 all. RS232/RS485	4-digit indicator+barg., 24 Vac/dc, 4 o.c., RS232/RS485
S301B-23-R-AR-S	85312040	EAR99	IT	Ind. 4 cfr barg. out rit. 24 Vac/dc, 3 all. RS232/RS485	4-digit indicator+barg., 24 Vac/dc, 3 SPDT, RS232/RS485
S311A-11-H	85312040	EAR99	IT	Ind.tot. 11 cifre, ingresso univ. 80-265 Vac	11 digit indicator, universal analog input, 80-265 Vac
S311A-11-H-O	85312040	EAR99	IT	Ind.tot. 11 cifre, ingresso univ. 80-265 Vac scheda opz.	11 digit indicator, univ. AI, 80-265 Vac, opt. board
S311A-11-L	85312040	EAR99	IT	Ind.tot. 11 cifre ingr. univ. 10-40 Vdc / 19-28 Vac	11 digit analog input indicator, 10-40 Vdc/19-28 Vac
S311A-11-L-O	85312040	EAR99	IT	Ind.tot. 11 cfr ingr.univ. 10-40Vdc/19-28Vac scheda opz.	11-digit input indicator, 10-40Vdc/19-28Vac, opt. board
S311A-4-H	85312040	EAR99	IT	Ind.tot. 4 cifre, ingresso univ. 80-265 Vac	4 digit indicator, universal analog input, 80-265 Vac
S311A-4-H-O	85312040	EAR99	IT	Ind.tot. 4 cifre, ingresso univ. 80-265 Vac, scheda opz.	4 digit indicator, 80-265 Vac, opt. board
S311A-4-L	85312040	EAR99	IT	Ind.tot. 4 cifre ingr. univ. 10-40 Vdc / 19-28 Vac	4 digit indicator, universal AI, 10-40Vdc/19-28 Vac
S311A-4-L-O	85312040	EAR99	IT	Ind.tot. 4 cfr ingr.univ. 10-40Vdc/19-28 Vac scheda opz.	4-digit indicator, 10-40 Vdc/19-28 Vac, opt. Board
S311A-6-H	85312040	EAR99	IT	Ind.tot. 6 cifre, ingresso univ. 80-265 Vac	6 digit indicator, universal analog input, 80-265 Vac
S311A-6-H-O	85312040	EAR99	IT	Ind.tot. 6 cifre, ingresso univ. 80-265 Vac, scheda opz.	6 digit indicator, universal AI, 80-265 Vac, opt. board
S311A-6-L	85312040	EAR99	IT	Ind.tot. 6 cifre ingr. univ. 10-40 Vdc / 19-28 Vac	6 digit indicator, universal AI, 10-40 Vdc/19-28 Vac
S311A-6-L-O	85312040	EAR99	IT	Ind.tot. 6 cfr ingr.univ. 10-40Vdc/19-28Vac scheda opz.	6 digit indicator, 10-40 Vdc / 19-28 Vac, opt. board
S311A-8-H	85312040	EAR99	IT	Ind.tot. 8 cifre ingr. univ. 80-265 Vac	8-digit indicator, universal analog input, 80-265 Vac
S311A-8-H-O	85312040	EAR99	IT	Ind.tot. 8 cifre ingr. univ. 80-265 Vac, scheda opz.	8-digit indicator, universal AI, 80-265 Vac, opt. board
S311A-8-L	85312040	EAR99	IT	Ind.tot. 8 cifre ingr. univ. 10-40 Vdc / 19-28 Vac	8-digit indicator, universal AI 0-40 Vdc/19-28 Vac
S311A-8-L-O	85312040	EAR99	IT	Ind.tot. 8 cfr ingr.univ. 10-40Vdc/19-28Vac scheda opz.	8-digit indicator, 10-40 Vdc/19-28 Vac, opt. board
S311AK-4-L	85312040	EAR99	IT	Indicatore 4 cfr ingr. analogico, 10-40 Vdc, 19-28 Vac	4 digit indicator analog input, 10-40 Vdc, 19-28 Vac
S311AK-4-L-IP66	85312040	EAR99	IT	Indicatore 4 cfr ingr. analogico, 10-40 Vdc, 19-28 Vac, IP66	4 digit indicator analog input 10-40 Vdc/19-28Vac, IP66
S311AK-4-L-IP66D	85312040	EAR99	IT	Ind. 4 cfr ingr. analogico, 10-40 Vdc, 19-28 Vac, IP66 (x2)	4 digit indicator, AI, 10-40 Vdc, 19-28 Vac, IP66 (x2)
S311D-11-H	85312040	EAR99	IT	Ind.tot. ingr.dig./freq., 80-265 Vac, 11 cifre	11-digit digital input indicator, 80-265 Vac
S311D-11-H-O	85312040	EAR99	IT	Ind.tot. ingr.dig./freq., 80-265 Vac, 11 cifre, scheda opz.	11 digit digital input indicator, 80-265 Vac opt. board
S311D-11-L	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq., 10-40 Vdc / 19-28 Vac, 11 cifre	11-digit digital input indicator, 10-40 Vdc / 19-28 Vac
S311D-11-L-O	85312040	EAR99	IT	Ind.tot. ingr.dig/freq 10-40 Vdc/19-28 Vac, 11 cfr, sch. opz.	11-digit dig. input ind., 10-40Vdc/19-28Vac, opt. board
S311D-4-H	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq., 80-265 Vac, display 4 cifre	4-digit, digital input indicator, 80-265 Vac

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
S311D-4-H-O	85312040	EAR99	IT	Ind.tot. Ingr.dig/freq 80-265 Vac, display 4 cfr, sch. opz.	4 digit digital input indicator, 80-265 Vac, opt. Board
S311D-4-L	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq, 10-40 Vdc / 19-28 Vac, 4 cifre	4-digit digital input indicator, 10-40 Vdc / 19-28 Vac
S311D-4-L-O	85312040	EAR99	IT	Ind.tot. Ingr. dig. 10-40 Vdc / 19-28 Vac, 4 cfr, sch. opz.	4-digit dig. input ind., 10-40Vdc/19-28Vac, opt. board
S311D-6-H	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq., 80-265 Vac, display 6 cifre	6-digit digital input indicator, 80-265 Vac
S311D-6-H-O	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq, 80-265 Vac, 6 cifre, scheda opz.	6-digit digital input indicator, 80-265 Vac,opt. Board
S311D-6-L	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq., 10-40 Vdc / 19-28 Vac, 6 cifre	6-digit digital input indicator, 10-40 Vdc/19-28 Vac
S311D-6-L-O	85312040	EAR99	IT	Ind.tot. Ingr.dig/freq 10-40 Vdc/19-28 Vac, 6 cfr, sch. opz.	6-digit dig. input ind., 10-40Vdc/19-28Vac, opt. board
S311D-8-H	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq., 80-265 Vac, 8 cifre	8-digit digital input indicator, 80-265 Vac
S311D-8-H-O	85312040	EAR99	IT	Ind.tot. Ingr.dig./freq., 80-265 Vac, 8 cifre, scheda opz.	8-digit digital input indicator, 80-265 Vac, opt. board
S311D-8-L	85312040	EAR99	IT	Ind.tot. Ingr. dig./freq., 10-40 Vdc / 19-28 Vac, 8 cifre	8-digit digital input indicator, 10-40 Vdc/19-28 Vac
S311D-8-L-O	85312040	EAR99	IT	Ind.tot. Ingr. dig/freq 10-40 Vdc/19-28 Vac, 8 cfr. sch. opz.	8-digit dig. input ind., 10-40Vdc/19-28 Vac, opt. board
S311G-4-H	85312040	EAR99	IT	Ind. Gen. con ing. analogico univ. a 4 cifre, 80-265 Vac	4-digit universal input indicator/signal generator, 80-265 Vac
S311G-4-H-O	85312040	EAR99	IT	Ind. Gen. con AI univ. 4 cifre, 80-265 Vac, scheda opz.	4-digit univ. input ind./signal gen., 80-265 Vac, opt. board
S311G-4-L	85312040	EAR99	IT	Ind. Gen. con AI universale, 4 cifre, 10-40 Vdc / 19-28 Vac	4-digit universal input indicator/signal generator, 10-40 Vdc, 19-28 Vac
S311G-4-L-O	85312040	EAR99	IT	Ind. Gen. AI univ. 4 cifre, 10-40 Vdc/19-28 Vac, scheda opz.	4-digit universal input indicator/signal gen., 10-40 Vdc, 19-28 Vac, opt. board
S311OPZ	85389091	EAR99	IT	Scheda opzionale per indicatori famiglia S311	S311 optional board, RS485, 2-CH relay, 1-CH DI
S311-T	-	EAR99	IT	Servizio di taratura indicatori famiglia S311	Calibration service for S311 Series indicators
S312A-4-H-4R	85312040	EAR99	IT	Indicatore analogico universale con display a 4 cifre	4-digit analog input Indicator, 4 relay, 85-265 Vac
S312A-4-L-4R	85312040	EAR99	IT	Indicatore analogico universale con display a 4 cifre	4-digit analog input Ind., 4 relay, 10-40Vdc, 19-28Vac
S315	85312040	EAR99	IT	Indicatore loop powered, ingresso 4..20mA	4 digit loop powered display with 4-20 mA input signal
S315-IP66	85312040	EAR99	IT	Indicatore loop powered, ingresso 4..20mA	4 digit loop powered display, 4-20 mA input, IP66 case
S315-IP66D	85312040	EAR99	IT	Due indicatori loop powered, ingresso 4..20mA	4 digit loop powered display, 4-20 mA, IP66 case (x2)
S320A-1-ST	85312040	EAR99	IT	Ind. 3 ½ cifre ing. V-I 2 all.rele, 96x96 mm 115/230 Vac	3 ½ digit indicator, V/I input, 2 relay, 115/230 Vac
S320A-23-ST	85312040	EAR99	IT	Ind. 3 ½ cifre, V/I, 2 relè, 96x96, 24 Vac/dc	3 ½ digit indicator, V/I input, 2 relay, 24 Vac/dc
S320A-23-ST-R	85312040	EAR99	IT	Ind.3 ½ cifre, V/I, 2 relè, 96x96, 24 Vac/dc uscita rit	3 ½ digit indicator, V/I input, 2 relay AO, 24 Vac/dc
S400CL-1	85363030	EAR99	DE	SPD 21Vac/30Vdc C1/2/3/D1 per segn. mA/V/digit. con sez.	Analog and Digital Signals SPD with knife disconnecter
S400CL-1-15	85363030	EAR99	DE	Kit 15 p.zi protezione da sovratensioni S400CL-1	S400CL-1 10 pieces kit
S400CL-1-P5	85363030	EAR99	DE	5 pcs - Parete finale chiusura modulo S400CL-1	S400CL-1 closing side (5 pieces)
S400ETH-DSK	85363030	EAR99	DE	SPD B2,C1/2/3,D1 per Eth. Class.D/Cat.5/5e (1Gbps), PoE	Ethernet Networks SPD, Class.D/Cat.5 (100 Mbps)/5e
S400HV-2	85363030	EAR99	DE	Prot. sovrat. 230Vac tipo 2, 3 cond.(L,N,PE) no cont. FM	Type 2 230 Vac SPD at 3 conductors (L, N, PE)
S400HV-2-RIC-SL	85363030	EAR99	DE	Ricambio spina 1L-N/PE per S400HV-2, no contatto FM/II/T2	S400HV2 plug spare 1L-NPE, no FM contact
S400HV-2-RIC-SN	85363030	EAR99	DE	Ricambio spina N/PE per S400HV2 II/T2 335Vac/260Vac/-	S400HV2 plug spare N/PE
S400LV-1	85363030	EAR99	DE	Prot. sovrat. 24V tipo 2, 3 cond. (L,N,PE) con contatto FM	Type 3 24 Vac/dc SPD with FM contact at 3 conductors
S400LV-1-RIC-SL	85363030	EAR99	DE	Ricambio spina 24Vac/dc per S400LV-1, contatto FM III/T3	S400LV-1 plug spare, with contact FM
S400NET-1	85363030	EAR99	DE	Prot. Sovrat. C1/2/3 D1, LINEE BUS 5F, RS232/422/485, LAN	Ethernet, serial, fieldbus networks SPD, 5 wires
S400NET-1-RIC				Ricambio spina per S400NET-1 C1/C2/C3/D1	Spare plug for S400NET-1 C1/C2/C3/D1
S401-L	85312040	EAR99	IT	Indicatore con visualizzatore Oled e interfaccia ModBUS	ModBUS RTU indicator with OLED 2,7" display
S485-FO-MONO-DL	85437090	5A991	IT	Convertitore RS485 in fibra monomodale double loop	RS485 single mode fiber, double loop converter
S485-FO-MONO-SL	85437090	5A991	IT	Convertitore RS485 in fibra monomodale single loop	RS485 - single mode fiber, single loop converter
S485-FO-MULTI-DL	85437090	5A991	IT	Convertitore rame/fibra RS485 double loop	Multidrop fiber optic - RS485 double loop converter
S485-FO-MULTI-SL	85437090	5A991	IT	Convertitore rame/fibra RS485 single loop	Multidrop fiber optic - RS485 single loop converter

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
S500-ETH	90289010	EAR99	IT	Interfaccia di comunicazione ottica - LAN Modbus TCP-IP,web server	Ethernet optical interface module
S500-MBU	90289010	EAR99	IT	Interfaccia di comunicazione ottica - M-Bus	M-BUS optical interface module
S500-MOD	90289010	EAR99	IT	Interfaccia di comunicazione ottica - RS485 Modbus Rtu	RS485 Modbus RTU optical interface module
S501-40-0	90283011	EAR99	IT	Contatore Energia 40A monofase 2 fili 1 DIN	40A single phase energy counter 2 wires 1 DIN
S501-40-0-MID	90283011	EAR99	IT	Contatore Energia 40A monofase 2 fili 1 DIN, MID	40A single phase energy counter 2 wires 1 DIN, MID certified
S501-40-MBU				Contatore Energia 40A monofase 2 fili 1 DIN, M-Bus, MID	40A single phase energy counter 2 wires 1 DIN, RS485 M-Bus
S501-40-MBU-MID	90283011	EAR99	IT	Contatore Energia 40A monofase 2 fili 1 DIN, M-Bus, MID	40A single phase energy counter 2 wires 1 DIN, RS485 M-Bus, MID
S501-40-MOD-MID	90283011	EAR99	IT	Contatore Energia 40A monofase 2 fili 1 DIN, RS485 Modbus, MID	40A single phase energy counter 2 wires 1 DIN, RS485 Modbus MID
S50-1-ST	85044090	EAR99	IT	Alimentatore per loop di corrente, alim. 115/230 Vac	Current loop power supply, 115/230 Vac
S502-80-ETH	90283011	EAR102	IT	Contatore Energia 80A monofase 2 fili 2 DIN, Ethernet	80A single phase energy counter 2 wires 2 DIN, Ethernet
S502-80-MBU	90283011	EAR101	IT	Contatore Energia 80A monofase 2 fili 2 DIN, M-BUS	80A single phase energy counter 2 wires 2 DIN, M-BUS
S502-80-MID	90283011	EAR99	IT	Contatore Energia 80A monofase 2 fili 2 DIN, certif. MID	80A Single Phase Energy Counter, 2 wires, 1 DIN, MID
S502-80-MOD	90283011	EAR100	IT	Contatore Energia 80A monofase 2 fili 2 DIN, RS485 Modbus	80A single phase energy counter 2 wires 2 DIN, RS485 Modbus
S504C-6-ETH-MID	90283019	EAR99	IT	Contatore Energia 1/5A 3fase 4 fili 4 DIN-Ethernet, MID	6A 3-phase energy counter 4 wires 4 DIN, Ethernet, MID
S504C-6-MBU-MID	90283019	EAR99	IT	Contatore Energia 1/5A 3fase 3/4 fili 4 DIN-MBus, MID	6A 3-phase energy counter 4 wires 4 DIN, M-BUS, MID
S504C-6-MOD-MID	90283019	EAR99	IT	Contatore Energia 1/5A 3fase 4 fili 4 DIN-RS485,MID	6A 3-phase energy counter 4 wires 4 DIN, Modbus, MID
S504C-80-ETH-MID	90283019	EAR99	IT	Contatore Energia 80A 3fase 4 fili 4 DIN-Ethernet, MID	80A 3-phase energy counter 4 wires 4 DIN, Ethernet, MID
S504C-80-MBU-MID	90283019	EAR99	IT	Contatore Energia 80A 3fase 4 fili 4 DIN-MBus, MID	80A 3-phase energy counter 4 wires 4 DIN, M-BUS, MID
S504C-80-MOD-MID	90283019	EAR99	IT	Contatore Energia 80A 3fase 4 fili 4 DIN-RS485, MID	80A 3-phase energy counter 4 wires 4 DIN, Modbus, MID
S534-6-MID	90283019	EAR99	IT	Contatore Energia 1/5A 3fase 3/4 fili 4 DIN, cert.MID	6A three phase energy counter 3/4 wires 4 DIN, MID
S534-80-MID	90283019	EAR99	IT	Contatore Energia 80A 3fase 3/4 fili 4 DIN, cert.MID	80A three phase energy counter 3/4 wires 4 DIN, MID
S6001-4GEUUPG	85176200	5A991	IT	Aggiornamento e sostituzione Modem 3G → 4GLTE/EMEA c/o laboratorio	Upgrade and replacement of 3G Modem → 4GLTE/EMEA by laboratory
S6001-4GUPG	85176200	5A991	IT	Aggiornamento e sostituzione Modem 3G → 4GLTE/WW c/o laboratorio	Upgrade and replacement of 3G Modem → 4GLTE/WW by laboratory
S6001-PC-4GWW	85371091	5A991	IT	Controllore pompe con I/O integrato, 4G WW LTE, sistema di programmazione Straton e HMI 7"	Advanced Pump Controller 4G WW LTE with 7" HMI
S6001-RTU-4GWW	85171800	5A991	IT	All-in-one RTU con I/O integrato, modem 4G WW LTE, Straton	Remote Control Unit with built-in IO and 4G WW LTE modem
S6001-RTU-E-4GWW	85171800	5A991	IT	All-in-one RTU con I/O integrato, modem 4G WW LTE, Straton, protocolli Energia	Remote Control Unit with built-in IO, 4G WW LTE, Energy protocols
S604B-6-ETH	90303370	3A002	IT	Analizz. BASIC, Ingresso per TA 1/5A, con Ethernet	Three-phase power meter, BASIC, CT/5A, Ethernet, 1MB log
S604B-6-MOD	90303370	3A002	IT	Analizz. BASIC, Ingresso per TA 1/5A, con RS485	Three phase power meter, BASIC, for CT/5A, Modbus,1MB
S604B-80-MOD	90303370	3A002	IT	Analizz. BASIC, Ingresso diretto 80A, con RS485	Three phase power meter, BASIC, 80A, Modbus,1MB log
S604E-6-ETH	90303370	3A002	IT	Analizzatore Energy PLUS x TA1/5A-Ethernet,8MB log. Arm.	Power Meter Energy PLUS x TA1/5A-Ethernet,8MB log. Harmonics
S604E-6-MOD	90303370	3A002	IT	Analizzatore Energy PLUS x TA1/5A-RS485 Modbus,8MB log. Arm.	Power Meter, Energy PLUS x TA1/5A-RS485 Modbus, 8MB log. Harm.
S604E-80-ETH	90303370	3A002	IT	Analizzatore Energy PLUS 80A-Ethernet,8MB log. Arm.	Power Meter Energy PLUS 80A-Ethernet,8MB log. Harmonics
S604E-80-MOD	90303370	3A002	IT	Analizzatore di Rete Energy PLUS 80A-RS485 Modbus,8MB log. Armoniche	Power Meter, Energy PLUS 80A-RS485 Modbus,8MB log. harmonics
S604E-ROG-ETH-30	90303370	3A002	IT	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 30 cm Øint. 9,5 cm	Kit Energy PLUS Ethernet+ 3 Rog. RC150 L= 30 cm Øint. 9,5 cm
S604E-ROG-ETH-45	90303370	3A002	IT	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 45 cm Øint. 14cm	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 45 cm Øint. 14cm
S604EROGETH45-10	90303370	3A002	IT	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 45 cm Øint. 14cm	Kit Energy PLUS Ethernet+3 Rog. RC150 L= 45 cm Øint. 14cm
S604EROGETH45-5	90303370	3A002	IT	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 45 cm Øint. 14cm	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 45 cm Øint. 14cm
S604E-ROG-ETH-70	90303370	3A002	IT	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 70cm Øint. 22cm	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 70cm Øint. 22cm
S604E-ROG-MOD-30	90303370	3A002	IT	Kit Energy PLUS RS485 Modbus +3 Rog. RC150 L= 30cm Øint.9,5cm	Kit Energy PLUS RS485 Modbus+3 Rog. RC150 L= 30cm Øint.9,5cm
S604E-ROG-MOD-45	90303370	3A002	IT	Kit Energy PLUS RS485 Modbus +3 Rog. RC150 L= 45cm Øint.14cm	Kit Energy PLUS RS485 +3 Rog. RC150 L= 45cm Øint.14cm

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
S604E-ROG-MOD-70	90303370	3A002	IT	Kit Energy PLUS RS485 Modbus +3 Rog. RC150 L= 70cm Øint.22cm	Kit Energy PLUS RS485 Modbus+3 Rog. RC150 L= 70cm Øint.22cm
S711B6MOD	90303370	3A002	IT	Analizzatore Base TA1/5A RS485 1MB 1 DI/ 1 DO LCD	LCD 96x96 BASIC Power Meter, TA1/5A, Modbus, I/O
S711E6ETH	90303370	3A002	IT	Analizzatore Energy Plus TA1/5A ETHERNET 8MB DI/DO LCD	LCD 96x96 Energy PLUS Power Meter, TA1/5A-Eth.,1DI 2DO
S711E6MOD	90303370	3A002	IT	Analizzatore Energy Plus TA1/5A RS485 8MB DI/DO LCD	LCD 96x96 Energy PLUS Power Meter, TA1/5A, Modbus
S711E6MODAO	90303370	3A002	IT	Analizzatore Energy Plus TA1/5A RS485 8MB DI/DO 1AO LCD	LCD 96x96 Energy PLUS Power Meter, TA1/5A, Modbus, AO
S711EROGETH30	90303370	3A002	IT	Analizzatore Energy Plus ETH. 8MB+3ROG L30Ø10CM DI/DO LCD	LCD 96x96 Energy PLUS Kit , Ethernet, N.3 RC150 (30cm)
S711EROGETH45	90303370	3A002	IT	Analizzatore Energy Plus ETH. 8MB+3ROG L45Ø14CM DI/DO LCD	LCD 96x96 Energy PLUS Kit , Ethernet, N.3 RC150 (45cm)
S711EROGETH70	90303370	3A002	IT	Analizzatore Energy Plus ETH. 8MB+3ROG L70Ø22CM DI/DO LCD	LCD 96x96 Energy PLUS Kit, Ethernet, N.3 RC150 (70cm)
S711EROGMOD30	90303370	3A002	IT	Analizzatore Energy Plus RS485 8MB+3ROG L30Ø10CM DI/DO LCD	LCD 96x96 Energy PLUS Kit, Modbus,N.3 RC150 (30cm)
S711EROGMOD30AO	90303370	3A002	IT	Analizzatore Energy Plus 485 8MB+3ROG L30Ø10CM DI/DO/AO LCD	LCD 96x96 Energy PLUS Kit, Modbus AO, Nr.3 RC150 (30cm)
S711EROGMOD45	90303370	3A002	IT	Analizzatore Energy Plus RS485 8MB+3ROG L45Ø14CM DI/DO LCD	LCD 96x96 Energy PLUS Kit, Modbus,N.3 RC150 (45cm)
S711EROGMOD45AO	90303370	3A002	IT	Analizzatore Energy Plus 485 8MB+3ROG L45Ø14CM DI/DO/AO LCD	LCD 96x96 Energy PLUS Kit, Modbus AO, Nr.3 RC150 (45cm)
S711EROGMOD70	90303370	3A002	IT	Analizzatore Energy Plus RS485 8MB+3ROG L70Ø22CM DI/DO LCD	LCD 96x96 Energy PLUS Kit, Modbus,N.3 RC150 (70cm)
S711EROGMOD70AO	90303370	3A002	IT	Analizzatore Energy Plus 485 8MB+3ROG L70Ø22CM DI/DO/AO LCD	LCD 96x96 Energy PLUS Kit, Modbus AO, Nr.3 RC150 (70cm)
S91	85437090	EAR99	IT	Relè multiprotezione per motori, 195 ÷ 255 Vac	Motor multi-protection relay,195 ÷ 255 Vac
S91-400	85437090	EAR99	IT	Relè multiprotezione per motori, 400 Vac ± 10 %	Motor multi-protection relay, 400 Vac ± 10 %
SCAN-FO-MONO-DL	85437090	5A991	IT	Convertitore CAN in fibra monomodale double loop	CAN - single mode fiber, double loop converter
SCAN-FO-MONO-SL	85437090	5A991	IT	Convertitore CAN in fibra monomodale single loop	CAN - single mode fiber, single loop converter
SCAN-FO-MULTI-DL	85437090	5A991	IT	Convertitore CAN in fibra multimodale double loop	CAN - multimode fiber, double loop converter
SCAN-FO-MULTI-SL	85437090	5A991	IT	Convertitore CAN in fibra multimodale single loop	CAN - multimode fiber, single loop converter
SCP	-	2D002	IT	SEMECA Codesys Package	SEMECA Codesys Package
SDD	-	2D002	IT	SENECA Discovery Device, IP scanner per Z-KEY, Z-PASS1/2	Discovery Device, IP scanner for Z-KEY, Z-PASS1/2
S-DIN	85389099	EAR99	IT	Accessorio M-RTU - aggancio per guida DIN in poliammide	M-RTU DIN rail guide support
SEAL	-	2D002	IT	SENECA Advanced language, software prog. avanzata	SENECA Advanced language, programming graphic software
SENECA-SMS	-	2D002	IT	App iOS / Android per gestione remota MYALARM2 e Z-GPRS2	MYALARM2 / Z-GPRS2 App iOS / Android for remote config.
SENECA-TEMP	-	2D002	IT	App iOS MYALARM2 per controllo temperature	MYALARM2 App iOS for temperature control
SESC	-	2D002	IT	SENECA Ethernet to Serial Connection Z-KEY, Z-PASS1/2	Ethernet to Serial Connection tool for Z-KEY, Z-PASS1/2
SETH-FO-MONO-DL	85437090	5A991	IT	Convertitore Ethernet in fibra monomodale double loop	Ethernet - single mode fiber, double loop converter
SETH-FO-MONO-SL	85437090	5A991	IT	Convertitore Ethernet in fibra monomodale single loop	Ethernet - single mode fiber, single loop converter
SETH-FO-MULTI-DL	85437090	5A991	IT	Convertitore Ethernet in fibra multimodale double loop	Ethernet - multimode fiber, double loop converter
SETH-FO-MULTI-SL	85437090	5A991	IT	Convertitore Ethernet in fibra multimodale single loop	Ethernet - multimode fiber, single loop converter
SG-EQ4	85389091	EAR99	IT	Scheda di equalizzazione fino a 4 celle di carico	Connection circuit up to 4 load cell in parallel
SG-EQ4-BOXPG7	85389091	EAR99	IT	Scheda + box di equalizzazione fino a 4 celle di carico	Connection circuit up to 4 load cell + IP67 box
SSD-0-0-0-0	85312040	4A994	IT	HMI touchscreen avanzato con I/O integrati	Advanced touchscreen HMI with integrated I/O
SSD-0-0-0-I	85312040	4A994	IT	HMI touchscreen avanzato con IIoT e I/O integrati	Advanced touchscreen HMI with integrated IIoT and I/O
SSD-0-0-V-0	85312040	4A994	IT	HMI touchscreen avanzato con VPN e I/O integrati	Advanced touchscreen HMI with integrated VPN and I/O
SSD-0-0-V-I	85312040	4A994	IT	HMI touchscreen avanzato con IIoT, VPN e I/O integrati	Advanced touchscreen HMI with integrated IIoT, VPN and I/O
SSD-0-L-0-0	85312040	4A994	IT	HMI touchscreen avanzato con logica e I/O integrati	Advanced touchscreen HMI with integrated logic and I/O
SSD-0-L-0-I	85312040	4A994	IT	HMI touchscreen avanzato con IIoT, logica e I/O integrati	Advanced touchscreen HMI with integrated IIoT, logic and I/O
SSD-0-L-V-0	85312040	4A994	IT	HMI touchscreen avanzato con logica, VPN e I/O integrati	Advanced touchscreen HMI with integrated logic, VPN and I/O

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
SSD-0-L-V-I	85312040	4A994	IT	HMI touchscreen avanzato con IIoT, logica, VPN e I/O integrati	Advanced touchscreen HMI with integrated IIoT, logic, VPN and I/O
SSD-UPG-I	-	2D002	IT	SSD - Upgrade funzioni "IIoT/MQTT/Cloud"	SSD - Upgrade "IIoT/MQTT/Cloud" functions
SSD-UPG-L	-	2D002	IT	SSD - Upgrade funzioni "logica"	SSD - Upgrade "logic" functions
SSD-UPG-L-I	-	2D002	IT	SSD - Upgrade funzioni "logica" e "IIoT/MQTT/Cloud"	SSD - Upgrade "logic" and "IIoT/MQTT/Cloud" functions
SSD-UPG-L-V	-	2D002	IT	SSD - Upgrade funzioni "logica" e "VPN"	SSD - Upgrade "logic" and "VPN" functions
SSD-UPG-L-V-I	-	2D002	IT	SSD - Upgrade funzioni "logica", "VPN" e "IIoT/MQTT/Cloud"	SSD - Upgrade functions "logic", "VPN" and "IIoT/MQTT/Cloud"
SSD-UPG-V	-	2D002	IT	SSD - Upgrade funzioni "VPN"	SSD - Upgrade "VPN" functions
SSD-UPG-V-I	-	2D002	IT	SSD - Upgrade funzioni "VPN" e "IIoT/MQTT/Cloud"	SSD - Upgrade functions "VPN" and "IIoT/MQTT/Cloud".
SSP	-	2D002	IT	Straton SENECA Package - CPU Seneca Installer suite	Straton SENECA Package - CPU Seneca Installer suite
S-TOOL	85235110	EAR99	IT	SENECA-TOOL - Kit di configurazione Z-PROG + Z-SETUP + Librerie Z-4XX-D	Config. toolkit including SW, libraries, CS-JACK-DB9F
STRATON-256-UPD	85238090	2D002	FR	STRATON IDE 256 Tags UPGRADE da V8 a V9	STRATON IDE 256 Tags UPGRADE from V8 to V9
STRATON-512-UPD	85238090	2D002	FR	STRATON IDE 512 Tags UPGRADE da V8 a V9	STRATON IDE 512 Tags UPGRADE from V8 to V9
STRATON-870-850	85235110	EAR99	FR	Lic. IEC 60870-5-101/104 Master / Slave + IEC 61850 Client / Server	IEC 60870-5-101/104 Master / Slave + IEC 61850 Client / Server lic.
STRATON-870M	85235110	EAR99	FR	Licenza attivazione IEC 60870-5-101/104 Master	IEC 60870-5-101/104 Master activation license
STRATON-870S	85235110	EAR99	FR	Licenza attivazione IEC 60870-5-101/104 Slave	IEC 60870-5-101/104 Slave activation license
STRATON-870S-850	85235110	EAR99	FR	Lic. att. IEC 60870-5-101/104 Slave+IEC 61850 Client/Server	IEC 60870-5-101/104 Slave license+IEC 61850 Client/Server
STRATON-D-USB	85235110	EAR99	FR	Straton dongle USB	Straton activation key for IEC 61131 controllers
STRATON-IDE256	85235110	EAR99	FR	Ambiente Straton 256 tag con chiave di attivazione USB	Straton development env. 256 tags, USB activation key
STRATON-IDE512	85235110	EAR99	FR	Ambiente Straton 512 tag con chiave di attivazione USB	Straton development env. 512 tags, USB activation key
STRATON-IDEUN	85235110	EAR99	FR	Straton IDE unlimited tag - ambiente di sviluppo IEC 61131	Straton development env. unlimited tags, USB activ. key
STRATON-UN-UPD	85235110	EAR99	FR	STRATON IDE Unlimited Tags UPGRADE da V8 a V9	STRATON IDE Unlimited Tags UPGRADE from V8 to V9
STRATON-UPGRADE1	-	2D002	FR	Straton upgrade da 256 a 512 tag	Straton upgrade from 256 to 512 tag
STRATON-UPGRADE2	-	2D002	FR	Straton upgrade da 512 a tag illimitati	Straton upgrade from 512 to unlimited tags
STRATON-UPGRADE3	-	2D002	FR	Straton upgrade da 256 a tag illimitati	Straton upgrade from 256 to unlimited tags
STRATON-WB	-	2D002	FR	Straton workbench IEC 61131 free editor	Straton workbench IEC 61131 free editor
T					
T120	85437090	EAR99	IT	Trasmettitore a 2 fili loop powered per Pt100 e Ni100	Pt100/Ni100 to 4-20mA out (non-Isolated)
T120-C	85437090	EAR99	IT	Trasmitt. 2 fili loop powered per Pt100 e Ni100 calibr.	Pt100/Ni100 to 4-20mA out (non-Isolated), configured
T121	85437090	EAR99	IT	Trasmettitore di temperatura universale isolato standard	Universal Input to 4-20mA out (Isolated)
T121-C	85437090	EAR99	IT	Trasmettitore di temperatura univ. isolato calibrato	Universal Input to 4-20mA out (Isolated), configured
T201	85043129	EAR99	IT	Trasduttore di corrente AC 0..40Aac, 8 scale, out 4-20mA, D 12mm, loop powered	AC Current Transd. 5-40 A to 4..20 mA (Loop powered);
T201DC	85043129	EAR99	IT	Trasduttore di corrente DC 0..40Adc, 8 scale, out 4-20mA, D 12mm loop powered (patented technology)	DC Current Transf. 5-40 A to 4..20 mA (Loop powered);
T201DC100	85043129	EAR99	IT	Trasduttore di corrente DC 100 Adc, 8 scale, out 4-20 mA, D 12mm, per loop di corrente 4..20 mA	DC Current Transf 0-100A to to 4..20 mA (Loop powered);
T201DCH	85043129	EAR99	IT	Trasduttore di corrente a effetto Hall 0-25/50A (AC/DC), out 0-10Vdc, D12mm TRMS	AC/DC Current Transf. 0-50 A to 0..10V, Auxiliary Power
T201DCH100	85043129	EAR99	IT	Trasformatore di corrente a effetto Hall 0-50/100A (AC/DC), uscita bipolare 0-10 Vdc, D12mm TRMS	AC/DC CT with Hall effect INP 0-100Aac/dc OUT 0-10Vdc
T201DCH100-LP	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 100 A) a effetto Hall TRMS con uscita 4..20 mA loop powered	AC/DC C.T. (± 100 A), Hall Effect, Loop Powered, 4-20 mA
T201DCH100-M	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 100 A) a effetto Hall TRMS con uscita 0..10V, ModBUS	AC/DC C.T. (± 100 A), Hall Effect, Loop Powered, 0-10V, Modbus
T201DCH100-MU	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 100 Aac/dc) a effetto Hall TRMS con uscita analogica o di allarme, interfaccia ModBUS e USB	AC/DC C.T. (± 100 A), TRMS 0..10V, Pnp alarm, Modbus, USB
T201DCH300	85043129	EAR99	IT	Trasduttore di corrente a effetto Hall 0-150/300A (AC/DC), uscita bipolare 0-10 Vdc, D12mm TRMS	AC/DC CT with Hall effect INP 0-300Aac/dc OUT 0-10Vdc
T201DCH300-LP	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 300 A) a effetto Hall TRMS con uscita 4..20 mA loop powered	AC/DC C.T. (± 300 A), Hall Effect, Loop Powered, 4-20 mA
T201DCH300-M	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 300 A) a effetto Hall TRMS con uscita 0..10V, ModBUS	AC/DC C.T. (± 300 A), Hall Effect, loop Powered, 0-10V, Modbus

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
T201DCH300-MU	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 300 Aac/dc) a effetto Hall TRMS con uscita analogica o di allarme, interfaccia ModBUS e USB	AC/DC C.T. (± 300 A), TRMS 0..10V, Pnp alarm, Modbus, USB
T201DCH50-LP	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 50 A) a effetto Hall TRMS con uscita 4..20 mA loop powered	AC/DC C.T. (± 50 A), Hall Effect, Loop Powered, 4-20 mA
T201DCH50-M	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 50 A) a effetto Hall TRMS con uscita 0..10V, ModBUS	AC/DC C.T. (± 50 A), Hall Effect, Loop Powered, 0-10V, Modbus
T201DCH50-MU	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 50 Aac/dc) a effetto Hall TRMS con uscita analogica o di allarme, interfaccia ModBUS e USB	AC/DC C.T. (± 50 A), TRMS, 0..10V, Pnp alarm, Modbus, USB
T201DCH600-MU	85043129	EAR99	IT	Trasduttore di corrente AC/DC (± 600 Aac/dc) a effetto Hall TRMS con uscita analogica o di allarme, interfaccia ModBUS e USB	AC/DC C.T. (± 600 A), TRMS 0..10V, Pnp alarm, Modbus, USB
T201DCH100-OPEN	85043129	EAR99	IT	Trasduttore di corrente apribile con ingresso fino a 100 Aac/dc uscita 0..10 V	Openable current transducer with input up to 100 Aac/dc output 0..10 V
T201DCH300-OPEN	85043129	EAR99	IT	Trasduttore di corrente apribile con ingresso fino a 300 Aac/dc uscita 0..10 V	Openable current transducer with input up to 300 Aac/dc output 0..10 V
T201DCH600-OPEN	85043129	EAR99	IT	Trasduttore di corrente apribile con ingresso fino a 600 Aac/dc uscita 0..10 V	Openable current transducer with input up to 600 Aac/dc output 0..10 V
T203PM100-MU	90303370	3A002	IT	Analizzatore di rete monofase AC/DC TRMS, 100 Vac/dc, ModBUS, 1AO, 1DO	Single-phase network analyzer AC/DC TRMS, 100 Vac/dc, ModBUS, 1AO, 1DO
T203PM300-MU	90303370	3A002	IT	Analizzatore di rete monofase AC/DC TRMS, 300 Vac/dc, ModBUS, 1AO, 1DO	Single-phase network analyzer AC/DC TRMS, 300 Vac/dc, ModBUS, 1AO, 1DO
T203PM600-MU	90303370	3A002	IT	Analizzatore di rete monofase AC/DC TRMS, 600 Vac/dc, ModBUS, 1AO, 1DO	Single-phase network analyzer AC/DC TRMS, 600 Vac/dc, ModBUS, 1AO, 1DO
TA100	85437090	EAR99	IT	TA per S203T, f.s.100 A, classe 0,1% (1/10000)	CT for S203T, 100A/100mA, 0,1% of accuracy
TA15	85437090	EAR99	IT	TA. per S203T, f.s.15 A, classe 0,1% (1/10000)	CT for S203T, 15A/100mA, 0,1% of accuracy
TA25	85437090	EAR99	IT	TA per S203T, f.s.25 A, classe 0,1% (1/10000)	Current transf. for S203T, 25A/100mA, 0,1% of accuracy
TAAA5-01005-2030	85437090	EAR99	IT	Trasformatore amperometrico apribile 100/5A CL. 0,5 D20X30MM	Split core current transformer 100/5A CL. 0.5 D20X30MM
TAAA5-01505-2030	85437090	EAR99	IT	Trasformatore amperometrico apribile 150/5A CL. 0,5 D20X30MM	Split core current transformer 150/5A CL. 0.5 D20X30MM
TAAA5-02005-2030	85437090	EAR99	IT	Trasformatore amperometrico apribile 200/5A CL. 0,5 D20X30MM	Split core current transformer 200/5A CL. 0.5 D20X30MM
TAAA5-02505-2030	85437090	EAR99	IT	Trasformatore amperometrico apribile 250/5A CL. 0,5 D20X30MM	Split core current transformer 250/5A CL. 0.5 D20X30MM
TAAA5-03005-2030	85437090	EAR99	IT	Trasformatore amperometrico apribile 300/5A CL. 0,5 D20X30MM	Split core current transformer 300/5A CL. 0.5 D20X30MM
TAAA5-04005-2030	85437090	EAR99	IT	Trasformatore amperometrico apribile 400/5A CL. 0,5 D20X30MM	Split core current transformer 400/5A CL. 0.5 D20X30MM
TAAA5-05005-5080	85437090	EAR99	IT	Trasformatore amperometrico apribile 500/5A CL. 0,5 D50X80MM	Split core current transformer 500/5A CL. 0.5 D50X80MM
TAAA5-06005-5080	85437090	EAR99	IT	Trasformatore amperometrico apribile 600/5A CL. 0,5 D50X80MM	Split core current transformer 600/5A CL. 0.5 D50X80MM
TAAA5-07505-5080	85437090	EAR99	IT	Trasformatore amperometrico apribile 750/5A CL. 0,5 D50X80MM	Split core current transformer 750/5A CL. 0.5 D50X80MM
TAAA5-08005-5080	85437090	EAR99	IT	Trasformatore amperometrico apribile 800/5A CL. 0,5 D50X80MM	Split core current transformer 800/5A CL. 0.5 D50X80MM
TAAA5-10005-5080				Trasformatore amperometrico apribile 1000/5A CL. 0,5 D50X80MM	Split core current transformer 1000/5A CL. 0.5 D50X80MM
TAC-C5-00605-023	85437090	EAR99	CN	Trasformatore amperometrico 60/5A CL.0,5 cava $\varnothing 23$ MM	Current Transducer 60/5A CL.0,5 $\varnothing 23$ MM
TAC-C5-01005-023	85437090	EAR99	CN	Trasformatore amperometrico 100/5A CL.0,5 cava $\varnothing 23$ MM	Current Transducer 100/5A CL.0,5 $\varnothing 23$ MM
TAC-C5-01505-023	85437090	EAR99	CN	Trasformatore amperometrico 150/5A CL.0,5 cava $\varnothing 23$ MM	Current Transducer 150/5A CL.0,5 $\varnothing 23$ MM
TAC-C5-02505-023	85437090	EAR99	CN	Trasformatore amperometrico 250/5A CL.0,5 cava $\varnothing 23$ MM	Current Transducer 250/5A CL.0,5 $\varnothing 23$ MM
TAC-C5-04005-037	85437090	EAR99	CN	Trasformatore amperometrico 400/5A CL.0,5 cava $\varnothing 37$ MM	Current Transducer 400/5A CL.0,5 $\varnothing 37$ MM
TAC-C5-06005-037	85437090	EAR99	CN	Trasformatore amperometrico 600/5A CL.0,5 cava $\varnothing 37$ MM	Current Transducer 600/5A CL.0,5 $\varnothing 37$ MM
TAC-C5-08005-037	85437090	EAR99	CN	Trasformatore amperometrico 800/5A CL.0,5 cava $\varnothing 37$ MM	Current Transducer 800/5A CL.0,5 $\varnothing 37$ MM
TAC-C5-10005-037	85437090	EAR99	CN	Trasformatore amperometrico 1000/5A CL.0,5 cava $\varnothing 37$ MM	Current Transducer 1000/5A CL.0,5 $\varnothing 37$ MM
TAC-C5-10005-046	85437090	EAR99	CN	Trasformatore amperometrico 1000/5A CL.0,5 cava $\varnothing 46$ MM	Current Transducer 1000/5A CL.0,5 $\varnothing 46$ MM
TAC-C5-15005-046	85437090	EAR99	CN	Trasformatore amperometrico 1500/5A CL.0,5 cava $\varnothing 46$ MM	Current Transducer 1500/5A CL.0,5 $\varnothing 46$ MM
TAC-C5-15005-062	85437090	EAR99	CN	Trasformatore amperometrico 1500/5A CL.0,5 cava $\varnothing 62$ MM	Current Transducer 1500/5A CL.0,5 $\varnothing 62$ MM
TAC-C5-20005-046	85437090	EAR99	CN	Trasformatore amperometrico 2000/5A CL.0,5 cava $\varnothing 46$ MM	Current Transducer 2000/5A CL.0,5 $\varnothing 46$ MM
TAC-C5-20005-062	85437090	EAR99	CN	Trasformatore amperometrico 2000/5A CL.0,5 cava $\varnothing 62$ MM	Current Transducer 2000/5A CL.0,5 $\varnothing 62$ MM
TAC-C5-25005-062	85437090	EAR99	CN	Trasformatore amperometrico 2500/5A CL.0,5 cava $\varnothing 62$ MM	Current Transducer 2500/5A CL.0,5 $\varnothing 62$ MM
TAC-C5-30005-062	85437090	EAR99	CN	Trasformatore amperometrico 3000/5A CL.0,5 cava $\varnothing 62$ MM	Current Transducer 3000/5A CL.0,5 $\varnothing 62$ MM

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
TAC-C5-40005-062	85437090	EAR99	CN	Trasformatore amperometrico 4000/5A CL.0,5 cava Ø62MM	Current Transducer 4000/5A CL.0,5 Ø62MM
TCK-250-1.5-M12	90251900	EAR99	IT	Termocoppia K , d=1.5 mm, L=100 mm, connettore M12	Thermocouple type K, d=1.5 mm, L=100 mm, M12 connector
TCK-250-3-M12	90251900	EAR99	IT	Termocoppia K , d=3 mm, L=250 mm, attacco connettore M12	Thermocouple type K , d=3 mm, L=250 mm, M12 connector
TCK-AC-M12	90251900	EAR99	IT	Termocoppia tipo K ad archetto, attacco connettore M12	Thermocouple type K, bow type, M12 connector
TCK-W-1000-M12	90251900	EAR99	IT	Termocoppia K, giunto esposto, L=1000 mm, connettore M12	TC type K, joint exposed, L=1000 mm, M12 connector
TEMP-TAG-Z-KEY	-	2D002	IT	Template Excel gestione tag modalità gateway - Z-KEY	Excel template for Z-KEY tags (gateway mode)
TEMP-TAG-Z-PASS	-	2D002	IT	Template Excel gestione tag modalità gateway - Z-PASS1/2	Excel template for Z-PASS-1/2/2S tags (gateway mode)
TEMP-WEB-Z-KEY	-	2D002	IT	Template pagina web Z-KEY	Web page template for Z-KEY
TEST-4	90303100	EAR99	IT	Generatore segnale, misuratore V-mA con simulaz. rampe	V/I handheld multimeter with ramps simulation
TEST-4-C	42021299	EAR99	IT	Valigetta per trasporto e protezione TEST-4	TEST-4 transport and protection case
TEST-4-PK	85389091	EAR99	IT	Precision Kit (set puntali e pinze a cocc.) per Test-4	Precision kit for Test-4
TEST-4-PWR	85044090	EAR99	IT	Alimentatore per Test-4	Test-4 power supply
TEST-4-R	85389091	EAR99	IT	Set puntali di precisione per Test-4	Precision test leads for Test-4
TEST-4-T	-	2D002	IT	Certificato di taratura ISO 9001 per Test-4	ISO 9001 calibration certificate for Test-4
TREND VIEWER	-	2D002	IT	Tool di visualizzazione dati	Data visualization tool
U					
USB-DR-OPC-KEY	85235110	EAR99	IT	Chiave USB per attivazione licenze DR e OPC (ricambio)	USB-key for DR and OPC license activation (spare)
USB-ISO	85437090	EAR99	IT	Isolatore galvanico USB	USB galvanic isolator
USB-SW-KEY	85235110	EAR99	IT	Chiave USB per configurazione di base	USB-key with controllers software, libraries, manuals
UT-M12	90251900	EAR99	IT	Sonda temperatura/umidità relativa, attacco M12	Temperature / Relative Humidity probe, M12 connector
V					
VISUAL11E	85312040	4A994	TW	Terminale HMI touchscreen 9,7", widescreen a colori, doppia interfaccia Ethernet	9,7" HMI widescreen colors, double Ethernet interface
VISUAL12E	85312040	4A994	TW	HMI touchscreen 15" widescreen colori, Eth. (x2), cust. Alluminio	15" HMI widescreen colors, Ethernet (x2) aluminum case
VISUAL1E	85312040	4A994	TW	Terminale HMI touchscreen 4,3" widescreen a colori, interfaccia Ethernet	4,3" HMI widescreen colors, Ethernet interface
VISUAL2E	85312040	4A994	TW	Terminale HMI touchscreen 7" widescreen a colori, interfaccia Ethernet	7" touch screen operator panel, Ethernet
VISUAL3	85312040	4A994	TW	Terminale HMI touchscreen 4,3" widescreen a colori, interfaccia Ethernet	4,3" touch screen operator panel, 480x272, ARM 600 MHz
VISUAL3-FLOW	85312040	4A994	TW	Terminale HMI touchscreen 4,3" widescreen a colori, interfaccia Ethernet, ricambio Flow Computer	4,3" touch screen operator panel, 480x272, ARM 600 MHz, spare parts Flow Computer
VISUAL4	85312040	4A994	TW	Terminale HMI touchscreen 7" widescreen a colori, interfaccia Ethernet	7" touch screen operator panel, 800x480, ARM 600 MHz
VISUAL4ET	85312040	4A994	TW	HMI touchscreen 7" widescreen colori, Eth. cust. alluminio	HMI touchscreen 7" widescreen colors, Eth. aluminum case
VISUAL5-PC	85312040	4A994	IT	Terminale HMI touchscreen 7" 16:9, 64k colori, TFT LCD, interfaccia Ethernet, versione ricambio S6001-PC	7"HMI widescreen 64k colors, Ethernet, S6001-PC spare version
VISUAL5-WB	85312040	4A994	IT	Terminale HMI touchscreen 7" 16:9, 64k colori, TFT LCD, interfaccia Ethernet, versione replica HMI / Web Server, funzione CHROMIUM	7"HMI widescreen 64k colors, Ethernet, HMI / Web Server ver.
VISUAL6E	85312040	4A994	TW	Terminale HMI touchscreen 7" widescreen a colori, doppia interfaccia Ethernet	7" HMI widescreen colors, double Ethernet interface
VISUAL7N	85312040	4A994	TW	Terminale HMI touchscreen 10,1" widescreen a colori, interfaccia Ethernet	10,1"HMI touchscreen 10,1" widescreen colors, Ethernet interface
VISUAL8	85312040	4A994	TW	Terminale HMI touchscreen 10,1" HD, widescreen a colori, interfaccia Ethernet	10,1" HD HMI widescreen colors, Ethernet interface
VISUAL9E	85312040	4A994	TW	Terminale HMI touchscreen 10,1" wide, 1024x600, Ethernet, Wi-Fi	10,1" wide HMI touchscreen, 1024x600, Ethernet, Wi-Fi
VISUALTV	85312040	4A994	TW	Interfaccia TV process	TV Process interface
VISUALWIFI	85312040	4A994	TW	Modulo espansione WiFi per VISUAL8	WiFi Expansion Module for VISUAL9E
VPN-BOX-2	84714100	5A991	EU	PC Box - Server VPN per connessioni simultanee e bassa latenza Poin-To_Point / Single LAN	PC Box - VPN Server for simultaneous connections and low latency Poin-To_Point / Single LAN
VPN-BOX-2-D	-	2D002	IT	Servizio di test su VPN-BOX-2 Point-to-Point valido per 30 gg max 2 device	Test service on VPN-BOX-2 Point-to-Point valid for 30 days max 2 devices
VPN-BOX-2-VM	-	2D002	IT	Macchina Virtuale VPN-BOX-2	VPN-BOX-2 Virtual Machine

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
VPN-BOX-2-VM-D	-	2D002	IT	Macchina Virtuale VPN-BOX-2 Point-to-Point / Single LAN max 2 device	Virtual Machine VPN-BOX-2 Point-to-Point / Single LAN max 2 devices
VPN-CC-2	-	2D002	IT	VPN Client Communicator, software accesso remoto VPN-BOX-2	VPN Client Communicator, remote access software VPN-BOX-2
W					
WEB FACTORY	-	2D002	IT	HMI / Web Editor integrato in Z-NET4	HMI / Web Editor embedded in Z-NET4
Z					
Z102	85437090	EAR99	IT	Convertitore potenziometrico, 24 Vac/dc	Potentiometer to DC Current/Voltage isolator/convertor
Z104	85437090	EAR99	IT	Convertitore V – I / frequenza, 24 Vac/dc	DC V/I to frequency isolator / converter
Z107	85437090	EAR99	IT	Convertitore seriale RS232 – RS485/422 , 24 Vac/dc	DIN rail RS232 - RS485/422 serial converter
Z109PT2-1	85437090	EAR99	IT	Convertitore isolatore da RTD, config. da App/MicroUSB	RTD to DC V/I isolator converter, prog. via MicroUSB/App
Z109REG	85437090	EAR99	IT	Convertitore universale standard, 24 Vac/dc	Analog universal converter with galvanic isolation
Z109REG2-1	85437090	EAR99	IT	Conv. Univ. 10-40 Vdc, 19-28 Vac, prog. da App/microUSB	High perf.universal converter, prog. via MicroUSB/App
Z109REG2-H	85437090	EAR99	IT	Conv. univ. con range esteso, 85-265 Vac/dc	High performance universal converter, 85-265 Vac/dc
Z109REG-BP	85437090	EAR99	IT	Convertitore universale con uscita bipolare V / I	Universal converter with bipolar mA / V output
Z109S	85437090	EAR99	IT	Separatore galvanico per loop 4..20 mA	DC current isolator for 0/4..20mA loops
Z109S-DI	85437090	EAR99	IT	Sep. galvanico per loop di corrente a elevato isolamento	DC wide range current isolator for 0/4..20mA loops
Z109TC2-1	85437090	EAR99	IT	Convertitore da TC, prog. Via Micro USB / App, 24 Vac/dc	TC to DC isolator / converter, prog. via MicroUSB/App
Z109UI2-1	85437090	EAR99	IT	Convertitore mA-V, prog. via MicroUSB/App, 24 Vac/dc	DC current / voltage converter, prog. via Micro USB/App
Z-10-D-IN	85389091	EAR99	IT	Modulo 10 ingressi digitali / RS485 - ModBUS RTU	10-CH Digital Input module / RS485 ModBUS RTU
Z-10-D-OUT	85389091	EAR99	IT	Modulo 10 uscite digitali / RS485 - ModBUS RTU	10-CH Digital Output module / RS485 ModBUS TU
Z110D	85437090	EAR99	IT	Sep. galvanico autoalimentato bicanale per loop 4-20 mA	DC current isolator (self-powered) double channel
Z110S	85437090	EAR99	IT	Sep. galvanico autoalim. monocanale per loop 4-20 mA	DC current isolator (self-powered) single channel
Z111	85437090	EAR99	IT	Convertitore frequenza / V – I, 24 Vac/dc	Frequency to DC isolator / converter
Z112A	85437090	EAR99	IT	Amplificatore per contatti digitali 1 canale	On/Off sensors digital amplifier, single channel
Z112D	85437090	EAR99	IT	Amplificatore per contatti digitali 2 canali	On/Off sensors amplifier, double channel
Z113-1	85437090	EAR99	IT	Doppia soglia allarme con ingresso univ. e uscita a relè	Double threshold with universal analog input
Z170REG-1	85437090	EAR99	IT	Conv. universale, prog. via Micro USB/App, 24 Vac/dc	DC duplicator / isolator prog. Via MicroUSB/App
Z190	85437090	EAR99	IT	Sommatore – sottrattore, 24 Vac/dc	DC Current/Voltage Adder/subtractor
Z201	85437090	EAR99	IT	Convertitore 5-10 Aac / V-I, alim. 10-40 Vdc, 19-28 Vac	AC Current to DC I/V Conv.19..40Vdc - 19..28 Vac
Z201-H	85437090	EAR99	IT	Convertitore 5-10 Aac / V-I, alim. 85-265 Vac/dc	AC Current to DC I/V Isolator/Conv.85..265Vac/dc
Z202	85437090	EAR99	IT	Convertitore 0..500 Vac / V-I, alim. 10-40 Vdc, 19-28 Vac	AC Voltage (500 A);to DC I/V Conv.19..40 Vdc-19..28 Vac
Z202-H	85437090	EAR99	IT	Convertitore 0..500 Vac / V-I, alim. 85-265 Vac/dc	AC Voltage (500 A);to DC I/V Isolator/Conv.85..265Vac/dc
Z202-LP	85437090	EAR99	IT	Conv. 0..500 Vac / V-I, loop powered (5-28 Vdc)	500 VAC- 540 VDC to 4..20 mA Converter, loop pow.
Z203-2	85437090	EAR99	IT	Analizzatore di rete monofase 500 Vac / 5A Micro USB	AC single phase advanced network analyzer, Micro USB port
Z204-1	85437090	EAR99	IT	Convertitore Vac/dc TRMS con uscita analogica e ModBus	AC/DC high voltage converter, analog out, ModBUS RTU
Z-3AO	85389091	EAR99	IT	Modulo 3 uscite analogiche / RS485 - ModBUS RTU	3-CH analog output module / RS485 ModBUS RTU
Z-4AI	85389091	EAR99	IT	Modulo a 4 ingressi analogici V-I / RS485 - ModBUS RTU	4-CH analog input module / RS485 ModBUS RTU
Z-4AI-D	85437090	EAR99	IT	Convertitore A/D 4 ingressi analogici 24 Vac/dc	4-CH analog input DC current-voltage A/D converter
Z-4DI-2AI-2DO	85389091	EAR99	IT	Modulo misto 4DI, 2 AI, 2DO, RS485 - ModBUS RTU	Module with 2 AI, 2 DO, 4 DI, ModBUS RTU
Z-4RTD2	85389091	EAR99	IT	Modulo 4 ingressi RTD / RS485 - ModBUS RTU, isolamento 6 vie, 14 bit	4-CH RTD input module / RS485 ModBUS RTU 6 ways isolation, @14bit
Z-4RTD2-SI	85389091	EAR99	IT	Modulo 4 ingressi RTD / RS485 - ModBUS RTU, isolamento 3 vie, 24 bit	4-CH RTD input module / RS485 ModBUS RTU, 3 ways isolation, @24bit
Z-4TC	85389091	EAR99	IT	Modulo ingressi analogici 4 TC / RS485 - ModBUS RTU	4-CH thermocouple input module / RS485 ModBUS RTU

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
Z-4TC-D	85437090	EAR99	IT	Convertitore A/D 4 termocoppie, 24 Vac/dc	Thermocouples A/D converter
Z-5DI-2DO	85389091	EAR99	IT	Modulo 5 DI 2 DO RS485 - ModBUS RTU	5CH Digital Input - 2CH Digital Output RS485-ModBUS RTU
Z-8AI	85389091	EAR99	IT	Modulo 8 ingressi analogici / RS485 - ModBUS RTU	8-CH analog input module / RS485 ModBUS RTU
Z-8NTC	85389091	EAR99	IT	Modulo 8 ingressi NTC / RS485 ModBUS RTU	8-CH NTC input module / RS485 ModBUS RTU
Z-8R-10A	85389091	5A991	IT	Scheda interfaccia 8 relè 24 Vdc, portata 250 Vac - 10 A	8 relay board with 250 Vac - 10 A
Z-8TC-1	85389091	EAR99	IT	Modulo 8 ingressi da termocoppie ModBUS @14bit	8-CH thermocouple input module @14 bits, ModBUS
Z-8TC-LAB	85389091	EAR99	IT	Modulo 8 ingressi da termocoppie ModBUS @15 bit e morsetti intercambiabili	8-CH thermocouple input module @15 bits, ModBUS interchangeable clamps
Z-8TC-SI	85389091	EAR99	IT	Modulo 8 ingressi da termocoppie ModBUS @24bit	8-CH thermocouple input module @24 bits, ModBUS
Z-8TC-SI-LAB	85389091	EAR99	IT	Modulo 8 ingressi da termocoppie ModBUS @24 bit e morsetti intercambiabili	8-CH thermocouple input module @24 bits, ModBUS interchangeable clamps
Z-AIR-1	85171800	5A991	IT	Radiomodem 868MHz con antenna omnidirettiva, RED, cavo 5 mt	Radiomodem 868MHz with omnidir. antenna, RED compl. 5 mt cable
Z-AIR-1-10M	85171800	5A991	IT	Radiomodem 868MHz con antenna omnidirettiva, RED, cavo 10 mt	Radiomodem 868MHz with omnidir. antenna, RED compl. 10 mt cable
ZC-16DI-8DO	85389091	EAR99	IT	Modulo 16 DI - 8 DO CANopen / ModBUS	16 CH DI / 8 CH DO module / CANopen-RS485 ModBUS RTU
ZC-24DI	85389091	EAR99	IT	Modulo 24 ingressi digitali CANopen / ModBUS	24-CH digital input CANopen / ModBUS
ZC-24DO	85389091	5A991	IT	Modulo 24 uscite digitali CANopen / ModBUS	24-CH digital output CANopen / ModBUS
ZC-3AO	85389091	EAR99	IT	Modulo 3 uscite analogiche (mA, V) CANopen	3-CH analog output (mA, V) CANopen module
ZC-4RTD	85389091	EAR99	IT	Modulo 4 ingressi P100, Ni100, Pt500, Pt1000 / CANopen	4-CH RTD input CANopen module
ZC-8AI	85389091	EAR99	IT	Modulo 8 ingressi analogici (mA, V) CANopen	8-CH analog input (mA, V) CANopen module
ZC-8TC	85389091	EAR99	IT	Modulo 8 ingressi termocoppia (J,K,E,N,S,R,B,T) CANopen	8-CH Thermocouple (J,K,E,N,S,R,B,T) CANopen module
ZC-SG	85389091	EAR99	IT	Modulo 1 ingresso strain gauge CANopen	1-CH strain gauge CANopen module
Z-DAQ-PID	85389091	EAR99	IT	Modulo I/O universale PID / RS485 - ModBUS RTU	1 CH AI / RS485 ModBUS RTU with PID regulation
Z-D-IN	85389091	EAR99	IT	Modulo 5 ingressi digitali / RS485 - ModBUS RTU	5 CH DI module / RS485 ModBUS RTU
Z-D-IO	85389091	EAR99	IT	Modulo di controllo 6 DI, 2 DO / RS485 ModBUS RTU	6 CH DI / 2 CH DO module / RS485 ModBUS RTU
Z-D-OUT	85389091	EAR99	IT	Modulo 5 uscite a relè / RS485 - ModBUS RTU	5 CH DO Relay module / RS485 ModBUS RTU
ZE-2AI	85389091	EAR99	IT	Modulo 2 ingressi analogici, ModBUS RTU / ModBUS TCP-IP	Module with 2 analog inp., ModBUS RTU / ModBUS TCP-IP
ZE-2AI-P	85389091	EAR99	IT	Modulo 2 ingressi analogici, Profinet IO	2-CH Analogue input Profinet IO module
ZE-4DI-2AI-2DO	85389091	EAR99	IT	Modulo misto 2 AI 2 DO, 4 DI, ModBUS RTU / TCP-IP	Module with 2 AI, 2 DO, 4 DI, ModBUS RTU / TCP-IP
ZE-4DI-2AI-2DO-P	85389091	5A991	IT	Modulo misto 2 ingressi analogici, 2 uscite digitali, 4 ingressi digitali, Profinet IO	4-CH Digital Input/ 2-CH Analogue Input, 2-CH Digital Output Profinet IO module
ZE-SG3	85389091	EAR99	IT	Modulo convertitore strain gauge ModBUS RTU / TCP-IP	Strain gauge input ModBUS RTU / TCP-IP module
ZE-SG3-P	85389091	EAR99	IT	Modulo convertitore strain gauge Profinet IO	Strain gauge input Profinet IO module
Z-FLOWCOMPUTER	90268020	4A994	IT	Flow computer per liquidi, gas e vapore, HMI 4,3"	Universal energy & flow computer with 4,3" HMI
Z-FLOWCOMPUTER-B	90268020	4A994	IT	Flow computer per liquidi, gas e vapore	Universal energy & flow computer
Z-GPRS3	85176200	5A991	IT	Datalogger avanzato GSM/GPRS, I/O integrato, all. vocali	Advanced GSM/GPRS datalogger, built-in IO, voice alarm
Z-KEY-0	85176200	5A991	IT	Gateway ModBUS / universale (ModBUS; Profinet, Ethernet/IP), 2 porte seriali, 1 porta Ethernet	ModBUS / universal (ModBUS; Profinet, Ethernet/IP) gateway, 2 serial ports, 1 Ethernet port
Z-KEY-2ETH	85176200	5A991	IT	Gateway ModBUS / universale (ModBUS; Profinet, Ethernet/IP), 2 porte seriali, 2 porte Ethernet	ModBUS / universal (ModBUS; Profinet, Ethernet/IP) gateway, 2 serial ports, 2 Ethernet ports
Z-KEY-2ETH-E	85176200	5A991	IT	Gateway ModBUS → Ethernet/IP (2 porte seriali, 2 porte Ethernet)	ModBUS → Ethernet/IP gateway (2 serial ports, 2 Ethernet ports)
Z-KEY-2ETH-P	85176200	5A991	IT	Gateway ModBUS ↔ Profinet IO (2 porte seriali, 2 porte Ethernet)	ModBUS ↔ Profinet IO gateway (2 serial ports, 2 Ethernet ports)
Z-KEY-MBUS	85176200	5A991	IT	Gateway ModBUS ↔ M-BUS (1 porta M-BUS, 2 porte seriali, 2 porte Ethernet)	ModBUS ↔ M-BUS gateway (1 M-BUS port, 2 serial ports, 2 Ethernet ports)
Z-KEY-P	85176200	5A991	IT	Gateway ModBUS ↔ Profinet IO (2 porte seriali, 1 porta Ethernet)	ModBUS ↔ Profinet IO gateway (2 serial ports, 1 Ethernet port)
Z-KEY-E	85176200	5A991	IT	Gateway ModBUS → Ethernet/IP (2 porte seriali, 1 porta Ethernet)	ModBUS → Ethernet/IP gateway (2 serial ports, 1 Ethernet port)
Z-LINK1-LO	85171800	5A991	IT	Radiomodem 869 Mhz con interfaccia RS232/RS485 con tecnologia LoRa	869 MHz radiomodem with RS232/RS485 interface and LoRa technology
Z-LINK2-LO	85171800	5A991	IT	Wireless LoRa gateway / ripetitore	LoRa wireless gateway / repeater

CODICE Order Code	NC / HS	ECCN	Origine Origin	DESCRIZIONE	DESCRIPTION
Z-LOGGER3	85176200	5A991	IT	Modulo avanzato gestione allarmi, datalogger, webservice	Advanced datalogger, alarm module, web server with built-in IO
Z-LTE-WW	85176200	5A991	IT	Datalogger 4G worldwide con I/O integrato, funzioni di telecontrollo e comandi vocali	4G worldwide datalogger with built-in I/O, remote control functions and voice commands
Z-MBUS	85437090	5A991	IT	Adattatore M-BUS ↔ RS232-RS485	M-BUS ↔ RS232-RS485 adapter
Z-NET3	-	2D002	IT	Software di configurazione sistemi Z-TWS3	Z-TWS3 based system configurator, Web Editor included
Z-NET4	-	2D002	IT	Configuratore sistemi I/O e controller Serie Z-PC	Z-PC system configurator, Web Editor included
Z-PASS1-RT	85176200	5A991	IT	IIoT Edge Gateway, I/O integrati	IIoT Edge Gateway, built-in I/O
Z-PASS2-4GWW-UPG	85176200	5A991	IT	Aggiornamento e sostituzione Modem 3G → 4GLTE/WW c/o laboratorio	Upgrade and replacement of 3G Modem → 4GLTE/WW c/o laboratory
Z-PASS2-S4GWWUPG	85171800	5A991	IT	Aggiornamento e sostituzione Modem 3G → 4GLTE/WW c/o laboratorio (Z-PASS2-S)	Upgrade and replacement of 3G Modem → 4GLTE/WW c/o laboratory (Z-PASS2-S)
Z-PASS2SE4GEUUPG	85176200	5A991	IT	Aggiornamento e sostituzione Modem 3G → 4GLTE/EMEA c/o laboratorio (Z-PASS2-S-E)	3G Modem upgrade and replacement → 4GLTE/EMEA c/o laboratory (Z-PASS2-S-E)
Z-PASS2SE4GWWUPG	85176200	5A991	IT	Aggiornamento e sostituzione Modem 3G → 4GLTE/WW c/o laboratorio (Z-PASS2-S-E)	Upgrade and replacement of 3G Modem → 4GLTE/WW c/o laboratory (Z-PASS2-S-E)
Z-PASS2-RT-4G	85176200	5A991	IT	IIoT Edge Gateway / Router 4G, GPS, I/O integrati	IIoT Edge Gateway / 4G Router, GPS, built-in I/O
Z-PASS2-RT-4G-S	85371091	5A991	IT	Controllore Edge IIoT, 4G, GPS e I/O integrati	Edge IIoT Controller, 4G, GPS, built-in I/O
Z-PASS2-RT-4G-E	85171800	5A991	IT	Controllore Edge IIoT, 4G, prot. Energia, GPS e I/O integrati	Edge IIoT Controller, 4G, energy protocols, GPS, built-in I/O
Z-PC-DIN1-35	85371098	EAR99	IT	Supporto per montaggio rapido su guida DIN 1 slot passo 35 mm	DIN rail bus system 1 slot 35 mm
Z-PC-DIN2-17.5	85371098	EAR99	IT	Supporto per montaggio rapido su guida DIN 2 slot passo 17.5 mm	DIN rail bus system 2 slots 17.5 mm
Z-PC-DIN4-35	85371098	EAR99	IT	Supporto per montaggio rapido su guida DIN 4 slot passo 35 mm	DIN rail bus system 4 slot 35 mm
Z-PC-DIN8-17.5	85371098	EAR99	IT	Supporto per montaggio rapido su guida DIN 8 slot passo 17.5 mm	DIN rail bus system 8 slot 17.5 mm
Z-PC-DINAL1-35	85371098	EAR99	IT	Supporto per montaggio rapido su guida DIN testa + 1 slot passo 35 mm	DIN rail bus system head terminal + 1 slot 35 mm
Z-PC-DINAL2-17.5	85371098	EAR99	IT	Supporto per montaggio rapido su guida DIN testa + 2 slot passo 17.5 mm	DIN rail bus system head terminal + 2 slots 17.5 mm
Z-PC-DINAL2-52.5	85371098	EAR99	IT	Supporto per montaggio rapido su guida DIN testa + 3 slot passo 17.5 mm	DIN rail bus system head terminal + 2 slots 52.5 mm
Z-SG	85371098	EAR99	IT	Modulo convertitore strain gauge / RS485 - ModBUS RTU	Strain gauge module / Analogue out + ModBUS RTU
Z-SG2	85389091	EAR99	IT	Modulo avanzato convertitore strain gauge / RS485 - ModBUS RTU	Advanced strain gauge input module / RS485 ModBUS RTU
Z-SG3	85389091	EAR99	IT	Modulo avanzato convertitore strain gauge / RS485 - ModBUS RTU	Advanced strain gauge input module / RS485 ModBUS RTU
Z-SUPPLY	85044090	EAR99	IT	Alimentatore switching monofase 24V @ 1,5 A	Single-phase switching power supply 24V @ 1.5A
Z-TWS11	84714100	4A994	IT	Controllore multifunzione IEC 61131, embedded PLC Straton con I/O integrato	IEC 61131 multifunction controller, built-in IO, Straton
Z-TWS4-RT-S	84714100	4A994	IT	Controllore Edge IIoT, IEC 61131, I/O integrato, workbench Straton	IEC 61131 IIoT Edge controller, built-in I/O, workbench Straton
Z-TWS4-RT-E	84714100	4A994	IT	Controllore Edge IIoT, IEC 61131, I/O integrato, protocolli Energia	IEC 61131 IIoT Edge controller, built-in I/O, energy protocols

*Questo elenco prodotti, ancorché soggetto a verifiche periodiche, è da ritenersi indicativo, suscettibile di variazioni e non vincolante
This product list, although subject to periodic verification, has to be considered purely indicative and not binding*