

Long terms supplier's declaration for product having preferential origin status

According to regulation EU 2015/2447 annex 22-16

I, the undersigned, hereby declare that the goods listed below (provide description), which are regularly supplied to our customers, originate in the EU and/or comply with the rules of origin for preferential trade with:

AL	Albania	GB	Great Britain	NI	Nicaragua	XK	Kosovo
BA	Bosnia-Erzegovina	GE	Georgia	NO	Norway	XL	Melilla
CA	Canada	GH	Ghana	PA	Panama	XS	Serbia
CAM	Cambodia	GT	Guatemala	PE	Peru	VN	Vietnam
CH	Switzerland	HN	Honduras	PG	Papua Nuova Guinea Occupied Territories	ZA	South Africa
CI	Ivory Coast	IL	Israel	PS	Territories	KR	Korea
CL	Chile	JO	Jordan	SC	Seychelles	UA	Ukraine
CO	Colombia	LB	Lebanon	SN	Singapore	CARIFORUM	
CM	Cameroon	LI	Liechtenstein	SV	El Salvador	ESA COUNTRIES	
CR	Costa Rica	MA	Morocco	TN	Tunisia	SADC COUNTRIES	
DZ	Algeria	MD	Moldova	XC	Ceuta	WPS	
EC	Ecuador	ME	Montenegro				
EG	Egypt	MK	North Macedonia				
FO	Faroe (isole)	MX	Mexico				
IS	Island						

I declare that:

- ☒ cumulation not applied
☐ cumulation applied with

This declaration applies to all shipments of these products dispatched from 01/01/2026 to 31/12/2026. I commit to promptly notifying any changes that render this declaration invalid. I also commit to providing the customs authorities with any additional supporting documents upon request.

Padova, 15.12.2025

Pierluigi Egidi
 Managing Director

SENECA S.R.L.
 Via Austria 26 - 35127 Padova
 Tel. 049 8705359 Fax 049 8706287
 C.F.-P.IVA 02536650282

Product list attached to the long term declaration

Order code	NC / HS	Origin	Description
A-169DV12	85291069	IT	169MHz antenna, dip. vertical lambda/2, BNC M, 5 mt cable
A-169DV12-10	85291069	IT	169MHz antenna, dip. vertical lambda/2, BNC M, 10 mt cable
A-169DV12-5	85291069	IT	169MHz vertical dipole antenna lambda/5mt cable+BNC+stem
A-169DV14	85291069	IT	169MHz antenna, stylus vert.lambda/4, BNC M, L=450mm
A-169DV16	85291069	IT	169MHz antenna, ¼ lambda, length 45 cm, + BNC M
A-169YAGI	85291069	IT	169MHz antenna, 3-element Yagi, BNC M, 10 m cable
A-DIN-T201	85389099	IT	Plastic DIN rail mount for T201 Series
A-GPS	85291069	SK	External GPS antenna with MMCX magnetic base, 3 mt cable
A-GPS-SMA	85291069	SK	GPS antenna with SMA mount
A-GSM	85291069	SK	External GSM dual band swing antenna 3.2 m cable
A-GSM-DIR-5M	85291069	IT	GSM-DECT-UMTS triband directional antenna SMA-M,cable 5 mt
A-GSM-MG	85291069	SK	External magnetic dual band antenna SMA cable 2,5 mt
A-GSM-OMNIDIR	85291069	IT	Omnidir antenna. GSM-UMTS-WIFI, 5.1 dB, SMA-M cable 5 mt
A-GSM-OMNIDIR-10	85291069	IT	Omnidir antenna GSM-UMTS-WIFI, 5.1 dB, SMA-M cable 10 mt
A-GSM-OMNIDIR-12	85291065	IT	Omnidir antenna WI FI- LTE 5.1dB 12mt cable SMA M
A-GSM-QUAD-N	85291069	SK	External omnidir antenna 4G/WI-FI, FME, 5 mt cable
ALIM-MY2	85044095	IT	230 V / 12 V power supply for MYALARM2 and R-KEY-LT
ALIM-USB-1A	85044095	IT	5V 1A stabilized power supply with USB-A port
ANT-WIFI-MP	85291069	IT	WiFi antenna 2.4/5 GHz "Blade", black, SMA-Mo
A-LTE-MG	85291065	SK	Magnetic antenna LTE/4G cable 3mt SMA M
A-MB-MG	85291065	SK	Magnetic multiband antenna 3mt cable SMA M 2.2dbi
A-SCR-90	85291069	IT	Antenna/spare part with 90° screw mount SMA connector
B-ALARM	85176200	IT	Remote alarm unit 1DI / 1DO, basic functions
BATT-2S	85076000	IT	Dual lithium battery pack. 3 cells 11.1 V - 14.5 Ah
BATT-GP80	85076000	IT	Replacement battery pack for B-ALARM
BATT-MY2	85076000	IT	Lithium battery pack 3.7V - 1,200mAh for MYALARM2
BATT-S	85076000	IT	Single battery pack lithium, 3 cells 11.1 V - 14.5 Ah
BOX-RTU-IP65	85389000	IT	IP65 box with battery installation support
CE-RJ45-RJ45-C	85444290	IT	Cross-over Ethernet cable (RJ45 / RJ45) 1.5 MT
CE-RJ45-RJ45-R	85444290	IT	Straight Ethernet cable (RJ45 / RJ45) 1.5 MT
C-PLUS2	84433900	IT	Panel printer TTL/USB/RS232 4-7.5Vdc for batch controller
CS-DB9F-CFV10	85444290		RS232 connection cable (DB9F-CFV10) for M-RTU
CS-DB9F-CLAMP	85444290	IT	RS485 serial cable (DB9F / terminals) 1.5 MT - VISUAL/Z-FLOW
CS-DB9F-DB25M	85444290	IT	S21N serial connection cable - FH190-24 impact printer
CS-DB9F-DB9F	85444290	IT	RS232 serial cable (DB9F / DB9F)
CS-DB9F-TIP	85444290	IT	K107B RS232 communication cable (DB9F - ferrules)
CS-DB9F-TIP-V	85444290	IT	RS485 serial cable (DB9F / ferrules) 1.5 MT - VISUAL1/2/3
CS-DB9M-DB9F	85444290	IT	RS232 straight serial cable for prog. (DB9M / DB9F)
CS-DB9M-DB9F-CR	85444290	IT	Firmware serial cable 2mt [DB9M / DB9F) for RTU-LP
CS-DB9M-DB9M	85444290	IT	RS232 serial cable (DB9M / DB9M)
CS-DB9M-MEF-1012	85444290	IT	Z-KEY serial com.cable (DB9M / MEF 10-12) 1.5mt
CS-DB9M-MEF-PH	85444290	IT	Serial com.cable (DB9M / MEF PH) 3 wires 1.5 MT
CS-DB9M-TIP	85444290	IT	RS485 serial cable for radiomodem (DB9M / Struts)
CS-DB9M-TIP-V	85444290	IT	RS485 serial cable (DB9M / test leads) for HMI VISUAL4
CS-JACK-DB9F	85444290	IT	Serial programming cable (Jack / DB9F)
CS-JACK-JACK	85444290	IT	Z109REG2 / Test-3 programming cable (Jack / Jack)
CS-RJ10-AMP	85444290	IT	RJ10 / AMP MODU II 4 F programming cable
CS-RJ10-DB9F	85444290	IT	RS232 Serial Cable (RJ10 / DB9F)
CS-RJ10-DB9M	85444290	IT	Modem Serial Cable (RJ10 / DB9M)
CS-TIP-MEF-PH	85444290	IT	Serial com. cable (Tips / 4 way connector)

Order code	NC / HS	Origin	Description
CU-A-MICROB	85444290	IT	USB-A Micro USB-B 5P Plug Cable (KIT-USB, MY2, Z109REGBP)
CU-A-MICRO-OTG	85444290	IT	Micro USB OTG - USB Type A female adapter cable
CU-A-MINIB-1	85444290	IT	USB-A Mini USB-B 5 P plug cable, 1 mt
CU-A-MINIB-2	85444290	IT	USB-A Mini USB-B 5 P plug cable, 2 mt
DR-02	85235110	IT	2-CH DAQ Software
DR-04	85235110	IT	4-CH DAQ Software
DR-04-PLUS	85235110	IT	4-CH Data Recoder+plus package
DR-08	85235110	IT	8-CH DAQ Software
DR-08-PLUS	85235110	IT	8-CH Data Recoder+plus package
DR-16	85235110	IT	16-CH DAQ Software
DR-16-PLUS	85235110	IT	16-CH Data Recoder+plus package
DR-32	85235110	IT	32-CH DAQ Software
DR-32-PLUS	85235110	IT	32-CH Data Recoder+plus package
DR-64	85235110	IT	64-CH DAQ Software
DR-64-PLUS	85235110	IT	64-CH Data Recoder+plus package
DR-UN	85235110	IT	Unlimited-CH DAQ Software
DR-UN-PLUS	85235110	IT	Unlimited-CH Data Recoder+plus package
DR-UPGRADE	85238090	IT	Data Recorder license upgrade service
EASY-USB	85437090	IT	USB to UART TTL converter with programming software
FD01	85389091	IT	Photodetector "pulsecap" pulse counting, max freq 10 Hz
K107A	85437090	IT	Isolated RS485/RS485 serial amplifier - 24 Vdc power supply
K107B	85437090	IT	Isolated RS232/RS485 serial converter 24 Vdc power supply
K107USB	85437090	IT	USB to RS485 converter
K109LV	85437090	IT	mV to DC Current/Voltage Isolator/Converter
K109PT	85437090	IT	PT100 to DC Current/Voltage Isolator/Converter
K109PT1000	85437090	IT	PT1000 to DC Current/Voltage Isolator/Converter
K109PT-HPC	85437090	IT	PT100 to DC Current/Volt. Isol/Conv. High prec.
K109S	85437090	IT	DC Current/Voltage to DC Current/Voltage Converter
K109TC	85437090	IT	TC to DC Current/Volt. Isolator/Converter-with alarm
K109UI	85437090	IT	DC Current/Volt. to DC Current/Volt. Isolator/Converter
K111	85437090	IT	Isolated dual output frequency trip amplifier
K111-C	85437090	IT	Isolated dual output frequency trip amplifier - config.
K111D	85437090	IT	2-CH frequency divider-repeater with 2 isolated outputs
K111D-C	85437090	IT	2-CH frequency divider-repeater with 2 isolated outputs config.
K112	85437090	IT	Universal digital Coupler/Isolator
K120RTD	85437090	IT	Pt100, Ni100 loop powered converter
K120RTD-C	85437090	IT	Pt100, Ni100 loop powered converter, config.
K121	85437090	IT	Universal isolator converter loop powered
K121-C	85437090	IT	Universal isolator converter loop powered - config.
K-BUS	85371098	DE	Expandable power supply connector, black color
K-BUS-G	85371098	DE	Expandable power supply connector, grey color
K-SUPPLY	85044095	IT	Redundant power supply module for K-Line modules
MSC	90303100	IT	Multifunction bluetooth calibrator
MSC-C	85437090	CN	Multifunction calibrator + display
MSC-D	90303100	IT	Multifunction calibrator with LCD display
MSC-D-LAT	85238090	IT	LAT Accredia calibration certificate – MSC-D
MSC-D-T	85238090	IT	Factory calibration report/service – MSC-D
MSC-LAT	85238090	IT	LAT Accredia calibration certificate – MSC
MSC-PK	85389091	IT	Test lead set for MSC and MSC-D
MSC-POWER	85044095	IT	MSC power supply
MSC-T	85238090	IT	MSC calibration report, MCS-D
MSC-TC-PROBE	85437090	IT	K-type test thermocouple for MSC and MSC-D

Order code	NC / HS	Origin	Description
MSD	85235110		Micro SD memory card with adapter
MY2B-0-0-M-B	85176200	IT	Remote Alarm Unit - basic version, no relay, clamps, blue color
MY2B-0-0-M-B-4X	85176200	IT	Remote Alarm Unit - basic, no relay, clamps, blue, IP66 case
MY2B-0-0-M-G	85176200	IT	Remote Alarm Unit - basic version, no relay, clamps, grey color
MY2B-0-0-M-G-4X	85176200	IT	Remote Alarm Unit - basic, no relay, clamps, grey, IP66 case
MY2BL-0-0-M-B	85176200	IT	Remote Alarm Unit - basic, no relay, clamps, grey, IP66 case
MY2BL-0-0-M-B-4X	85176200	IT	Remote Alarm Unit 4G/LTE, basic, blue, IP66
MY2BL-0-0-M-G	85176200	IT	Remote Alarm Unit 4G/LTE, basic, grey
MY2BL-0-0-M-G-4X	85176200	IT	Remote Alarm Unit 4G/LTE, basic, grey, IP66
MY2BL-R-0-M-B	85176200	IT	Remote Alarm Unit 4G/LTE, basic, relay, blue
MY2BL-R-0-M-B-4X	85176200	IT	Remote Alarm Unit 4G/LTE, basic, relay, blue, IP66
MY2BL-R-0-M-G	85176200	IT	Remote Alarm Unit 4G/LTE, basic, relay, grey
MY2BL-R-0-M-G-4X	85176200	IT	Remote Alarm Unit 4G/LTE, basic, relay, grey, IP66
MY2B-R-0-M-B	85176200	IT	Remote Alarm Unit - basic version, relay, clamps, blue color
MY2B-R-0-M-B-4X	85176200	IT	Remote Alarm Unit - basic, relay, clamps, blue, IP66 case
MY2B-R-0-M-G	85176200	IT	Remote Alarm Unit - basic version, relay, clamps, grey color
MY2B-R-0-M-G-4X	85176200	IT	Remote Alarm Unit - basic, relay, clamps, grey, IP66 case
MY2CEI-016-0-220	85176200	IT	2G Remote Discharge Unit built-in antenna, 220 Vac - 12 Vdc
MY2CEI-016-0-24	85176200	IT	2G Remote Discharge Unit, built-in antenna, 24 Vac - 12 Vdc
MY2CEI-016-A-220	85176200	IT	2G Remote Discharge Unit, A-GSM, 220 Vac - 12 Vdc
MY2CEI-016-A-24	85176200	IT	2G Remote Discharge Unit, A-GSM, 24 Vac - 12 Vdc
MY2CEI-4G-0-220	85176200	IT	4G Remote Discharge Unit, built-in antenna, 220 Vac - 12 Vdc
MY2CEI-4G-0-24	85176200	IT	4G Remote Discharge Unit, built-in antenna, 24 Vac - 12 Vdc
MY2CEI-4G-A-220	85176200	IT	4G Remote Discharge Unit, A-GSM, 220 Vac - 12 Vdc
MY2CEI-4G-A-24	85176200	IT	4G Remote Discharge Unit, A-GSM, 24 Vac - 12 Vdc
MY2-CONV24-12	90268020		DC DC converter 24 -> 12 V for MY2, MY3, MYCEI, MYSEAL
MY2G-0-0-M-B	85176200	IT	MyALARM2 - gps version, no relay, clamps, blue color
MY2G-0-0-M-B-4X	85176200	IT	MyALARM2 - gps, no relay, clamps, blue, IP66 case
MY2G-0-0-M-G	85176200	IT	MyALARM2 - gps version, no relay, clamps, grey color
MY2G-0-0-M-G-4X	85176200	IT	MyALARM2 - gps, no relay, clamps, grey, IP66 case
MY2GL-0-0-M-B	85176200	IT	MyALARM2 - gps version, relay, clamps, blue color
MY2GL-0-0-M-B-4X	85176200	IT	MyALARM2 -gps, relay, clamps, blue, IP66 case
MY2GL-0-0-M-G	85176200	IT	MyALARM2 - gps version, relay, clamps, grey color
MY2GL-0-0-M-G-4X	85176200	IT	MyALARM2 - gps, relay, clamps, grey, IP66 case
MY2GL-R-0-M-B	85176200	IT	Remote alarm unit, GPS, 4G/LTE, clamps, blue case
MY2GL-R-0-M-B-4X	85176200	IT	Remote alarm unit, GPS, 4G/LTE, clamps, IP66 blue case
MY2GL-R-0-M-G	85176200	IT	Remote alarm unit, GPS, 4G/LTE, clamps, gray case
MY2GL-R-0-M-G-4X	85176200	IT	Remote alarm unit, GPS, 4G/LTE, clamps, IP66 gray case
MY2G-R-0-M-B	85176200	IT	Remote alarm unit, GPS, 4G/LTE, relays, clamps, blue case
MY2G-R-0-M-B-4X	85176200	IT	Remote alarm unit, GPS, 4G/LTE, relays. clamps, IP66 blue case
MY2G-R-0-M-G	85176200	IT	Remote alarm unit, GPS, 4G/LTE, relays. clamps, gray case
MY2G-R-0-M-G-4X	85176200	IT	Remote alarm unit, GPS, 4G/LTE, relays. clamps, IP66 gray case
MY2-KITIP66	85369095	IT	IP66 ABS kit enclosure for field application
MY2S-0-0-M-B	85176200	IT	Remote alarm unit- security, no relay, clamps, blue color
MY2S-0-0-M-B-4X	85176200	IT	Remote alarm unit - security, no relay, clamps, blue, IP66 case
MY2S-0-0-M-G	85176200	IT	Remote alarm unit - security, no relay, clamps, grey color
MY2S-0-0-M-G-4X	85176200	IT	Remote alarm unit - security, no relay, clamps, grey, IP66 case
MY2SL-0-0-M-B	85176200	IT	Remote alarm unit - security, relay, clamps, blue color
MY2SL-0-0-M-B-4X	85176200	IT	Remote alarm unit -security, relay, clamps, blue, IP66 case
MY2SL-0-0-M-G	85176200	IT	Remote alarm unit - security, relay, clamps, grey color
MY2SL-0-0-M-G-4X	85176200	IT	Remote alarm unit - security, relay, clamps, grey, IP66 case
MY2SL-R-0-M-B	85176200	IT	Remote alarm unit,security audio, 4G/LTE, clamps, blue case

Order code	NC / HS	Origin	Description
MY2SL-R-0-M-B-4X	85176200	IT	Remote alarm unit,security audio, 4G/LTE, clamps, IP66 blue case
MY2SL-R-0-M-G	85176200	IT	Remote alarm unit,security audio,4G/LTE, clamps, gray case
MY2SL-R-0-M-G-4X	85176200	IT	Remote alarm unit,security audio, 4G/LTE, clamps, IP66 gray case
MY2S-R-0-M-B	85176200	IT	Remote alarm unit,security audio,4G/LTE, relays, clamps,blue case
MY2S-R-0-M-B-4X	85176200	IT	Remote alarm unit,security audio, 4G/LTE, relays, clamps, IP66 blue case
MY2S-R-0-M-G	85176200	IT	Remote alarm unit,security audio,4G/LTE, relays, clamps, gray case
MY2S-R-0-M-G-4X	85176200	IT	Remote alarm unit,security audio, 4G/LTE, relays, terminals, IP66 gray case
MY3C-1Y	85238090	IT	12-month MyAlarm3 Cloud Service Renewal
MY3CLOUD-R-0-0-G	85176200	IT	Remote Alarm Unit, Cloud support, relay, grey color
MY3CLOUD-R-0-G-G	85176200	IT	Remote Alarm Unit, Cloud support, relay, GPS, gray color
MY3CL-R-0-0-G	85176200	IT	Remote Alarm Unit,Cloud support, Wi-Fi, relay, gray color
MY3CL-R-0-G-G	85176200	IT	Remote Alarm Unit, 4G/LTE, cloud based, relay, GPS, gray color
MY3W-AIR-R-0-G	85176200	IT	Remote Alarm Unit, Cloud support, relay, Wi-Fi, gray color
MY-PT-150-3	90251900	IT	PT100 handheld transmitter with PT-150-3-M12 probe
MY-PT-150-3R	90251900	IT	PT100 handheld transmitter with PT-150-3R-M12 probe
MY-PT-250-2	90251900	IT	PT100 handheld transmitter with PT-250-2-M12 probe
MY-PT-KIT	90251900	IT	PT100 hand. trans. kit with PT-150-3,PT-250-2, PT-150-3R
MY-TC-250-1.5	90251900	IT	TC hand. Trans. with TCK-250-1,5-M12 and TCK-W-1000-M12
MY-TC-250-3	90251900	IT	TC hand. trans. with TCK-250-3-M12 and TCK-W-1000-M12
MY-TC-AC	90251900	IT	TC hand. Trans. with TCK-AC-M12 and TCK-W-1000-M12
MY-TC-KIT	90251900	IT	TC hand. Trans. Kit with Seneca handled termocouples
MY-UT	90251900	IT	Temp./Relat. Humidity hand. Trans. with UT-M12 probe
NTC-150	90251900		External NTC probe 1.5 m for MyALARM Series
POZZ-100	90259000		Stainless thermowell att.1/2" GM for PT100 L=100mm
POZZ-150	90259000		Stainless thermowell att.1/2" GM for PT100 L=150mm
POZZ-200	90259000		Stainless thermowell att.1/2" GM for PT100 L=200mm
POZZ-250	90259000		Stainless thermowell att.1/2" GM for PT100 L=250mm
POZZ-300	90259000		Stainless thermowell att.1/2" GM for PT100 L=300mm
POZZ-50	90259000		Stainless thermowell att.1/2" GM for PT100 L=50mm
PT100-100	90251900		Pt100 L=100mm 3 wire watertight head att.1/2" G.M.
PT100-100-MA	90251900		Pt100 L=100mm 3 wire watertight head att.1/2" G.M. 4-20 mA
PT100-150	90251900		Pt100 L=150 mm 3 wires watertight head att.1/2" G.M.
PT100-150-MA	90251900		Pt100 L=150 mm 3 wires watertight head att.1/2" G.M. 4-20 mA
PT100-200	90251900		Pt100 L=200 mm 3 wires watertight head att.1/2" G.M.
PT100-200-MA	90251900		Pt100 L=200 mm 3 wires watertight head att.1/2" G.M. 4-20 mA
PT100-250	90251900		Pt100 L=250 mm 3 wires watertight head att.1/2" G.M.
PT100-250-MA	90251900		Pt100 L=250 mm 3 wires watertight head att.1/2" G.M. 4-20 mA
PT100-300	90251900		Pt100 L=300 mm 3 wires watertight head att.1/2" G.M.
PT100-300-MA	90251900		Pt100 L=300 mm 3 wires watertight head att.1/2" G.M. 4-20 mA
PT100-50	90251900		Pt100 L=50 mm 3 wires watertight head att.1/2" G.M.
PT100-50-MA	90251900		Pt100 L=50 mm 3 wires watertight head att.1/2" G.M. 4-20 mA
PT100-A	90251900		Air-ambient thermoresistance IP66 standard
PT100-A-MA	90251900		Air-ambient thermoresistance IP66 4-20 mA output
PT100-SOLAR	90251900		PT100 solar with 25x25x3 mm plate, 3 m cable
PT100-SOLAR-MA	90251900		Photovoltaic module temperature probe, 4-20mA output
PT-150-3-M12	90251900	IT	PT100 class B, d=3 mm, L=150 mm, M12 connection
PT-150-3R-M12	90251900	IT	PT100 class B, d=3 mm, L= 150 mm, therm. tap. M12 connection
PT-250-2-M12	90251900	IT	PT100 class B, d=2 mm, L= 250 mm, M12 connection
R-16DI-8DO	85389091	IT	16-CH DI / 8-CH DO Relay Modbus RTU/TCP-IP (2 ETH) module
R-16DI-8DO-P	85389091	IT	16-CH DI / 8-CH DO Relay Profinet (2 ETH) module
R-2AI-6DIDO	85389091	IT	2-CH AI, 6-CH DI/DO, ModBUS RTU/TCP-IP module

Order code	NC / HS	Origin	Description
R-2AI-6DIDO-P	85389091	IT	2-CH AI, 6-CH DI/DO, Profinet module
R203-2-H	90303900	IT	Three-phase Power Meter, 2xETH, 90-264 Vac, ModBUS RTU/TCP-IP
R203-2-H-E	90303900	IT	Three-phase Power Meter, 2xETH, 90-264 Vac, Ethernet/IP
R203-2-H-P	90303900	IT	Three-phase Power Meter, 2xETH, 90-264 Vac, Profinet IO
R203-2-H-U	90303900	IT	Three-phase Power Meter, 2xETH, 90-264 Vac, OPC UA Server
R203-2-L	90303900	IT	Three-phase Power Meter, 2xETH, 24 Vdc, ModBUS RTU/TCP-IP
R203-2-L-P	90303900	IT	Three-phase Power Meter, 2xETH, 24 Vdc, Profinet IO
R203-2-L-U	90303900	IT	Three-phase Power Meter, 2xETH, 24 Vdc, OPC UA Server
R203-LAT	85238090	IT	LAT Accredia calibration certificate – R203 Series
R203-T	85238090	IT	Factory calibration report/service – R203 Series
R204-2-L	90303900	IT	Three-phase Power Meter, 2xETH, 10-30 Vdc, ModBUS RTU/TCP-IP, UL
R204-2-L-E	90303900	IT	Three-phase Power Meter, 2xETH, 10-30 Vdc, Ethernet/IP, UL
R204-2-L-P	90303900	IT	Three-phase Power Meter, 2xETH, 10-30 Vdc, Profinet IO, UL
R204-2-L-U	90303900	IT	Three-phase Power Meter, 2xETH, 10-30 Vdc, OPC UA Server, UL
R204-LAT	85238090	IT	LAT Accredia calibration certificate – R204 Series
R204-T	85238090	IT	Factory calibration report/service – R204 Series
R-32DIDO-2	85389091	IT	Digital Input/Output Module, 32 Channels, Modbus RTU/TCP-IP - 2 ETH
R-32DIDO-2-P	85389091	IT	Digital Input/Output Module, 32 Channels, Profinet IO (2 ETH)
R-4AO-8DIDO-2	85389091	IT	4-CH Analog Outputs, 8 DI/DO, ModBUS RTU/TCP-IP module
R-4AO-8DIDO-2-P	85389091	IT	4-CH Analog Outputs 8 DI/DO, Profinet module
R-4RTD-8DIDO-2	85389091	IT	4-CH RTD, 8 DI/DO, ModBUS RTU/TCP-IP module
R-4RTD-8DIDO-2-P	85389091	IT	4-CH RTD Module, 8 DI/DO, Profinet module
R-8AI-8DIDO-2	85389091	IT	8-CH AI, 8-CH DI/DO, ModBUS RTU/TCP-IP module
R-8AI-8DIDO-2-P	85389091	IT	8-CH AI, 8-CH DI/DO, Profinet module
R-BT1	85076000	IT	Single Battery Pack
R-BT2	85076000	IT	Double Battery Pack 3.6V
RC150-025-100-10	85437090	IT	Rogowski coil L=25cm, D.int.8cm, 100mV/1KA-50Hz, 10m Cable
RC150-025-100-3M	85437090	IT	Rogowski coil L=25cm, D.int.8cm, 100mV/1KA-50Hz, 3m Cable
RC150-025-100-5M	85437090	IT	Rogowski coil L=25cm, D.int.8cm, 100mV/1KA-50Hz, 5m Cable
RC150-035-100-10	85437090	IT	Rogowski coil L=35cm, D.int.11cm, 100mV/1KA-50Hz, 10m Cable
RC150-035-100-3M	85437090	IT	Rogowski coil L=35cm, D.int.11cm, 100mV/1KA-50Hz, 3m Cable
RC150-035-100-5M	85437090	IT	Rogowski coil L=35cm, D.int.11cm, 100mV/1KA-50Hz, 5m Cable
RC150-040-100-10	85437090	IT	Rogowski coil L=40cm, D.int.12cm, 100mV/1KA-50Hz, 10m Cable
RC150-040-100-3M	85437090	IT	Rogowski coil L=40cm, D.int.12cm, 100mV/1KA-50Hz, 3m Cable
RC150-040-100-5M	85437090	IT	Rogowski coil L=40cm, D.int.12cm, 100mV/1KA-50Hz, 5m Cable
RC150-060-100-10	85437090	IT	Rogowski coil L=60cm, D.int.19cm, 100mV/1KA-50Hz, 10m Cable
RC150-060-100-3M	85437090	IT	Rogowski coil L=60cm, D.int.19cm, 100mV/1KA-50Hz, 3m Cable
RC150-060-100-5M	85437090	IT	Rogowski coil L=60cm, D.int.19cm, 100mV/1KA-50Hz, 5m Cable
RC150-090-100-10	85437090	IT	Rogowski coil L=90cm, D.int.28cm, 100mV/1KA-50Hz, 10m Cable
RC150-090-100-3M	85437090	IT	Rogowski coil L=90cm, D.int.28cm, 100mV/1KA-50Hz, 3m Cable
RC150-090-100-5M	85437090	IT	Rogowski coil L=90cm, D.int.28cm, 100mV/1KA-50Hz, 5m Cable
RC150-120-100-3M	85437090	IT	Rogowski coil L=120cm, D.int.38cm, 100mV/1KA-50Hz, 3m Cable
RC150-120-100-5M	85437090	IT	Rogowski coil L=120cm, D.int.38cm, 100mV/1KA-50Hz, 5m Cable
RC150-180-100-3M	85437090	IT	Rogowski coil L=180cm, D.int.57cm, 100mV/1KA-50Hz, 3m Cable
RC190-030-333-3M	85437090	IT	Rogowski coil L=30cm, D.int.6cm, 333mV/1KA-50Hz, 3m Cable
RC190-030-333-5M	85437090	IT	Rogowski coil L=30cm, D.int.6cm, 333mV/1KA-50Hz, 5m Cable
RC190-035-333-3M	85437090	IT	Rogowski coil L=35cm, D.int.7cm, 333mV/1KA-50Hz, 3m Cable
RC190-060-333-3M	85437090	IT	Rogowski coil L=60cm, D.int.17cm, 333mV/1KA-50Hz, 3m Cable
RC190-090-333-3M	85437090	IT	Rogowski coil L=90cm, D.int.26cm, 333mV/1KA-50Hz, 3m Cable
R-COMM-0-4GWW	85176200	IT	Communication Module with 4GWW Modem
R-COMM-B-4GWW	85176200	IT	Communication Module with Mini UPS and 4GWW Modem
RC-V250-100	85437090	IT	Rogowski coil 100mV/kA - 50/60Hz Ø 65mm

Order code	NC / HS	Origin	Description
RC-V400-050	85437090	IT	Rogowski coil 50mV/kA - 50/60Hz, 2m Cable
RC-V400-100	85437090	IT	Rogowski coil 100mV/kA - 50/60Hz, 2m Cable
RC-V500-100	85437090	IT	Rogowski coil 100mV/kA - 50/60Hz, 2m Cable
R-GWR	85171800	IT	ModBUS Gateway for Wireless Sensors
R-GWR-AF	85171800	IT	Flood Sensor Cable
R-GWR-IP-1	85171800	IT	Industrial LoRa Sensor with Analog/Digital Input
R-GWR-IP-2	85171800	IT	Industrial LoRa Sensor with A/D Input, Double Battery
R-GWR-S-1	85171800	IT	Home Automation LoRa Sensor with A/D Input and Flood Detection
R-KEY-LT	85176200	IT	ModBUS Gateway, 1 Serial Port, 1 Ethernet Port
R-KEY-LT-C	85176200	IT	ModBUS ↔ MQTT (1 Serial Port, 1 Ethernet Port) gateway
R-KEY-LT-E	85176200	IT	ModBUS → Ethernet/IP (1 Serial Port, 1 Ethernet Port) gateway
R-KEY-LT-I	85176200	IT	ModBUS ↔ IEC 61850 (1 Serial Port, 1 Ethernet Port) gateway
R-KEY-LT-P	85176200	IT	ModBUS ↔ Profinet IO (1 Serial Port, 1 Ethernet Port) gateway
R-KEY-LT-U	85176200	IT	ModBUS ↔ OPC UA (1 Serial Port, 1 Ethernet Port) gateway
R-KEY-MBUS	85176200	IT	ModBUS ↔ M-BUS (1 M-BUS Port, 1 Serial Port, 1 Ethernet Port) gateway
RM169-1	85171800	IT	169MHZ Radiomodem, 1DI, 1DO, RS485, BNC F Connector, RED
RM169-1-169DV12	85171800	IT	169MHZ Radiomodem, 1DI, 1DO, RS485, Lambda/2 Dip Antenna, RED
RM169-1-169DV14	85171800	IT	169MHZ Radiomodem, 1DI, 1DO, RS485, Lambda/4 Stick Antenna, RED
RM169-1-169YAGI	85171800	IT	169MHZ Radiomodem, 1DI, 1DO, RS485, Yagi 3-Element Dir. Antenna, RED
RM169-1-DV12-10	85171800	IT	169MHZ Radiomodem, 1DI, 1DO, RS485, Dip Antenna 10m Cable, RED
R-PASS-0-4-0	85176200	IT	IIoT Edge Gateway with 4 Ethernet Ports
R-PASS-0-4-E	85176200	IT	IIoT Edge Controller Straton with Energy Protocols and 4 Ethernet Ports
R-PASS-0-4-S	85176200	IT	IIoT Edge Controller Straton with 4 Ethernet Ports
R-PASS-W-4-0	85176200	IT	IIoT Edge Gateway with Wi-Fi and 4 Ethernet Ports
R-PASS-W-4-E	85176200	IT	IIoT Edge Controller Straton, Wi-Fi, 4 ETH, Energy Protocols
R-PASS-W-4-S	84714100	IT	IIoT Edge Controller Straton with Wi-Fi and 4 Ethernet Ports
R-SG3	85389091	IT	Strain Gauge Modbus TCP-IP / Modbus RTU converter module
R-SG3-P	85389091	IT	Strain Gauge Profinet converter module
RTURADIO-169	85171800	IT	169MHZ Radio RTU, 4DI, 2DO, 1 Counter, 2AO, 2AI, RS485
RTURADIO-169DV12	85171800	IT	169MHZ Radio RTU, 4DI, 2DO, 1 Counter, 2AO, 2AI, RS485
RTURADIO-169DV14	85171800	IT	169MHZ Radio RTU, 4DI, 2DO, 1 Counter, 2AO, 2AI, RS485
RTURADIO-169YAGI	85171800	IT	169MHZ Radio RTU, 4DI, 2DO, 1 Counter, 2AO, 2AI, RS485
RTURADIO-DV12-10	85171800	IT	169MHZ Radio RTU, 4DI, 2DO, 1 Counter, 2AO, 2AI, RS485
S100S-1-ST	85044095	IT	Dual power supply for current loop, 115 / 230 Vac
S107P	85437090	IT	RS232-RS485/422 serial converter (portable)
S107USB	85437090	IT	Portable USB/RS485 serial converter
S109REG-1-ST	85437090	IT	Isolator converter Pt100 / V-I , 115 / 230 Vac
S109REG-1-X7	85437090	IT	V-I / V-I isolator converter input up to 200 Vdc
S109S-1-ST	85437090	IT	Isolator for 4...20 mA loop, 115 / 230 Vac
S112A-1-ST	85437090	IT	On-off amplifier, 1 relay outputs, 115/230 Vac
S112M-1-ST	85437090	IT	On-off amplifier, 5 relay outputs, 115/230 Vac
S112M-23-ST	85437090	IT	Multiple digital contact amplifier, 24 Vac/dc
S117P1	85437090	IT	RS232-TTL-RS485/USB Serial Converter
S170-1-ST	85437090	IT	Signal converter duplicator, alim.115/230 Vac
S201RC-LP	85437090	IT	Loop powered current converter for sens. Rogowski
S203RC-D	90303370	IT	Three-phase network analyzer, 600Vac/1000Arms, Rogowski, LCD
S203TA-D	90303370	IT	Three-phase network analyzer, 600Vac/5Arms, standard TA, LCD
S20ADP	85389091	IT	Input adapter board - standard
S20ADP-CM	85389091	IT	Input adaptor card, modular enclosure
S20ADP-CM-S	85389091	IT	NPN sine pulse square wave adapter card
S20ADP-IP65	85389091	IT	Input adapter card, watertight enclosure
S20N1-1-ST	90268020	IT	Basic batch controller, 115 / 230 Vac power supply

Order code	NC / HS	Origin	Description
S20N1-23-ST	90268020	IT	Basic batch controller, 24 Vac/dc
S20N1EX-1-ST	90268020	IT	Basic batch controller in Eexd housing, 115 / 230 Vac
S20N1EX-23-ST	90268020	IT	Basic batch controller in Eexd enclosure, 24 Vac / dc
S20N1IP65-1-ST	90268020	IT	Basic batch controller in IP65 housing, 115 / 230 Vac
S20N1IP65-23-ST	90268020	IT	Basic batch controller in IP65 enclosure, 24 Vac/dc
S20N1-KIT-1-ST	90268020	IT	External control kit for S20N / S21, 115/230 Vac
S20N1-KIT-23-ST	90268020	IT	External control kit for S20N / S21, 24 Vac/dc
S2000-1-ST	85371091	IT	Computing unit 115/230 Vac
S21N1-1-ST	90268020	IT	Batch controller with advanced functions, 115 / 230 Vac
S21N1-23-ST	90268020	IT	Batch controller with advanced functions, 24 Vac/dc
S21N1EX-1-ST	90268020	IT	Batch controller with advanced functions Eexd, 115 / 230 Vac
S21N1EX-23-ST	90268020	IT	Batch controller with advanced functions Eexd, 24 Vac/dc
S21N1IP65-1-ST	90268020	IT	Batch controller with advanced functions IP65, 115/230 Vac
S21N1IP65-23-ST	90268020	IT	Batch controller with advanced functions IP65, 24 Vac/dc
S232-FO-MONO-DL	85437090	IT	RS232 converter in single-mode fiber double loop
S232-FO-MONO-SL	85437090	IT	RS232 single-mode fiber single loop converter
S232-FO-MULTI-DL	85437090	IT	Multi-drop fiber optic - RS232 double loop converter
S232-FO-MULTI-SL	85437090	IT	Multi-drop fiber optic - RS232 single loop converter
S301-1-R	85312040	IT	4 digit indicator, univ. input, retr.out, 115/230 Vac
S301-1-R-AOC-S	85312040	IT	4-digit indicator, 115/230 Vac, 4 o.c., RS232/RS485
S301-1-R-AR-S	85312040	IT	4-digit indicator, 115/230 Vac, 3 SPDT, RS232/RS485
S301-23-R	85312040	IT	4 digit indicator, univ. input, retr.output, 24 Vac/dc
S301-23-R-AOC-S	85312040	IT	4-digit indicator, 24 Vac/dc, 4 o.c., RS232/RS485
S301-23-R-AR-S	85312040	IT	4-digit indicator, 24 Vac/dc, 3 SPDT, RS232/RS485
S301B-1-R	85312040	IT	4 digit indicator+barg. univ. in, retr. out, 115/230Vac
S301B-1-R-AOC-S	85312040	IT	4-digit indicator+barg. 115/230 Vac, 4 o.c. RS232/RS485
S301B-1-R-AR-S	85312040	IT	4-digit indicator, 115 / 230 Vac, 3 SPDT, RS232/RS485
S301B-23-R	85312040	IT	4 digit indicator + bargraph, power supply 24 Vac/dc
S301B-23-R-AOC-S	85312040	IT	4-digit indicator+barg., 24 Vac/dc, 4 o.c., RS232/RS485
S301B-23-R-AR-S	85312040	IT	4-digit indicator+barg., 24 Vac/dc, 3 SPDT, RS232/RS485
S311A-11-H	85312040	IT	11 digit indicator, universal analog input, 80-265 Vac
S311A-11-H-O	85312040	IT	11 digit indicator, univ. AI, 80-265 Vac, opt. board
S311A-11-L	85312040	IT	11 digit analog input indicator, 10-40 Vdc/19-28 Vac
S311A-11-L-O	85312040	IT	11-digit input indicator, 10-40Vdc/19-28Vac, opt. board
S311A-4-H	85312040	IT	4 digit indicator, universal analog input, 80-265 Vac
S311A-4-H-O	85312040	IT	4 digit indicator, 80-265 Vac, opt. board
S311A-4-L	85312040	IT	4 digit indicator, universal AI, 10-40Vdc/19-28 Vac
S311A-4-L-O	85312040	IT	4-digit indicator, 10-40 Vdc/19-28 Vac, opt. Board
S311A-6-H	85312040	IT	6 digit indicator, universal analog input, 80-265 Vac
S311A-6-H-O	85312040	IT	6 digit indicator, universal AI, 80-265 Vac, opt. board
S311A-6-L	85312040	IT	6 digit indicator, universal AI, 10-40 Vdc/19-28 Vac
S311A-6-L-O	85312040	IT	6 digit indicator, 10-40 Vdc / 19-28 Vac, opt. board
S311A-8-H	85312040	IT	8-digit indicator, universal analog input, 80-265 Vac
S311A-8-H-O	85312040	IT	8-digit indicator, universal AI, 80-265 Vac, opt. board
S311A-8-L	85312040	IT	8-digit indicator, universal AI 0-40 Vdc/19-28 Vac
S311A-8-L-O	85312040	IT	8-digit indicator, 10-40 Vdc/19-28 Vac, opt. board
S311AK-4-L	85312040	IT	4 digit indicator analog input, 10-40 Vdc, 19-28 Vac
S311AK-4-L-IP66	85312040	IT	4 digit indicator analog input 10-40 Vdc/19-28Vac, IP66
S311AK-4-L-IP66D	85312040	IT	4 digit indicator, AI, 10-40 Vdc, 19-28 Vac, IP66 (x2)
S311D-11-H	85312040	IT	11-digit digital input indicator, 80-265 Vac
S311D-11-H-O	85312040	IT	11 digit digital input indicator, 80-265 Vac opt. board
S311D-11-L	85312040	IT	11-digit digital input indicator, 10-40 Vdc / 19-28 Vac

Order code	NC / HS	Origin	Description
S311D-11-L-O	85312040	IT	11-digit dig. input ind., 10-40Vdc/19-28Vac, opt. board
S311D-4-H	85312040	IT	4-digit, digital input indicator, 80-265 Vac
S311D-4-H-O	85312040	IT	4 digit digital input indicator, 80-265 Vac, opt. Board
S311D-4-L	85312040	IT	4-digit digital input indicator, 10-40 Vdc / 19-28 Vac
S311D-4-L-O	85312040	IT	4-digit dig. input ind., 10-40Vdc/19-28Vac, opt. board
S311D-6-H	85312040	IT	6-digit digital input indicator, 80-265 Vac
S311D-6-H-O	85312040	IT	6-digit digital input indicator, 80-265 Vac,opt. Board
S311D-6-L	85312040	IT	6-digit digital input indicator, 10-40 Vdc/19-28 Vac
S311D-6-L-O	85312040	IT	6-digit dig. input ind., 10-40Vdc/19-28Vac, opt. board
S311D-8-H	85312040	IT	8-digit digital input indicator, 80-265 Vac
S311D-8-H-O	85312040	IT	8-digit digital input indicator, 80-265 Vac, opt. board
S311D-8-L	85312040	IT	8-digit digital input indicator, 10-40 Vdc/19-28 Vac
S311D-8-L-O	85312040	IT	8-digit dig. input ind., 10-40Vdc/19-28 Vac, opt. board
S311G-4-H	85312040	IT	Ind. gen. with univ. analog input 4 digits, 80-265 Vac
S311G-4-H-O	85312040	IT	Ind. Gen. with 4-digit univ. AI, 80-265 Vac, option board.
S311G-4-L	85312040	IT	Ind. Gen. with universal AI, 4 digits, 10-40 Vdc / 19-28 Vac
S311G-4-L-O	85312040	IT	Ind. Gen. AI univ. 4 digits, 10-40 Vdc/19-28 Vac, option board
S311OPZ	85389091	IT	S311 family indicator option card
S311-T	90268020	IT	S311 family indicator calibration service
S312A-4-H-4R	85312040	IT	Universal analog indicator with 4-digit display
S312A-4-L-4R	85312040	IT	Universal analog indicator with 4-digit display
S315	85312040	IT	Loop powered indicator, 4..20mA input
S315-IP66	85312040	IT	Loop powered indicator, 4..20mA input
S315-IP66D	85312040	IT	Two loop powered indicators, 4..20mA input
S320A-1-ST	85312040	IT	Ind. 3 ½ digits ing. V-I 2 all.relay, 96x96 mm 115/230 Vac
S320A-23-ST	85312040	IT	Ind. 3 ½ digits, V/I, 2 relays, 96x96, 24 Vac/dc
S320A-23-ST-R	85312040	IT	Ind.3 ½ digits, V/I, 2 relays, 96x96, 24 Vac/dc rit output
S400CL-1-N	85363030	DE	SPD 21Vac/30Vdc C1/2/3/D1 for mA/V/digit. sign with sect.
S400HV-2	85363030	DE	Overvoltage prot. 230Vac type 2, 3 cond.(L,N,PE) no cont. FM
S400HV-2-RIC-SL	85363030	DE	Spare 1L-N/PE plug for S400HV-2, no FMII/T2 contact
S400HV-2-RIC-SN	85363030	DE	N/PE plug replacement for S400HV2 II/T2 335Vac/260Vac/-
S400LV-1-N	85363030	DE	Overvoltage protection 24 VAC/DC, Type III, FM contact, 3F.(L,N,PE)
S400NET-1	85363030	DE	Overvoltage protection C1/2/3 D1,5F BUS LINES, RS232/422/485, LAN
S401-L	85312040	IT	Indicator with Oled display and ModBUS interface
S485-FO-MONO-DL	85437090	IT	RS485 converter in single-mode fiber double loop
S485-FO-MONO-SL	85437090	IT	RS485 single-mode fiber single loop converter
S485-FO-MULTI-DL	85437090	IT	RS485 double loop copper to fiber converter
S485-FO-MULTI-SL	85437090	IT	RS485 single loop copper to fiber converter
S50-1-ST	85044095	IT	Power supply for current loop, 115/230 Vac power supply
S500-MBU	85437090	IT	Optical communication interface - M-Bus
S500-MOD	90289010	IT	Optical communication interface - RS485 Modbus Rtu
S501-40-0	90283011	IT	Energy Counter 40A single phase 2 wires 1 DIN
S501-40-0-MID	90283011	IT	Energy Counter 40A single-phase 2 wires 1 DIN, MID
S501-40-MBU-MID	90283011	IT	Energy Counter 40A single-phase 2 wires 1 DIN, M-Bus, MID
S501-45-MOD-MID	90283011	CN	Energy Counter 40A single-phase 2-wire 1 DIN, Modbus, MID
S502-80-ETH	90283011	IT	Energy Counter 80A single-phase 2 wires 2 DIN, Ethernet
S502-80-MBU	90283011	IT	Energy Counter 80A single-phase 2 wires 2 DIN, M-BUS
S502-80-MID	90283011	IT	Energy Counter 80A single-phase 2 wires 2 DIN, certif. MID
S502-80-MOD	90283011	IT	Energy Counter 80A single-phase 2-wire 2 DIN, RS485 Modbus
S504C6-ETH-MID-N	90283019	IT	Energy Counter 1/5A three-phase 3/4 wire 4 DIN-Ethernet, MID
S504C-6-MBU-MID	90283019	IT	Energy Counter 1/5A three-phase 3/4 wire 4 DIN-MBus, MID
S504C-80-ETH-MID	90283019	IT	Energy Counter 80A three-phase 4-wire 4 DIN-Ethernet, MID

Order code	NC / HS	Origin	Description
S504C-80-MBU-MID	90283019	IT	Energy Counter 80A three-phase 4-wire 4 DIN-M-Bus, MID
S504C-80-MOD-MID	90283019	IT	Energy Counter 80A three-phase 4-wire 4 DIN-RS485, MID
S534-80-CMEST	90283019	IT	Kit energy counter MID 80A three-phase 4-DIN + Modbus interface
S534-TA-CMEST	90283019	IT	Kit energy counter MID CT three-phase 4-DIN + Modbus interface
S534-100-MOD-MID	90283019	CN	Energy Counter 1/5A three-phase 3/4 wire 4 DIN, Modbus, MID
S534-6-MOD-MID	90283019	CN	Energy Counter 80A three-phase 3/4 wire 4 DIN, Modbus, MID
S534-6-MID	90283019	IT	Energy Counter 1/5A three-phase 3/4 wire 4 DIN, MID
S534-80-MID	90283019	IT	Energy Counter 80A three-phase 3/4 wire 4 DIN, MID
S604B-6-ETH	90303370	IT	BASIC analyzer, Input for TA 1/5A, with Ethernet
S604B-6-MOD	90303370	IT	BASIC analyzer, Input for TA 1/5A, with RS485
S604B-80-MOD	90303370	IT	BASIC analyzer, Direct input 80A, with RS485
S604E-6-ETH	90303370	IT	Energy PLUS analyzer x TA1/5A-Ethernet,8MB log. Arm.
S604E-6-MOD	90303370	IT	Energy PLUS analyzer x TA1/5A-RS485 Modbus,8MB log. Arm.
S604E-80-ETH	90303370	IT	Energy PLUS 80A-Ethernet analyzer,8MB log. Arm.
S604E-80-MOD	90303370	IT	Energy PLUS 80A Network Analyzer, Modbus,8MB log. Harmonics
S604E-ROG-ETH-30	90303370	IT	Energy PLUS Ethernet Kit + 3 Rog. RC150 L= 30 cm Dint. 9.5cm
S604E-ROG-ETH-45	90303370	IT	Energy PLUS Ethernet Kit + 3 Rog. RC150 L= 45 cm Dint. 14cm
S604E-ROG-ETH-70	90303370	IT	Kit Energy PLUS Ethernet + 3 Rog. RC150 L= 70cm Dint. 22cm
S604E-ROG-MOD-30	90303370	IT	Energy PLUS Modbus Kit +3 Rog. RC150 L= 30cm Dint.9.5cm
S604E-ROG-MOD-45	90303370	IT	Kit Energy PLUS RS485 Modbus +3 Rog. RC150 L= 45cm Dint.14cm
S604E-ROG-MOD-70	90303370	IT	Kit Energy PLUS RS485 Modbus +3 Rog. RC150 L= 70cm Dint.22cm
S711B6MOD	90303370	IT	Base Analyzer TA1/5A RS485 1MB 1 DI/ 1 DO LCD
S711E6ETH	90303370	IT	Energy Plus Analyzer TA1/5A ETHERNET 8MB DI/ DO LCD
S711E6MOD	90303370	IT	Energy Plus Analyzer TA1/5A RS485 8MB DI/DO LCD
S711E6MODAO	90303370	IT	Energy Plus Analyzer TA1/5A RS485 8MB DI/DO 1AO LCD
S711EROGETH30	90303370	IT	Energy Plus ETH Analyzer. 8MB+3ROG L30Ø10CM DI/DO LCD
S711EROGETH45	90303370	IT	Energy Plus ETH Analyzer. 8MB+3ROG L45Ø14CM DI/DO LCD
S711EROGETH70	90303370	IT	Energy Plus ETH Analyzer. 8MB+3ROG L70Ø22CM DI/DO LCD
S711EROGMOD30	90303370	IT	Energy Plus Analyzer RS485 8MB+3ROG L30Ø10CM DI/DO LCD
S711EROGMOD30AO	90303370	IT	Energy Plus 485 8MB+3ROG L30Ø10CM DI/DO/AO LCD Analyzer
S711EROGMOD45	90303370	IT	Energy Plus Analyzer RS485 8MB+3ROG L45Ø14CM DI/DO LCD
S711EROGMOD70	90303370	IT	Energy Plus Analyzer RS485 8MB+3ROG L70Ø22CM DI/DO LCD
S91	85437090	IT	Multiprotection relay for motors, 195 ÷ 255 Vac
S91-400	85437090	IT	Multiprotection relay for motors, 400 Vac ± 10 %
SCAN-FO-MONO-DL	85437090	IT	Double loop single-mode fiber CAN converter
SCAN-FO-MONO-SL	85437090	IT	CAN converter in single-mode fiber single loop
SCAN-FO-MULTI-DL	85437090	IT	Double loop multimode fiber CAN converter
SCAN-FO-MULTI-SL	85437090	IT	Single loop multimode fiber CAN converter
S-DIN	85389099	IT	M-RTU / RTU-LP accessory - polyamide DIN rail attachment
SETH-FO-MONO-DL	85437090	IT	Ethernet to single-mode fiber double loop converter
SETH-FO-MONO-SL	85437090	IT	Ethernet to single-mode fiber single loop converter
SETH-FO-MULTI-DL	85437090	IT	Ethernet converter to multimode fiber double loop
SETH-FO-MULTI-SL	85437090	IT	Ethernet converter to multimode single loop fiber
SG-EQ4	85389091	IT	Equalization board up to 4 load cells
SG-EQ4-BOXPG7	85389091	IT	Equalization board + box for up to 4 load cells
SSD-0-0-0-0	85312040	IT	Advanced touchscreen HMI with integrated I/O
SSD-0-L-V-I	85312040	IT	Advanced touchscreen HMI, IIoT, logic, VPN, integrated I/O
SSD-E-L-V-I	85312040	IT	Multifunction HMI / IIoT Gateway / IEC 61131-3 controller + IEC 61850/IEC 60870
SSD-S-L-V-I	85312040	IT	Multifunctional HMI / IIoT Gateway / Controller IEC 61131-3
SSD-UPG-I	85238090	IT	SSD - Upgrade "IIoT/MQTT/Cloud" functions
SSD-UPG-L	85238090	IT	SSD - Upgrade "logic" functions
SSD-UPG-L-I	85238090	IT	SSD - Upgrade "logic" + "IIoT/MQTT/Cloud" functions

Order code	NC / HS	Origin	Description
SSD-UPG-L-V	85238090	IT	SSD - Upgrade "logic" + "VPN" functions
SSD-UPG-L-V-I	85238090	IT	SSD - Upgrade "logica, "VPN" + "IIoT/MQTT/Cloud" functions
SSD-UPG-V	85238090	IT	SSD - Upgrade "logic, 'VPN'+ 'IIoT/MQTT/Cloud' functions
SSD-UPG-V-I	85238090	IT	SSD - Upgrade "VPN" + "IIoT/MQTT/Cloud" functions
STRATON-256-UPD	85238090	FR	Straton IDE 256 Tags update from previous version
STRATON-256-UPD2	85238090	FR	Straton IDE 256 Tags update older than 2 versions
STRATON-512-UPD	85238090	FR	Straton IDE 512 Tags update from previous version
STRATON-512-UPD2	85238090	FR	Straton IDE 512 Tags update older than 2 versions
STRATON-870-850	85235110	FR	IEC 60870-5-101/104 M/S+ IEC 61850 C/S License
STRATON-870M	85235110	FR	IEC 60870-5-101/104 Master activation license
STRATON-870S	85235110	FR	IEC 60870-5-101/104 Slave activation license
STRATON-870S-850	85235110	FR	IEC 60870-5-101/104 Slave+IEC 61850 Client/Server activation license
STRATON-D-USB	85235110	FR	Straton USB dongle
STRATON-IDE256	85235110	FR	Straton environment 256 tags with USB activation key
STRATON-IDE512	85235110	FR	Straton 512 tag environment with USB activation key
STRATON-IDEUN	85235110	FR	Straton IDE unlimited tags - IEC 61131 development environment
STRATON-UN-UPD	85235110	FR	Straton IDE Unlimited Tags update from previous version
STRATON-UN-UPD2	85238090	FR	Straton IDE Unlimited Tags update from 2 previous versions
STRATON-UPGRADE1		FR	Straton upgrade from 256 to 512 tags
STRATON-UPGRADE2		FR	Straton upgrade from 256 to unlimited tags
STRATON-UPGRADE3		FR	Straton upgrade from 512 to unlimited tags
T120	85437090	IT	Loop powered 2-wire transmitter for Pt100 and Ni100
T120-C	85437090	IT	Calibrated loop powered 2-wire transmitter for Pt100 and Ni100
T121	85437090	IT	Standard insulated universal temperature transmitter
T121-C	85437090	IT	Univ. temperature transmitter isolated calibrated
T201	85437090	IT	AC current transducer 0..40Aac, 4-20mA, loop powered
T201DC	85437090	IT	DC current transducer 0..40Adc, 4-20mA, loop powered
T201DC100	85437090	IT	Current transducer DC 100 Adc, 4..20mA current loop
T201DCH	85437090	IT	Current transducer 0-25/50A (AC/DC), 0-10Vdc, TRMS
T201DCH100	85437090	IT	AC/DC current transducer (± 100A), 0-10Vdc, TRMS
T201DCH100-LP	85437090	IT	AC/DC current transducer (± 100 A), TRMS, loop powered
T201DCH100-M	85437090	IT	AC/DC current transducer (± 100 A), TRMS, 0..10V, ModBUS
T201DCH100-MU	85437090	IT	AC/DC current transducer (±100 A ac/dc), ModBUS, USB
T201DCH100-OPEN	85043129	IT	Open core current transducer up to 100 Aac/dc, 0..10 V
T201DCH300	85437090	IT	AC/DC current transducer (±300 A), 0-10 Vdc, TRMS
T201DCH300-LP	85437090	IT	AC/DC current transducer (± 300 A), TRMS, loop powered
T201DCH300-M	85437090	IT	AC/DC current transducer (± 300 A), TRMS, 0..10V, ModBUS
T201DCH300-MU	85437090	IT	AC/DC current transducer (±300 A ac/dc), ModBUS, USB
T201DCH300-OPEN	85043129	IT	Open core current transducer up to 300 Aac/dc, 0..10 V
T201DCH50-LP	85437090	IT	AC/DC current transducer (±50 A), TRMS. loop powered
T201DCH50-M	85437090	IT	AC/DC current transducer (± 50 A), TRMS, 0..10V, ModBUS
T201DCH50-MU	85437090	IT	AC/DC current transducer (±50 A ac/dc), ModBUS, USB
T201DCH600-MU	85437090	IT	AC/DC current transducer (±600 Aac/dc), ModBUS, USB
T201DCH600-OPEN	85043129	IT	Open core current transducer up to 600 Aac/dc, 0..10 V
T203PM100-MU	90303370	IT	Single-phase AC/DC TRMS analyzer, 100 Vac/dc, ModBUS, 1AO, 1DO
T203PM300-MU	90303370	IT	Single-phase AC/DC TRMS analyzer, 300 Vac/dc, ModBUS, 1AO, 1DO
T203PM600-MU	90303370	IT	Single-phase AC/DC TRMS analyzer, 600 Vac/dc, ModBUS, 1AO, 1DO
TAA-01005-2030	85437090	IT	Open core current transformer 100/5A CL. 0.5 D20X30mm
TAA-01005-3637	85437090	IT	Open core current transformer 100/5A CL. 0.5 D36X37mm
TAA-01505-2030	85437090	IT	Open core current transformer 150/5A CL. 0.5 D20X30mm
TAA-02005-2030	85437090	IT	Open core current transformer 200/5A CL. 0.5 D20X30mm
TAA-02505-2030	85437090	IT	Open core current transformer 250/5A CL. 0.5 D20X30mm

Order code	NC / HS	Origin	Description
TAA-02505-5080	85437090	IT	Open core current transformer 250/5A CL. 0.5 D50X80mm
TAA-03005-2030	85437090	IT	Open core current transformer 300/5A CL. 0.5 D20X30mm
TAA-04005-2030	85437090	IT	Open core current transformer 400/5A CL. 0.5 D20X30mm
TAA-04005-5080	85437090	IT	Open core current transformer 400/5A CL. 0.5 D50X80mm
TAA-05005-5080	85437090	IT	Open core current transformer 500/5A CL. 0.5 D50X80mm
TAA-05005-8080	85437090	IT	Open core current transformer 500/5A CL. 0.5 D80X80mm
TAA-06005-5080	85437090	IT	Open core current transformer 600/5A CL. 0.5 D50X80mm
TAA-07505-5080	85437090	IT	Open core current transformer 750/5A CL. 0.5 D50X80mm
TAA-08005-5080	85437090	IT	Open core current transformer 800/5A CL. 0.5 D50X80mm
TAA-08005-8080	85437090	IT	Open core current transformer 800/5A CL. 0.5 D80X80mm
TAA-10005-8080	85437090	IT	Open core current transformer 1000/5A CL.0.5 D80X80mm
TAA-12505-80120	85437090	IT	Open core current transformer 1250/5A CL.0.5 D80X120mm
TAC01005-22-3010	85437090	IT	Through-bar current transformer 100/5A CL. 0.5
TAC01005-32-4010	85437090	IT	Through-bar current transformer 100/5A CL.0.5
TAC01505-22-3010	85437090	IT	Through-bar current transformer 150/5A CL. 0.5
TAC-0205-00-0000	85437090	IT	Primary wound current transformer 20/5A CL. 0.5
TAC02505-32-4010	85437090	IT	Through-bar current transformer 250/5A CL. 0.5
TAC-0255-00-0000	85437090	IT	Primary wound current transformer 25/5A CL. 0.5
TAC-0305-00-0000	85437090	IT	Primary wound current transformer 30/5A CL. 0.5
TAC04005-32-4010	85437090	IT	Through-bar current transformer 400/5A CL. 0.5
TAC05005-32-4010	85437090	IT	Through-bar current transformer 500/5A CL. 0.5
TAC-0505-22-3010	85437090	IT	Through-bar current transformer 50/5A CL. 0.5
TAC-0605-22-3010	85437090	IT	Through-bar current transformer 60/5A CL.0.5
TAC08005-32-4010	85437090	IT	Through-bar current transformer 800/5A CL. 0.5
TCK-250-1.5-M12	90251900	IT	Thermocouple K , d=1.5 mm, L=100 mm, M12 connector
TCK-250-3-M12	90251900	IT	Thermocouple K , d=3mm, L=250mm, M12 connector connection
TCK-AC-M12	90251900	IT	Type K thermocouple, bow type, M12 connector connection
TCK-W-1000-M12	90251900	IT	K-type thermocouple, exposed joint, L=1000 mm, M12 connector
TEST-4	90303100	IT	Signal generator, V-mA meter with ramp simulation
TEST-4-C	42021299	IT	TEST-4 transport and protection case
TEST-4-LAT		IT	LAT Accredia calibration certificate – TEST-4
TEST-4-PK	85389091	IT	Precision Kit (set of test leads and cocc. clamps) for Test-4
TEST-4-PWR	85044095	IT	Power supply for Test-4
TEST-4-R	85389091	IT	Precision test lead set for Test-4
TEST-4-T		IT	Calibration certificate for Test-4
UPG-E			Straton Activation for Edge Devices (R-PASS, Z-PASS1/2, SSD)
UPG-S			Straton Activation for Edge Devices (R-PASS, Z-PASS1/2, SSD)
USB-DR-OPC-KEY	90268020	IT	USB key for DR and OPC license activation (replacement)
USB-ISO	85437090	IT	USB galvanic isolator
USB-SW-KEY	85235110	IT	USB key for basic configuration
UT-M12	90251900	IT	Temperature/relative humidity probe, M12 connection
VISUAL11E	85312040	TW	HMI 9.7" XGA TFT Display, 2xETH, 4GB Flash, UL
VISUAL12E	85312040	TW	HMI 15" WVA Display, 2xETH, 4GB Flash, UL
VISUAL1E	85312040	TW	HMI 4.3" TFT Display, 1xETH, 256MB Flash
VISUAL2E	85312040	TW	HMI 7" TFT Display, 1xETH, 256MB Flash
VISUAL3E	85312040	TW	HMI 4.3" TFT Display, 2xETH, 4GB Flash
VISUAL4ET	85312040	TW	HMI 7" WVA Display, 2xETH, 4GB Flash, UL, -20..+55°C
VISUAL5-PC	85312040	IT	HMI 7" TFT Display, 1xETH, 4GB Flash (ver. S6001-PC)
VISUAL5-WB	85312040	IT	HMI 7" TFT Display, 1xETH, 4GB Flash
VISUAL6E	90268020	TW	HMI 7" TFT Display, 2xETH, 4GB Flash, UL
VISUAL7N	85312040	TW	HMI 10.1" WVA Display, 1xETH, 256MB Flash
VISUAL8E	85312040	TW	HMI 10.1" TFT Display, 2xETH, 4GB Flash, UL

Order code	NC / HS	Origin	Description
VISUAL9E	85312040	TW	HMI 10.1" TFT Display, 2xETH, 128MB Flash
VISUALEA	85312040	TW	Remote assistance card for VISUAL HMI Series
VISUALTV	85312040	TW	TV interface
VISUALWIFI	85312040	TW	WiFi expansion module for VISUAL Series
VPN-BOX-2-2Y	84714100	IT	Low-latency Point-to-Point / Single LAN VPN server (2 anni)
VPN-BOX-2-2Y-VM	84714100	IT	VPN-BOX-2 Virtual Machine (2 Years)
VPN-BOX2-UPD1		IT	12-month extension for VPN-BOX-2Y (HW & VM) subscription
Z102	85437090	IT	Potentiometer to DC Current/Voltage isolator/converter
Z104	85437090	IT	DC V/I to frequency isolator / converter
Z107	85437090	IT	DIN rail RS232 - RS485/422 serial converter
Z109PT2-1	85437090	IT	RTD to DC V/I isolator converter, prog. via MicroUSB/App
Z109REG	85437090	IT	Analog universal converter with galvanic isolation
Z109REG2-1	85437090	IT	High perf.universal converter, prog. via MicroUSB/App
Z109REG2-H	85437090	IT	High performance universal converter, 85-265 Vac/dc
Z109REG-BP	85437090	IT	Universal converter with bipolar mA / V output
Z109S	85437090	IT	DC current isolator for 0/4..20mA loops
Z109S-DI	85437090	IT	DC wide range current isolator for 0/4..20mA loops
Z109S-H	85437090	IT	Galvanic isolator for 4–20 mA loop, 90–260 Vac supply
Z109TC2-1	85437090	IT	TC to DC isolator / converter, prog. via MicroUSB/App
Z109UI2-1	85437090	IT	DC current / voltage converter, prog. via Micro USB/App
Z-10-D-IN	85389091	IT	10-CH Digital Input module / RS485 ModBUS RTU
Z-10-D-OUT	85389091	IT	10-CH Digital Output module / RS485 ModBUS TU
Z110DI	85437090	IT	Self-powered galvanic isolator, dual channel, high isolation
Z111	85437090	IT	Frequency to DC isolator / converter
Z112A	85437090	IT	On/Off sensors digital amplifier, single channel
Z112D	85437090	IT	On/Off sensors amplifier, double channel
Z113-1	85437090	IT	Double threshold with universal analog input
Z170REG-1	85437090	IT	DC duplicator / isolator prog. Via MicroUSB/App
Z190	85437090	IT	DC Current/Voltage Adder/subtractor
Z201	85437090	IT	AC Current to DC I/V Conv.19..40Vdc - 19..28 Vac
Z201-H	85437090	IT	AC Current to DC I/V Isolator/Conv.85..265Vac/dc
Z202	85437090	IT	AC Voltage(500 A);to DC I/V Conv.19..40 Vdc-19..28 Vac
Z202-H	85437090	IT	AC Voltage(500 A);to DC I/V Isolator/Conv.85..265Vac/dc
Z202-LP	85437090	IT	500 VAC- 540 VDC to 4..20 mA Converter, loop pow.
Z203-2	85437090	IT	AC single phase advanced network analyzer, Micro USB port
Z204-1	85437090	IT	AC/DC high voltage converter, analog out, ModBUS RTU
Z-3AO	85389091	IT	3-CH analog output module / RS485 ModBUS RTU
Z-4AI	85389091	IT	4-CH analog input module / RS485 ModBUS RTU
Z-4AI-D	85437090	IT	4-CH analog input DC current-voltage A/D converter
Z-4DI-2AI-2DO	85389091	IT	Module with 2 AI, 2 DO, 4 DI, ModBUS RTU
Z-4RTD2	85389091	IT	4-CH RTD input module / RS485 ModBUS RTU 6 ways isolation, @14bit
Z-4RTD2-SI	85389091	IT	4-CH RTD input module / RS485 ModBUS RTU, 3 ways isolation, @24bit
Z-4TC	85389091	IT	4-CH thermocouple input module / RS485 ModBUS RTU
Z-4TC-D	85437090	IT	Thermocouples A/D converter
Z-5DI-2DO	85389091	IT	5CH Digital Input - 2CH Digital Output RS485-ModBUS RTU
Z-8AI	85389091	IT	8-CH analog input module / RS485 ModBUS RTU
Z-8NTC	85389091	IT	8-CH NTC input module / RS485 ModBUS RTU
Z-8R-10A	85389091	IT	8 relay board with 250 Vac - 10 A
Z-8TC-1	85389091	IT	8-CH thermocouple input module @14 bits, ModBUS
Z-8TC-LAB	85389091	IT	8-CH thermocouple input module @15 bits, ModBUS interchangeable clamps
Z-8TC-SI	85389091	IT	8-CH thermocouple input module @24 bits, ModBUS
Z-8TC-SI-LAB	85389091	IT	8-CH thermocouple input module @24 bits, ModBUS interchangeable clamps

Order code	NC / HS	Origin	Description
Z-AIR-1	85171800	IT	Radiomodem 868MHz with omnidir. antenna, RED compl. 5 mt cable
Z-AIR-1-10M	85171800	IT	Radiomodem 868MHz with omnidir. antenna, RED compl. 10 mt cable
ZC-16DI-8DO	85389091	IT	16 CH DI / 8 CH DO module / CANopen-RS485 ModBUS RTU
ZC-24DI	85389091	IT	24-CH digital input CANopen / ModBUS
ZC-24DO	85389091	IT	24-CH digital output CANopen / ModBUS
ZC-3AO	85389091	IT	3-CH analog output (mA, V) CANopen module
ZC-4RTD	85389091	IT	4-CH RTD input CANopen module
ZC-8AI	85389091	IT	8-CH analog input (mA, V) CANopen module
ZC-8TC	85389091	IT	8-CH Thermocouple (J,K,E,N,S,R,B,T) CANopen module
ZC-SG	85389091	IT	1-CH strain gauge CANopen module
Z-DAQ-PID	85389091	IT	1 CH AI / RS485 ModBUS RTU with PID regulation
Z-D-IN	85389091	IT	5 CH DI module / RS485 ModBUS RTU
Z-D-IO	85389091	IT	6 CH DI / 2 CH DO module / RS485 ModBUS RTU
Z-D-OUT	85389091	IT	5 CH DO Relay module / RS485 ModBUS RTU
ZE-2AI	85389091	IT	Module with 2 analog inp., ModBUS RTU / ModBUS TCP-IP
ZE-2AI-P	85389091	IT	2-CH Analogue input Profinet IO module
ZE-4DI-2AI-2DO	85389091	IT	Module with 2 AI, 2 DO, 4 DI, ModBUS RTU / TCP-IP
ZE-4DI-2AI-2DO-P	85389091	IT	4-CH Digital Input/ 2-CH Analogue Input, 2-CH Digital Output Profinet IO module
ZE-SG3	85389091	IT	Strain gauge input ModBUS RTU / TCP-IP module
ZE-SG3-P	85389091	IT	Strain gauge input Profinet module
Z-FLOWCOMPUTER	90268020	IT	Flow computer for liquida, gas and steam, HMI 4,3"
Z-GPRS3-BTT	85076000	IT	Spare battery kit and front label Z-GPRS3
Z-KEY-0	85176200	IT	ModBUS gateway, 2 serial ports, 1 Ethernet port
Z-KEY-2ETH	85176200	IT	ModBUS gateway, 2 serial ports, 2 Ethernet ports
Z-KEY-2ETH-C	85176200	IT	ModBUS ↔ MQTT gateway (2 serial ports, 2 Eth ports)
Z-KEY-2ETH-E	85176200	IT	ModBUS → Ethernet/IP gateway (2 serial ports, 2 Eth ports)
Z-KEY-2ETH-I	85176200	IT	ModBUS ↔ IEC 61850 gateway (2 serial ports, 2 Eth ports)
Z-KEY-2ETH-P	85176200	IT	ModBUS ↔ Profinet IO gateway (2 serial ports, 2 Eth ports)
Z-KEY-2ETH-U	85176200	IT	ModBUS ↔ OPC UA gateway (2 serial ports, 2 Eth ports)
Z-KEY-C	85176200	IT	ModBUS ↔ MQTT gateway (2 serial ports, 1 Eth port)
Z-KEY-E	85176200	IT	ModBUS ↔ Ethernet/IP gateway (2 serial ports, 1 Eth port)
Z-KEY-I	85176200	IT	ModBUS ↔ IEC 61850 gateway (2 serial ports, 1 Eth port)
Z-KEY-MBUS	85176200	IT	ModBUS ↔ M-BUS gateway (1 M-BUS port, 2 serial ports, 2 Eth ports)
Z-KEY-P	85176200	IT	ModBUS ↔ Profinet IO gateway (2 serial ports, 1 Eth port)
Z-KEY-U	85176200	IT	ModBUS gateway ↔ OPC UA (2 serial ports, 1 Eth port)
Z-LINK2-LO	85171800	IT	Wireless LoRa gateway/repeater
Z-LOGGER3	85176200	IT	Alarm management datalogger, datalogger, webserver
Z-LOGGER3-BTT	85076000	IT	Battery replacement kit and front label Z-LOGGER3
Z-LTE-BTT	85076000	IT	Battery replacement kit for Z-LTE
Z-LTE-WW	85176200	IT	4GWW datalogger, built-in I/O, remote control, voice com.
Z-MBUS	85437090	IT	M-BUS ↔ RS232-RS485 adapter
Z-NET4	85235110	IT	Z-PC Line I/O system configurator and controller
Z-PASS1-RT	85176200	IT	IIoT Edge gateway, integrated I/O
Z-PASS2-RT-4G	85176200	IT	IIoT Edge gateway / 4G router, GPS, built-in I/O
Z-PASS2-RT-4G-E	85171800	IT	IIoT Edge controller, 4G, energy prot, GPS, built-in I/O
Z-PASS2-RT-4G-S	85371091	IT	IIoT Edge controller, 4G, integrated GPS built-in I/O
Z-PC-DIN1-35	85371098	IT	Support for quick mounting on DIN rail 1 slot pitch 35mm
Z-PC-DIN2-17.5	85371098	IT	Support for quick mounting on DIN rail 2 slots pitch 17.5 mm
Z-PC-DIN4-35	85371098	IT	Support for quick mounting on DIN rail 4 slots pitch 35mm
Z-PC-DIN8-17.5	85371098	IT	Support for quick mounting on DIN rail 8 slots pitch 17.5 mm
Z-PC-DINAL1-35	85371098	IT	Support DIN rail mounting head + 1 slot pitch 3
Z-PC-DINAL2-17.5	85371098	IT	Support DIN rail mounting head + 1 slot pitch 17.5 mm

Order code	NC / HS	Origin	Description
Z-PC-DINAL2-52.5	85371098	IT	Support DIN rail mounting head + 1 slot pitch 52.5 mm
Z-SG	85389091	IT	Strain gauge / RS485 - ModBUS RTU converter module
Z-SG3	85389091	IT	Advanced strain gauge converter module / ModBUS RTU
Z-SG3-P	85389091	IT	Advanced strain gauge / Profinet converter module
Z-SUPPLY	85044095	IT	Single-phase switching power supply 24V @ 1.5 A
Z-TWS11	84714100	IT	IEC 61131 multifunction controller, Straton, integrated I/O
Z-TWS4-RT-E	84714100	IT	Edge IIoT controller, IEC 61131, I/O, energy protocols
Z-TWS4-RT-S	84714100	IT	Edge IIoT controller, IEC 61131, embedded I/O, Straton